

# Class: SubgraphApi

TheGraph API client for CoW Protocol.

## Constructors

### constructor

•new SubgraphApi (context? ) :[SubgraphApi](#)

Create a new CoW Protocol API instance.

### Parameters

Name	Type	Description
context	Partial <SubgraphApiContext	

Any properties of the SubgraphApiContext may be overridden by passing a PartialSubgraphApiContext.

### Returns

[SubgraphApi](#)

### Defined in

external/cow-sdk/src/subgraph/api.ts:54

## Properties

### API\_NAME

•API\_NAME :string ='CoW Protocol Subgraph'

### Defined in

external/cow-sdk/src/subgraph/api.ts:46

### context

•context :SubgraphApiContext

### Defined in

external/cow-sdk/src/subgraph/api.ts:48

## Methods

### getContextWithOverride

►getContextWithOverride (contextOverride? ) :SubgraphApiContext

Override parts of the context for a specific call.

### Parameters

Name	Type	Description
contextOverride	Partial <SubgraphApiContext	

Override the context for this call only.

### Returns

SubgraphApiContext

The context with the override applied.

## Defined in

external/cow-sdk/src/subgraph/api.ts:129

## getEnvConfigs

►getEnvConfigs (env ):SubgraphApiBaseUrls

Get the base URLs for the given environment.

## Parameters

Name	Type	Description
env	<a href="#">CowEnv</a>	The environment to get the base URLs for.

## Returns

SubgraphApiBaseUrls

The base URLs for the given environment.

## Defined in

external/cow-sdk/src/subgraph/api.ts:138

## getLastDaysVolume

►getLastDaysVolume (days ,contextOverride? ):Promise <LastDaysVolumeQuery

Query the volume over the last N days from TheGraph for the CoW Protocol.

## Parameters

Name	Type	Description
days	number	The number of days to query.
contextOverride	Partial <SubgraphApiContext	Override the context for this call only.

## Returns

Promise <LastDaysVolumeQuery

The volume for the last N days.

## Defined in

external/cow-sdk/src/subgraph/api.ts:77

## getLastHoursVolume

►getLastHoursVolume (hours ,contextOverride? ):Promise <LastHoursVolumeQuery

Query the volume over the last N hours from TheGraph for the CoW Protocol.

## Parameters

Name	Type	Description
hours	number	The number of hours to query.
contextOverride	Partial <SubgraphApiContext	Override the context for this call only.

## Returns

Promise <LastHoursVolumeQuery

The volume for the last N hours.

## Defined in

external/cow-sdk/src/subgraph/api.ts:87

## getTotals

►getTotals (contextOverride? ):Promise <{\_\_typename? :'"Total" ;feesEth? :any ;feesUsd? :any ;orders :any ;settlements :any ;tokens :any ;traders :any ;volumeEth? :any ;volumeUsd? :any }>

Query the totals from TheGraph for the CoW Protocol.

### Parameters

Name	Type	Description
contextOverride	Partial	<SubgraphApiContext

Override the context for this call only.

### Returns

Promise <{\_\_typename? :'"Total" ;feesEth? :any ;feesUsd? :any ;orders :any ;settlements :any ;tokens :any ;traders :any ;volumeEth? :any ;volumeUsd? :any }>

The totals for the CoW Protocol.

### Defined in

external/cow-sdk/src/subgraph/api.ts:66

## runQuery

►runQuery <T

(query ,variables? ,contextOverride? ):Promise <T

Run a query against the CoW Protocol Subgraph.

### Type parameters

Name	T
------	---

### Parameters

Name	Type	Default value	Description
query	string	DocumentNode undefined	GQL query string or DocumentNode.
variables	undefined	Variables undefined	To be passed to the query.
contextOverride	Partial	<SubgraphApiContext	

{ } Override the context for this call only.

### Returns

Promise <T

Results of the query.

Throws

[CowError](#) if the query fails.

### Defined in

external/cow-sdk/src/subgraph/api.ts:102 [Previous](#) [OrderSigningUtils](#) [Next](#) [Twap](#)