

eth_getTransactionByBlockNumberAndIndex

Returns information about a transaction given block number and transaction index position.

Parameters

- blockParameter
 - : (string) [required]
 -] A hexadecimal block number, or one of the tags latest
 - , earliest
 - , pending
 - or finalized
 - . See the [default block parameter](#)
 - .
- warning
 - safe
 - isn't supported. Use finalized
 - instead.
- transaction index position
 - : [required]
 -] A hexadecimal of the integer representing the position in the block.

Returns

A transaction object, or null when no transaction was found. The transaction object will consist of the following keys and their values:

- accessList
 - : [optional]
 -] A list of addresses and storage keys accessed by the transaction. See [access list transactions](#)
 - .
- blockHash
 - : 32 bytes. A hash of the block including this transaction. null
 - when it's pending.
- blockNumber
 - : The number of the block including this transaction. null
 - when it's pending.
- chainID
 - : [optional]
 -] chain ID specifying the network. Returned only for [EIP-1559 transactions](#)
 - .
- from
 - : 20 bytes. The address of the sender.
- gas
 - : Gas provided by the sender.
- gasPrice
 - : Gas price provided by the sender in Wei.
- hash
 - : 32 bytes. The hash of the transaction.
- input
 - : The data sent along with the transaction.
- maxPriorityFeePerGas
 - : [optional]
 -] Maximum fee, in Wei, the sender is willing to pay per gas above the base fee. See [EIP-1559 transactions](#)
 - .
- maxFeePerGas
 - : [optional]
 -] Maximum total fee (base fee + priority fee), in Wei, the sender is willing to pay per gas. See [EIP-1559 transactions](#)
 - .
- nonce
 - : The number of transactions made by the sender prior to this one.
- r
 - : 32 bytes. The ECDSA signature
 - .
- s
 - : 32 bytes. The ECDSA signature

- .
- to
- : 20 bytes. The address of the receiver.null
- when it's a contract creation transaction.
- transactionIndex
- : The transaction's index position in the block, in hexadecimal.null
- when it's pending.
- type
- : The [transaction type](#)
- .
- v
- : The ECDSA recovery ID.
- value
- : The value transferred in Wei.
- yParity
- : [optional
-] Parity (0x0
- for even,0x1
- for odd) of the y-value of [secp256k1](#)
- signature.

Example

Replace YOUR-API-KEY with an API key from your [Infura dashboard](#) .

Request

- cURL
- WSS

```
curl https://scroll-mainnet.infura.io/v3/ \-X POST \-H "Content-Type: application/json" \-d '{"jsonrpc": "2.0", "method": "eth_getTransactionByBlockNumberAndIndex", "params": ["0x5BAD55", "0x0"], "id": 1}' wscat -c wss://scroll-mainnet.infura.io/ws/v3/ -x '{"jsonrpc": "2.0", "method": "eth_getTransactionByBlockNumberAndIndex", "params": ["0x5BAD55", "0x0"], "id": 1}'
```

Response

- JSON

```
{ "id" : 1, "jsonrpc" : "2.0", "result" : { "accessList": [],
"blockHash": "0x1682216b3a937e57aeb8c7fcf64a8851ac9a5dd2407f7a76e01aad1ccc0aee19",
"blockNumber": "0x11dca94", "chainId": "0x1", "from": "0x1f9090aae28b8a3dceadf281b0f12828e676c326", "gas": "0x565f",
"gasPrice": "0xef8230501", "hash": "0x140fc3229057d6a484227cbcae16331f586310f68f2095dbc75b3af53d4874bd",
"input": "0x", "maxFeePerGas": "0xef8230501", "maxPriorityFeePerGas": "0x0", "nonce": "0x63b1f",
"r": "0x483a889fdbe4bcebd02fcef8b0644dd710de2b2b2f36f4762b90738016e5c639",
"s": "0x39efb4a71072e6585223e9e77e63920fa65f3de5091d510667782d4cd34ce0a4",
"to": "0x388c818ca8b9251b393131c08a736a67ccb19297", "transactionIndex": "0xa4", "type": "0x2", "v": "0x1",
"value": "0x12ff2241f48fc83", "yParity": "0x1" } }
```

Last updated on Nov 5, 2024 [Previous eth_getTransactionByBlockHashAndIndex](#) [Next eth_getTransactionByHash](#)