

getaddress-name)

- [getAddresses\(name\[\]\)](#)

Cluster → Address

getAddress(name)

Get the wallet associated to a cluster name. You can pass just the cluster name or also include the wallet name as shown in the 2 examples.

...

```
Copy constclusterAddress_Option1=awaitclusters.getAddress('clusters/');
constclusterAddress_Option2=awaitclusters.getAddress('clusters/main');
```

...

Returns

...

```
Copy { "type":"evm", "address":"0x5755d1dcea21caa687339c305d143e6e78f96adf", "name":"clusters/main", "isVerified":true
}
```

...

getAddresses(name[])

Get the wallets associated to multiple cluster names. You can pass just the cluster name or also include the wallet name.

...

```
Copy constclusterAddresses=awaitclusters.getAddresses([ "clusters/", "clusters/main", "layerzero/", "layerzero/main" ]);
```

...

Returns

...

```
Copy [ { name:"clusters/", type:"evm", address:"0x5755d1dcea21caa687339c305d143e6e78f96adf", isVerified:true }, {
name:"clusters/main", type:"evm", address:"0x5755d1dcea21caa687339c305d143e6e78f96adf", isVerified:true }, {
name:"layerzero/", type:"evm", address:"0xccdead94e8cf17de32044d9701c4f5668ad0bef9", isVerified:true }, {
name:"layerzero/main", type:"evm", address:"0xccdead94e8cf17de32044d9701c4f5668ad0bef9", isVerified:true } ]
```

...

[Previous Address → Cluster](#) [Next Cluster → Metadata](#) Last updated 5 months ago