Testnet upgrade: v0.35

About the v0.35 upgrade

This release adds the Axelar Virtual Machine to the network and adds support for CosmWasm contract creation.

△ This release enables CosmWasm. Contracts created with CosmWasm will requirgovernance proposals to be deployed for the indefinite future. Instructions for2024-February-13 testnet upgrade to axelar-corev0.35.3, valdv0.35.3, and tofndv0.10.1. Release can be foundhere.

Upgrade height12017025 countdown

 \triangle Go v1.21 will be needed to buildaxelard.

Node operators using binaries need to downloadwasmvm v1.3.1 <u>libwasmvm.x86_64.so</u> and add the parent folder toLD_LIBRARY_PATH.

Node operators will need to use the updated osmsprund to prune their nodes.

If using the community node setup scripts, please update to the latest commit onmain first.wasmvm lib will be auto-downloaded to AXELARD_HOME/lib but you'll need to add it to LD_LIBRARY_PATH before running the script. 1. If you're a validator or have delegated to one, please vote for the upgrade proposal via

axelard tx gov vote70 yes --from validator Bash Copy 1. Wait for the proposed upgrade block,12017025 2. . Your node will panic at that block height with a log:{"level":"error","module":"consensus","err":"UPGRADE \"v0.35\" NEEDED at height: 12017025", ...} 3. . Stop your node after chain halt.

pkill -f 'axelard start'

Validators need to also stop vald/tofnd

pkill -f 'vald-start' pkill -f tofnd Bash Copy 1. Backup the state:

cp -r \sim /.axelar_testnet/.core/data \sim /.axelar-lisbon-3-upgrade-0.34/.core/data Bash Copy \triangle Caution: If you backup the entire folder, \sim /.axelar_testnet/.core, that'll also include your private keys (insideconfig andkeyring-file subfolders). That can be dangerous if anyone gets access to your backups. We recommend backing up keys separately when you first create your node, and then excluding them from any data backups. 1. Restart youraxelard 2. node with the newv0.35.3 3. build. 4. If you're a validator also restartvald 5. withv0.35.3 6. andtofnd 7. withv0.10.1 8.

Example using join scripts in axelarate-community git repo:

in axelarate-community repo

git checkout maingit pullKEYRING_PASSWORD = "pw-1" ./scripts/node.sh-n testnet-a v0.35.3# For validators, restart vald/tofnd KEYRING_PASSWORD = "pw-1" TOFND_PASSWORD = "pw-2" ./scripts/validator-tools-host.sh-n testnet-a v0.35.3-g v0.10.1 Bash Copy Edit this page