

Tokens

GET /v1/tokens

Get the Enso supported tokens.

This endpoint includes defi tokens and base, swappable tokens. For more details, see the [position types](#).

Example:

```
curl
-X
'GET' \ 'https://api.enso.finance/api/v1/tokens?chainId=1&page=1' \ -H
'accept: /
```

Try it on [swagger\(opens in a new tab\)](#)

Optional Query Parameters:

Query Param Description chainId The chainId of the positions to return address Address of the token to search for protocolSlug Protocol slug of the defi token, e.g. aave-v2 type Token type, baseToken or defiToken primaryAddress Contract entrypoint for this positions/token. It can be used in the bundler endpoint underlyingTokens Address of the underlying tokens to search for page Page, used for pagination

Response example:

```
{ "meta" : { "total" :
5850 , "lastPage" :
6 , "currentPage" :
1 , "perPage" :
1000 , "prev" :
null , "next" :
2 } , "data" : [ { "chainId" :
1 , "address" :
"0x3Ed3B47Dd13EC9a98b44e6204A523E766B225811" , "type" :
"defi" , "protocolSlug" :
"aave-v2" , "underlyingTokens" : [ "0xdAC17F958D2ee523a2206206994597C13D831ec7" ] } , { "chainId" :
1 , "address" :
"0x9ff58f4fFB29fA2266Ab25e75e2A8b3503311656" , "type" :
"defi" , "protocolSlug" :
"aave-v2" , "underlyingTokens" : [ "0x2260FAC5E5542a773Aa44fBCfE7C193bc2C599" ] } , { "chainId" :
1 , "address" :
"0x030bA81f1c18d280636F32af80b9AAAd02Cf0854e" , "type" :
"defi" , "protocolSlug" :
"aave-v2" , "underlyingTokens" : [ "0xC02aaA39b223FE8D0A0e5C4F27eAD9083C756Cc2" ] } . . .
}
```

[Overview Wallet](#)