

# debug\_traceTransaction

Returns tracing results for the specified transaction.

## Parameters

- transactionHash
- : (string)[required]
- hash of the block to trace.
- Optional tracing options object with the following fields:\* tracer
  - - : (string)[optional]
  - - type of tracer. Supports [callTracer](#)
  - - or [prestateTracer](#)
  - - .
  - - tracerConfig
  - - : (object)[optional]
  - - tracer configuration options:\* onlyTopCall
      - - : (boolean)[optional]
    - - - when true
    - - - , will only trace the primary (top-level) call and not any
    - - - sub-calls. It eliminates the additional processing for each call frame.
    - - timeout
    - - : (string)[optional]
    - - string of decimals numbers to set the timeout. The default is 5 seconds. The maximum
    - - timeout is 10 seconds. Valid units are ns
    - - ,us
    - - ,ms
    - - ,s
    - - . For example, 3s30ms
    - - .

## Returns

Depending on the specified tracer type, returns a [callTracer](#) object or [prestateTracer](#) object.

## Example

### Request

- cURL
- WSS

```
curl https://linea-mainnet.infura.io/v3/ \ -X POST \ -H "Content-Type: application/json" \ -d
'{"method":"debug_traceTransaction","params":
["0x5d3faa9b9605a8fb04d989a79bfe6d3b708bdcfc66048d2fe18ed2dda4a8297c", {"tracer":
"callTracer"}], "id":1, "jsonrpc":"2.0"}' wscat -c wss://linea-goerli.infura.io/ws/v3/ \ -x
'{"method":"debug_traceTransaction","params":
["0x5d3faa9b9605a8fb04d989a79bfe6d3b708bdcfc66048d2fe18ed2dda4a8297c", {"tracer":
"callTracer"}], "id":1, "jsonrpc":"2.0"}'
```

## Result

```
{ "jsonrpc": "2.0", "id": 1, "result": { "from": "0xa5ba45f484bc67fe293cf01f7d92d5ba3514dd42", "gas": "0x5208", "gasUsed":
"0x5208", "input": "0x", "to": "0x45a318273749d6eb00f5f6ca3bc7cd3de26d642a", "type": "CALL", "value":
"0x2ca186f5fda8004" } }
```

Last updated on Apr 19, 2024 [Previous debug\\_traceBlockByNumber](#) [Next eth\\_accounts](#)