

eth_sendRawTransaction

Submits a pre-signed transaction for broadcast to the Ethereum network.

Parameters

transaction data : [Required] The signed transaction data.

Returns

transaction hash : 32 bytes. The transaction hash, or the zero hash if the transaction is not yet available. Use [eth_getTransactionReceipt](#) to get the contract address, after the transaction was mined, when you created a contract.

Example

Replace YOUR-API-KEY with an API key from your [Infura dashboard](#).

Request

- cURL
- WSS

```
[{"url": "https://zkscopy-mainnet.infura.io/v3/YOUR-API-KEY -X POST -H \"Content-Type: application/json\" -d '{\"jsonrpc\": \"2.0\", \"method\": \"eth_sendRawTransaction\", \"params\": [\"0xf869018203ce882520894f1752151ebef6c7334fad080c5704d77216b732881bc16d674ec80000801ba02da1c48b670996dcbb1447ef9e0fb33033c48a4fe938f420bec3e56bfd24071a062e0aa78a81bf01\"]' wscat -c wss://zkscopy-mainnet.infura.io/ws/v3/YOUR-API-KEY -x '{\"jsonrpc\": \"2.0\", \"method\": \"eth_sendRawTransaction\", \"params\": [\"0xf869018203ce882520894f1752151ebef6c7334fad080c5704d77216b732881bc16d674ec80000801ba02da1c48b670996dcbb1447ef9e0fb33033c48a4fe938f420bec3e56bfd24071a062e0aa78a81bf01\"]'"}]
```

Response

- JSON

```
{ "id": 1, "jsonrpc": "2.0", "result": "0xe670ec64341771606e55d6b4ca35a1a6b75ee3d5145a99d05921026d1527331" }
```

Error response

If this call causes the EVM to execute a REVERT operation, an error response of the following form is returned, with the revert reason pre-decoded as a string:

[illegible]

Last updated on Nov 5, 2024 [Previous eth](#) [protocolVersion](#) [Next eth](#) [sendTransaction](#)