

```

D4D4D4;--ch-t-background: #1E1E1E;--ch-t-lighter-
inlineBackground: #1e1e1ee6;--ch-t-editor-background:
#1E1E1E;--ch-t-editor-foreground: #D4D4D4;--ch-t-editor-
rangeHighlightBackground: #ffffff0b;--ch-t-editor-
infoForeground: #3794FF;--ch-t-editor-
selectionBackground: #264F78;--ch-t-focusBorder:
#007FD4;--ch-t-tab-activeBackground: #1E1E1E;--ch-t-
tab-activeForeground: #ffffff;--ch-t-tab-
inactiveBackground: #2D2D2D;--ch-t-tab-
inactiveForeground: #ffffff80;--ch-t-tab-border: #252526;--
ch-t-tab-activeBorder: #1E1E1E;--ch-t-editorGroup-
border: #444444;--ch-t-editorGroupHeader-
tabsBackground: #252526;--ch-t-editorLineNumber-
foreground: #858585;--ch-t-input-background: #3C3C3C;-
-ch-t-input-foreground: #D4D4D4;--ch-t-icon-foreground:
#C5C5C5;--ch-t-sideBar-background: #252526;--ch-t-
sideBar-foreground: #D4D4D4;--ch-t-sideBar-border:
#252526;--ch-t-list-activeSelectionBackground: #094771;--
ch-t-list-activeSelectionForeground: #ffffffe;--ch-t-list-
hoverBackground: #2A2D2E; }

```

Migrate to v2

This guide references the major changes between v1 and v2 to help those migrating an existing app.

Note: When upgrading toprotocol-kit v2, it's necessary to upgrade tosafe-core-sdk-types v3.

MasterCopy to Singleton

To avoid confusion between terms used as synonyms, we aligned all our code to use the wordsingleton .

- RenameisL1SafeMasterCopy
- toisL1SafeSingleton

```

_10 // old: _10 SafeFactory.create({ ethAdapter, isL1SafeMasterCopy: true }) _10 _10 // new: _10 SafeFactory.create({
ethAdapter, isL1SafeSingleton: true })

```

Ethers v6

FromprotocolKit v2 ,EthersAdapter will only be compatible with ethers.js v6. If you still need to use v5, we recommend you keepprotocolKit v1 , but we encourage you to migrate to the latest version when you can.

Protocol Kit createTransaction() accepts only transaction array

InprotocolKit v1 , thecreateTransaction() method accepted either an object or an array as a parameter. To avoid confusion, we changed it to accept only an array. Here is a migration example:

```
_24 // old: _24 const safeTransactionData = { _24 to: ", _24 data: ", _24 value: ", _24 nonce: ", _24 safeTxGas: " _24 } _24
const safeTransaction = protocolKit.createTransaction({ safeTransactionData }) _24 _24 // new: _24 const
safeTransactionData = { _24 to: ", _24 data: ", _24 value: " _24 } _24 const options = { _24 nonce: ", _24 safeTxGas: " _24 }
_24 const safeTransaction = protocolKit.createTransaction({ _24 transactions: [safeTransactionData], _24 options _24 })
```

[Migrate to v1](#) [Migrate to v3](#)

Was this page helpful?

[Report issue](#)