

# Cluster → Address

Get address

GET /v0.1/address/:name

GET /v0.1/address/:name/:addressName

Get the wallet associated to a cluster name. You can pass just the cluster name or also include the address name as shown in the 2 examples.

Name Description name Name of the cluster addressName (optional) Address name of the cluster Example

...

Copy <https://api.clusters.xyz/v0.1/address/clusters> <https://api.clusters.xyz/v0.1/address/clusters/main>

...

Response

200 404 ``

Copy { "type": "evm", "address": "0x5755d1dcea21caa687339c305d143e6e78f96adf", "name": "clusters/main", "isVerified": true }  
}

Copy null

...

Bulk get addresses

POST /v0.1/address/names

Get the wallets associated to a cluster name. You can pass just the cluster name or also include the address name.

Name Description POSTbody Array of cluster names (with or without address name) Example

...

Copy `curl-XPOST 'https://api.clusters.xyz/v0.1/address/names' --data-raw '[ "clusters/", "clusters/main", "layerzero/", "layerzero/main" ]'`

...

Response

Any names in the array that are not found will be omitted from the response.

200 500 ``

Copy [ { "name": "clusters/", "type": "evm", "address": "0x5755d1dcea21caa687339c305d143e6e78f96adf", "isVerified": true }, { "name": "clusters/main", "type": "evm", "address": "0x5755d1dcea21caa687339c305d143e6e78f96adf", "isVerified": true }, { "name": "layerzero/", "type": "evm", "address": "0xccdead94e8cf17de32044d9701c4f5668ad0bef9", "isVerified": true }, { "name": "layerzero/main", "type": "evm", "address": "0xccdead94e8cf17de32044d9701c4f5668ad0bef9", "isVerified": true } ]

Copy []

...

[Previous REST API](#) [Next Address → Cluster](#) Last updated 2 days ago On this page \* [Get address](#) \* [Bulk get addresses](#)