

zks_getBytecodeByHash

Returns the bytecode of a transaction for the provided hash.

Parameters

- hash
- : (string) [Required
-] The hash of the transaction.

Response

The byte code of the given transaction.

Example

Replace YOUR-API-KEY with an API key from your [Infura dashboard](#).

Request

- cURL
- WSS

```
curl https://zksync-mainnet.infura.io/v3/YOUR-API-KEY \ -X POST \ -H "Content-Type: application/json" \ -d '{"jsonrpc": "2.0", "id": 1, "method": "zks_getBytecodeByHash", "params": ["0x0100067d861e2f5717a12c3e869cfb657793b86bbb0caa05cc1421f16c5217bc"]}' wscat -c wss://zksync-mainnet.infura.io/ws/v3/YOUR-API-KEY -x '{"jsonrpc": "2.0", "id": 1, "method": "zks_getBytecodeByHash", "params": ["0x0100067d861e2f5717a12c3e869cfb657793b86bbb0caa05cc1421f16c5217bc"]}'
```

Response

- JSON

```
{ "jsonrpc": "2.0", "result": [ 0, 4, 0, 0, 0, 0, 0, 2, 0, 11, ..., ... ], "id": 1 }
```

Last updated on Nov 5, 2024 [Previous zks_getBridgeContracts](#) [Next zks_getL1BatchBlockRange](#)