

Migrating to v1

This guide references the major changes between `safe-service-client` and `api-kit` v1 to help those migrating an existing application.

Note: Follow this guide before migrating to `api-kit` v2.

After completing this guide, you can remove `@safe-global/safe-service-client` from your `package.json`.

Adding the new dependency

To add the API Kit to your project, run the following:

```
yarn
```

```
add
```

```
@safe-global/api-kit@1.3.1
```

Change your initialization like this:

```
// old import SafeServiceClient from
```

```
'@safe-global/safe-service-client'
```

```
const
```

```
safeService
```

```
=
```

```
new
```

```
SafeServiceClient ({ txServiceUrl :
```

```
'https://your-transaction-service-url' , ethAdapter })
```

```
// new import SafeApiKit from
```

```
'@safe-global/api-kit'
```

```
const
```

```
apiKit
```

```
=
```

```
new
```

```
SafeApiKit ({ txServiceUrl :
```

```
'https://your-transaction-service-url' , ethAdapter })
```

getSafeDelegates()

The `getSafeDelegates` was updated to accept more filtering parameters. Now, it accepts an object with multiple properties instead of only the `safeAddress` parameter.

```
const
```

```
delegateConfig :
```

```
GetSafeDelegateProps
```

```
= { safeAddress ,
```

```
// Optional delegateAddress ,
```

```
// Optional delegatorAddress ,
```

```
// Optional label ,
```

```
// Optional limit ,  
// Optional offset // Optional } const  
delegates :  
SafeDelegateListResponse  
=  
await  
apiKit .getSafeDelegates (delegateConfig)
```

addSafeDelegate()

Parameter object properties were updated as follows:

```
// old const  
delegateConfig :  
SafeDelegateConfig  
= { safe , delegate , label , signer } await  
safeService .addSafeDelegate (delegateConfig)  
// new const  
delegateConfig :  
AddSafeDelegateProps  
= { safeAddress ,  
// Optional delegateAddress , delegatorAddress , label , signer } await  
apiKit .addSafeDelegate (delegateConfig)
```

removeAllSafeDelegates()

The method was deprecated and removed.

removeSafeDelegate()

Parameter object properties were updated as follows:

```
// old const  
delegateConfig :  
SafeDelegateDeleteConfig  
= { safe , delegate , signer } await  
safeService .removeSafeDelegate (delegateConfig)  
// new const  
delegateConfig :  
DeleteSafeDelegateProps  
= { delegateAddress , delegatorAddress , signer } await  
apiKit .removeSafeDelegate (delegateConfig)
```

getBalances()

The method was deprecated and removed.

getUSDBalances()

The method was deprecated and removed.

getCollectibles()

The method was deprecated and removed.

[Reference](#) [Migrating to V2](#)

Was this page helpful?

[Report issue](#)