

## seid add-genesis-account

Add a genesis account to genesis.json. The provided account must specify the account address or key name and a list of initial coins. If a key name is given, the address will be looked up in the local Keybase. The list of initial tokens must contain valid denominations. Accounts may optionally be supplied with vesting parameters. The association between the sei address and the eth address will also be created here if using keyring-backend test.

Usage: `seid add-genesis-account [address_or_key_name] [coin][,[coin]] [flags]`

Flags: `--height int` Use a specific height to query state at (this can error if the node is pruning state) `-h, --help` help for add-genesis-account `--home string` The application home directory (default "`~/sei`") `--keyring-backend string` Select keyring's backend (`os|file|kwallet|pass|test`) (default "`os`") `--node string` : to Tendermint RPC interface for this chain (default "`tcp://localhost:26657`") `-o, --output string` Output format (`text|json`) (default "`text`") `--vesting-amount string` amount of coins for vesting accounts `--vesting-end-time int` schedule end time (unix epoch) for vesting accounts `--vesting-start-time int` schedule start time (unix epoch) for vesting accounts

Global Flags: `--log_format string` The logging format (`json|plain`) `--log_level string` The logging level (`trace|debug|info|warn|error|fatal|panic`) `--trace` print out full stack trace on errors Last updated on July 1, 2024 [CLI Reference](#)  
[add-wasm-genesis-message](#)