tensor.random uniform like

...

Copy fnrandom uniform like(tensor:@Tensor, high:Option, low:Option, seed:Option)->Tensor;

٠.,

RandomUniformLike generates a tensor with random values using a uniform distribution, matching the shape of the input tensor.

This operation creates a new tensor with the same shape as the input tensor, where each element is initialized with a random value sampled from a uniform distribution.

Args

- tensor
- (@Tensor
-) The input tensor of [N,C,H,W], where N is the batch axis, C is the channel or depth, H is the height and W is the width.
- high
- (Option) An optional parameter specifying the upper bound (exclusive) of the uniform distribution. If not provided, defaults to 1.0.
- low
- (Option) An optional parameter specifying the lower bound (inclusive) of the uniform distribution. If not provided, defaults to 0.0.
- seed
- (Option) An optional parameter specifying the seed for the random number generator. If not provided, a random seed will be used.

Returns

- ATensor
- with the same shape as the input tensor, filled with random values from a uniform distribution within the specified range.

Examples

...

Copy useorion::operators::tensor::{FP8x23Tensor,FP8x23TensorAdd}; usecore::array::{ArrayTrait,SpanTrait}; useorion::operators::tensor::{TensorTrait,Tensor}; useorion::utils::{assert_eq, assert_seq_eq}; useorion::operators::tensor::FP8x23TensorPartialEq; useorion::numbers::{FixedTrait,FP8x23};

fnexample()->Tensor { letmutshape=ArrayTrait::::new(); shape.append(1); shape.append(8); shape.append(1); shape.append(2);

letmutdata=ArrayTrait::new(); data.append(FP8x23{ mag:70016, sign:true}); data.append(FP8x23{ mag:57536, sign:false}); data.append(FP8x23{ mag:116032, sign:false}); data.append(FP8x23{ mag:162944, sign:true}); data.append(FP8x23{ mag:151808, sign:true}); data.append(FP8x23{ mag:151808, sign:true}); data.append(FP8x23{ mag:28368, sign:false}); data.append(FP8x23{ mag:21024, sign:false}); data.append(FP8x23{ mag:24992, sign:false}); data.append(FP8x23{ mag:125120, sign:true}); data.append(FP8x23{ mag:79168, sign:true}); data.append(FP8x23{ mag:136960, sign:true}); data.append(FP8x23{ mag:10104, sign:true}); data.append(FP8x23{ mag:136704, sign:false}); data.append(FP8x23{ mag:184960, sign:true}); lettensor=TensorTrait::new(shape.span(), data.span()); return TensorTrait::random_uniform_like(@tensor, Option::Some(FP8x23 { mag: 83886080, sign: false }), Option::Some(FP8x23

[[[7299130, 4884492]], [[2339070, 1559536]], [[3448557, 984617]], [[5745934, 3670947]], [[4665989, 3079292]], [[3375288, 948254]], [[3749966, 4911069]], [[1358829, 4368105]]]]

. . .

Previous tensor.blackman window Next tensor.label encoder

Last updated15 days ago