

## seid query

Querying subcommands

Usage: seid query [flags] seid query [command]

Aliases: query, q

Available Commands: accesscontrol Querying commands for the accesscontrol module account Query for account by address auth Querying commands for the auth module authz Querying commands for the authz module bank Querying commands for the bank module block Get verified data for a the block at given height dex Querying commands for the dex module distribution Querying commands for the distribution module epoch Querying commands for the epoch module evidence Query for evidence by hash or for all (paginated) submitted evidence evm Querying commands for the evm module feegrant Querying commands for the feegrant module gov Querying commands for the governance module ibc Querying commands for the IBC module ibc-transfer IBC fungible token transfer query subcommands mint Querying commands for the minting module oracle Querying commands for the oracle module params Querying commands for the params module slashing Querying commands for the slashing module staking Querying commands for the staking module tendermint-validator-set Get the full tendermint validator set at given height tokenfactory Querying commands for the tokenfactory module tx Query for a transaction by hash, "/" combination or comma-separated signatures in a committed block txs Query for paginated transactions that match a set of events upgrade Querying commands for the upgrade module wasm Querying commands for the wasm module

Flags: --chain-id string The network chain ID -h, --help help for query

Global Flags: --home string directory for config and data (default "~/seid") --log\_format string The logging format (json|plain) - --log\_level string The logging level (trace|debug|info|warn|error|fatal|panic) --trace print out full stack trace on errors

Use "seid query [command] --help" for more information about a command. Last updated on July 1, 2024 [prune](#)  
[accesscontrol](#)