

seid tx evm

evm transactions subcommands

Usage: seid tx evm [flags] seid tx evm [command]

Available Commands: add-erc-cw20-pointer Submit an add ERC-CW20 pointer proposal add-erc-cw721-pointer Submit an add ERC-CW721 pointer proposal add-erc-native-pointer Submit an add ERC-native pointer proposal associate-address associate EVM and Sei address for the sender associate-contract-address Set address association for a CosmWasm contract. call-contract Call EVM contract with a bytes payload in hex call-precompile call method on precompile deploy Deploy an EVM contract for binary at specified path deploy-wsei Deploy ERC20 contract for a native Sei token erc20-send send recipient (in smallest unit) ERC20 tokens native-send Send funds from one account to an EVM address (e.g. 0x....). Note, the '--from' flag is ignored as it is implied from [from_key_or_address]. When using '--dry-run' a key name cannot be used, only a bech32 address. register-cw-pointer Register a CosmWasm pointer for an ERC20/721 contract. Pointer type is either ERC20 or ERC721. register-evm-pointer Register an EVM pointer for a CosmWasm contract. Pointer type is either CW20, CW721, or NATIVE. send send usei to EVM address

Flags: -h, --help help for evm

Global Flags: --chain-id string The network chain ID --home string directory for config and data (default "~/.sei") --log_format string The logging format (json|plain) --log_level string The logging level (trace|debug|info|warn|error|fatal|panic) --trace print out full stack trace on errors

Use "seid tx evm [command] --help" for more information about a command. Last updated on July 1, 2024 [evidence add-erc-cw20-pointer](#)