Registration

Check availability

Check the availability of one or more clusters

GET /v0.1/register/check/:name

POST /v0.1/register/check

Name Description BODY string[] - an array of names to check Example

Copy

Single check

curlhttps://api.clusters.xyz/v0.1/register/check/namethatdoesntexist

Bulk Check

```
curl-request POST\\ --url https://api.clusters.xyz/v0.1/register/check\\ --header'Content-Type: application/json'\\ --data' ["foobar", "namethat doesnt exist"] In the properties of the properti
Response
Single Check Bulk Check ```
Copy { "name":"namethatdoesntexist", "isAvailable":true }
Copy [ { "name": "foobar", "isAvailable": false }, { "name": "namethatdoesntexist", "isAvailable": true } ]
Register Transaction Data
POST /v0.1/register
Get the transaction data for registering a cluster so that a user can sign it
Name Description network ``
Copy "1" "10" "56" "137" "8453" "17000" "42161" "43114" "11155111" "solana"
"" sender The sender's address (EVM or Solana) names { name: string; bidAmountWei?: string }[] bidAmountWei(optional) is always in ETH
Ethereum - Mainnet Ethereum - Bridging Solana Example
"names": [ { "name": "namethatdoesntexist1" }, { "name": "namethatdoesntexist2" } ] }'
Response
200 500 ``
Copy { "gasToken":{ "symbol": "ETH", "decimals":18 }, "transactionData":{ "to": "0x00000000000e1a99dddd5610111884278bdbda1d", "data":
``` Names unavailable
Copy { "status":500, "error": "names_unavailable", "message": "1 or more names are unavailable" }
Bridge Failure
Copy { "status":500, "error": "lz_quote_fail", "message": "lz quote failed. most likely caused by wallets having insufficient balances" }
"" Note: Make sure the sender has enough funds to cover the transaction or the endpoint will result in an error from the bridge. Example
Response
200 500 ``
Copy { "gasToken":{ "symbol":"BNB", "decimals":18 }, "transactionData":{ "to":"0x000000000001a99dddd5610111884278bdbda1d", "data"
``` Names unavailable
Copy { "status":500, "error":"names_unavailable", "message":"1 or more names are unavailable" }
Bridge Failure
Copy { "status":500, "error": "Iz quote fail", "message": "Iz quote failed. most likely caused by wallets having insufficient balances" }
``` Example
```

Response Notice when using solana, transaction Data is an array of transactions instead of a single object on other networks. This is because only one name is supported per transaction at the moment when Copy { "gasToken":{ "symbol":"SOL", "decimals":"lamports" }, "transactionData":[ { ...Transaction }, { ...Transaction } ], "registrationFee":"443581060", "bridgeFee":"0", "names":[ { "name":"namethatdoesntexist1", "amount":"221790530" }, { "name":"namethatdoesntexist2", "amount":"221790530" } ]} " Names unavailable Copy { "status":500, "error":"names\_unavailable", "message":"1 or more names are unavailable" } Bridge Failure Copy { "status":500, "error":"lz\_quote\_fail", "message":"lz quote failed. most likely caused by wallets having insufficient balances" } Trasaction Status Checks the status of a transaction GET /v0.1/register/tx/:tx For now, if you registered more than one name in a transaction, it'll only give you the status of the first name. Example Copy curlhttps://api.clusters.xyz/v0.1/register/tx/0xffea3b29c64016772b7d3194b3c3899a62191e654990b6e3393b410667102284

Response

 $Copy\ type status = 'not\_found'|'pending'|'bridging'|'invalid'|'lost\_bid'|'finalized'' and the property of t$ 

200 ```

 $Copy \ \{ \ "tx":"0xffea3b29c64016772b7d3194b3c3899a62191e654990b6e3393b410667102284", \ "status":"finalized" \ \} \\$ 

Previous Cluster -- Metadata Next Indexing Last updated 18 hours ago On this page \*Check availability \* Register Transaction Data \* Transaction Status