

eth_getTransactionByBlockHashAndIndex

Returns information about a transaction given block hash and transaction index position.

Parameters

- block hash
- : [Required]
-] A string representing the hash (32 bytes) of a block.
- transaction index position
- : [Required]
-] A hexadecimal of the integer representing the position in the block.

Returns

A transaction object, or null when no transaction was found. The transaction object will consist of the following keys and their values:

- accessList
 - : [optional]
 -] A list of addresses and storage keys accessed by the transaction. See [access list transactions](#)
 - .
- blockHash
 - : 32 bytes. A hash of the block including this transaction.null
 - when it's pending.
- blockNumber
 - : The number of the block including this transaction.null
 - when it's pending.
- chainID
 - : [optional]
 -] chain ID specifying the network. Returned only for [EIP-1559 transactions](#)
 - .
- from
 - : 20 bytes. The address of the sender.
- gas
 - : Gas provided by the sender.
- gasPrice
 - : Gas price provided by the sender in Wei.
- hash
 - : 32 bytes. The hash of the transaction.
- input
 - : The data sent along with the transaction.
- maxPriorityFeePerGas
 - : [optional]
 -] Maximum fee, in Wei, the sender is willing to pay per gas above the base fee. See [EIP-1559 transactions](#)
 - .
- maxFeePerGas
 - : [optional]
 -] Maximum total fee (base fee + priority fee), in Wei, the sender is willing to pay per gas. See [EIP-1559 transactions](#)
 - .
- nonce
 - : The number of transactions made by the sender prior to this one.
- r
 - : 32 bytes. The ECDSA signaturer
 - .
- s
 - : 32 bytes. The ECDSA signatures
 - .
- to
 - : 20 bytes. The address of the receiver.null
 - when it's a contract creation transaction.
- transactionIndex
 - : The transaction's index position in the block, in hexadecimal.null
 - when it's pending.
- type
 - : The [transaction type](#)
 - .
- v
 - : The ECDSA recovery ID.
- value
 - : The value transferred in Wei.

Example

Replace YOUR-API-KEY with an API key from your [Infura dashboard](#).

Request

- cURL

```
curl https://celo-alfajores.infura.io/v3/YOUR-API-KEY \-X POST \-H "Content-Type: application/json" \-d '{"jsonrpc":"2.0","method":"eth_getTransactionByBlockHashAndIndex","params":["0xb3b20624f8f0f86be50dd04688409e5cea4bd02d700bf6e79e9384d47d6a5a35","0x0"],"id":1}'
```

Response

- JSON

[illegible]

"0x66b51cbb10cd1b2a09aaff137d9f6d4255bf73cb7702b666ebd5af502ffa4410", "to" : "0x4b9c25ca0224aef6a7522cabdbc3b2e125b7ca50", "transactionIndex" : "0x0",
"type" : "0x0", "v" : "0x25", "value" : "0x0" } }

Last updatedonApr 19, 2024 [Previous eth_getStorageAt](#) [Next eth_getTransactionByBlockNumberAndIndex](#)