

Logs

?module=logs

`https://instance_base_url/api?module=logs`

Get Event Logs by Address and/or Topic(s)

getLogs

Event logs for an address and topic. Useand/or with the topic operator to specify topic retrieval options when adding multiple topics. Up to a maximum of 1,000 event logs.

Example:

...

[illegible]

...

*=required field

Request Params Example Result Parameter Description
fromBlock integer block number to start searching for logs. *latest* is also supported
toBlock integer block number to stop searching for logs. *latest* is also supported.
Note can be same as *fromBlock* if looking at logs for a single block
address string 160-bit code used for identifying contracts. An address and/or topic is required.
topic0 string for first required topic. *topic1* string for 2nd optional topic. *topic2* string for 3rd optional topic. *topic3* string for 4th optional topic.
topic0_1_opr operator when topic 0 and 1 are used. Either *and* or *or*
topic0_2_opr operator for topic 0 and topic 2. Either *and* or *or*
topic0_3_opr operator for topic 0 and topic 3. Either *and* or *or*
topic1_2_opr operator for topic 1 and topic 2. Either *and* or *or*
topic1_3_opr the topic operator for topic 1 and topic 3. Either *and* or *or*
topic2_3_opr the topic operator for topic 2 and topic 3. Either *and* or *or*

```
Copy { "message": "OK", "result": [ { "address": "0x33990122638b9132ca29c723bdf037f1a891a70c",  
"blockNumber": "0x5c958", "data": "0x", "gasPrice": "0xba43b7400", "gasUsed": "0x10682", "logIndex": "0x",  
"timeStamp": "0x561d688c", "topics": [ "0xf63780e752c6a54a94fc52715dbc5518a3b4c3c2833d301a204226548a2a8545",  
"0x72657075746174696f6e0000000000000000000000000000000000000000000000000000",  
"0x0000000000000000000000000000000000000000000000000000000000000000",  
"transactionHash": "0x0b03498648ae2da924f961dda00dc6bb0a8df15519262b7e012b7d67f4bb7e83",  
"transactionIndex": "0x" } ], "status": "1" }
```

...

Last updated 10 months ago