

# eth\_getTransactionCount

Returns the number of transactions sent from an address.

## Parameters

- address
- : [Required
- ] A string representing the address (20 bytes).
- block parameter
- : [Required
- ] A hexadecimal block number, or one of the string tagslatest
- ,earliest
- ,pending
- , orfinalized
- . See the[default block parameter](#)
- .
- warning
- safe
- isn't supported. Usefinalized
- instead.

## Returns

transaction count : A hexadecimal equivalent of the integer representing the number of transactions sent from the given address.

## Example

ReplaceYOUR-API-KEY with an API key from your[Infura dashboard](#) .

## Request

- cURL
- WSS

```
curl https://scroll-mainnet.infura.io/v3/ \ -X POST \ -H "Content-Type: application/json" \ -d '{"jsonrpc": "2.0", "method": "eth_getTransactionCount", "params": ["0xc94770007dda54cF92009BFF0dE90c06F603a09f", "0x5bad55"], "id": 1}' wscat -c wss://scroll-mainnet.infura.io/ws/v3/ -x '{"jsonrpc": "2.0", "method": "eth_getTransactionCount", "params": ["0xc94770007dda54cF92009BFF0dE90c06F603a09f", "0x5bad55"], "id": 1}'
```

## Response

- JSON

```
{ "jsonrpc": "2.0", "id": 1, "result": "0x1a" }
```

Last updatedonNov 5, 2024 [Previous eth\\_getTransactionByHash](#) [Next eth\\_getTransactionReceipt](#)