

```

D4D4D4;--ch-t-background: #1E1E1E;--ch-t-lighter-
inlineBackground: #1e1e1ee6;--ch-t-editor-background:
#1E1E1E;--ch-t-editor-foreground: #D4D4D4;--ch-t-editor-
rangeHighlightBackground: #ffffff0b;--ch-t-editor-
infoForeground: #3794FF;--ch-t-editor-
selectionBackground: #264F78;--ch-t-focusBorder:
#007FD4;--ch-t-tab-activeBackground: #1E1E1E;--ch-t-
tab-activeForeground: #ffffff;--ch-t-tab-
inactiveBackground: #2D2D2D;--ch-t-tab-
inactiveForeground: #ffffff80;--ch-t-tab-border: #252526;--
ch-t-tab-activeBorder: #1E1E1E;--ch-t-editorGroup-
border: #444444;--ch-t-editorGroupHeader-
tabsBackground: #252526;--ch-t-editorLineNumber-
foreground: #858585;--ch-t-input-background: #3C3C3C;
--ch-t-input-foreground: #D4D4D4;--ch-t-icon-foreground:
#C5C5C5;--ch-t-sideBar-background: #252526;--ch-t-
sideBar-foreground: #D4D4D4;--ch-t-sideBar-border:
#252526;--ch-t-list-activeSelectionBackground: #094771;--
ch-t-list-activeSelectionForeground: #ffffffe;--ch-t-list-
hoverBackground: #2A2D2E; }

```

Migrate to v2

This guide references the major changes between v1 and v2 to help those migrating an existing app.

API Kit constructor

It won't be necessary to specify `atxServiceUrl` in environments where Safe has a Transaction Service running. Providing the chain ID will be enough. If you want to use your custom service or the kit in a chain not supported by a Safe Transaction Service, you can add the `txServiceUrl` parameter.

```

_21 // old: _21 import SafeApiKit from '@safe-global/api-kit' _21 _21 const apiKit = new SafeApiKit({ _21 txServiceUrl:
'https://your-transaction-service-url', _21 ethAdapter _21 }) _21 _21 // new: _21 import SafeApiKit from '@safe-global/api-kit'
_21 _21 const chainId: bigint = 1n _21 const apiKit = new SafeApiKit({ _21 chainId _21 }) _21 _21 // or set a custom
Transaction Service _21 const apiKit = new SafeApiKit({ _21 chainId, _21 txServiceUrl: 'https://your-transaction-service-url'
_21 })

```

Use the route you prefer

API Kit v1 forced any custom service to be hosted under the `/api` route of the URL specified in `txServiceUrl`. This isn't the case anymore; you can specify any preferred route or subdomain.

Note that if you use a custom service running under `/api`, you will now need to migrate as follows:

```

_13 // old: _13 const txServiceUrl = 'https://your-transaction-service-domain/' _13 const apiKit = new SafeApiKit({ _13
txServiceUrl, _13 ethAdapter _13 }) _13 // new: _13 const chainId: bigint = 1n _13 const txServiceUrl = 'https://your-
transaction-service-domain/api' _13 const apiKit = new SafeApiKit({ _13 chainId, _13 txServiceUrl _13 })

```

MasterCopy to Singleton

To avoid confusion between terms used as synonyms, we aligned all our code to use the word `singleton` .

- Rename type `MasterCopyResponse`
- to `SafeSingletonResponse`
- Rename method `getServiceMasterCopiesInfo()`
- to `getServiceSingletonsInfo()`

[Migrate to V1](#)

Was this page helpful?

[Report issue](#)