# eth\_syncing

Returns an object with data about the sync status orfalse.

## **Parameters**

None.

## Returns

- · sync status
- : (boolean) Returnsfalse
- · only when not syncing.
- · sync blocks
- :\* startingBlock

\_

- : A hexadecimal equivalent the integer indicating the block at which the import started (will only be reset after the sync reaches the head).
- currentBlock
- - : A hexadecimal equivalent the integer indicating the current block, same aseth blockNumber
- ۰.

- highestBlock
- .
- : A hexadecimal equivalent the integer indicating the highest block.

# **Example**

ReplaceYOUR-API-KEY with an API key from your Infura dashboard .

### Request

- cURL
- WSS

curl https://arbitrum-mainnet.infura.io/v3/YOUR-API-KEY \ -X POST \ -H "Content-Type: application/json" \ -d '{"jsonrpc":"2.0","method":"eth\_syncing","params": [],"id":1}' wscat -c wss://arbitrum-mainnet.infura.io/ws/v3/YOUR-API-KEY - x '{"jsonrpc":"2.0","method":"eth\_syncing","params": [],"id":1}'

### Response

JSON

```
{ "jsonrpc": "2.0", "id": 1, "result": false }
```

Last updatedonApr 19, 2024 Previous eth\_sign Next net\_peerCount