

ChildTransaction

Classes

ChildTransactionReceipt

Extension of ethers-js TransactionReceipt, adding Arbitrum-specific functionality

Implements

- TransactionReceipt

Methods

getBatchConfirmations()

getBatchConfirmations (childProvider : JsonRpcProvider) :

Promise < BigNumber

Get number of parent chain confirmations that the batch including this tx has

Parameters

Parameter Type Description childProvider JsonRpcProvider

Returns

Promise < BigNumber

number of confirmations of batch including tx, or 0 if no batch included this tx

Source

[message/ChildTransaction.ts:138](#)

getBatchNumber()

getBatchNumber (childProvider : JsonRpcProvider) :

Promise < BigNumber

Get the number of the batch that included this tx (will throw if no such batch exists)

Parameters

Parameter Type Description childProvider JsonRpcProvider

Returns

Promise < BigNumber

number of batch in which tx was included, or errors if no batch includes the current tx

Source

[message/ChildTransaction.ts:151](#)

getChildToParentEvents()

getChildToParentEvents () : ChildToParentTransactionEvent [] Get ChildToParentTransactionEvent events created by this transaction

Returns

ChildToParentTransactionEvent []

Source

[message/ChildTransaction.ts:97](#)

getChildToParentMessages()

getChildToParentMessages < T

(parentSignerOrProvider :
T) :

Promise < ChildToParentMessageReaderOrWriter < T

[]

Get any child-to-parent-messages created by this transaction

Type parameters

Type parameter T extends SignerOrProvider

Parameters

Parameter Type parentSignerOrProvider T

Returns

Promise <[ChildToParentMessageReaderOrWriter](#) <T

[]>

Source

[message/ChildTransaction.ts:119](#)

getRedeemScheduledEvents()

getRedeemScheduledEvents () : object [] Get event data for any redeems that were scheduled in this transaction

Returns

object []

Source

[message/ChildTransaction.ts:111](#)

isDataAvailable()

isDataAvailable (childProvider : JsonRpcProvider , confirmations :

number) :

Promise < boolean

Whether the data associated with this transaction has been made available on parent chain

Parameters

Parameter Type Default value Description childProvider JsonRpcProvider undefined confirmations number 10 The number of confirmations on the batch before data is to be considered available

Returns

Promise <boolean

Source

[message/ChildTransaction.ts:173](#)

monkeyPatchWait()

static

monkeyPatchWait (contractTransaction : ContractTransaction) : ChildContractTransaction Replaces the wait function with one that returns an L2TransactionReceipt

Parameters

Parameter	Type	Description
contractTransaction	ContractTransaction	

Returns

ChildContractTransaction

Source

[message/ChildTransaction.ts:187](#)

toRedeemTransaction()

static

toRedeemTransaction (redeemTx : ChildContractTransaction , childProvider : Provider) : RedeemTransaction Adds a waitForRedeem function to a redeem transaction

Parameters

Parameter	Type	Description
redeemTx	ChildContractTransaction	
childProvider	Provider	

Returns

RedeemTransaction

Source

[message/ChildTransaction.ts:208](#) [Edit this page](#) [Previous ChildToParentMessageNitro](#) [Next ParentToChildMessage](#)