Sending Tx and Bundles

Flashbots provides a variety of methods for submitting transactions and bundles. This guide is designed to help you understand these options and select the one that best fits your needs.

Understanding Relay and RPC Endpoints

Flashbots offers two primary JSON-RPC endpoints on Ethereum Mainnet:rpc.flashbots.net andrelay.flashbots.net .

rpc.flashbots.net

- For Retail Users
- Purpose
- : Designed specifically for retail users as a drop-in RPC replacement in their wallet.
- Features
- : Provides MEV protection and MEV refunds for eligible transactions. Support all the regula Ethereum JSON RPC
- but not Flashbots specific JSON RPC methods
- Performance
- · :Rate limited
- · to satisfy the need of regular users.
- · : Transactions are submitted througheth sendRawTransaction
- to fit wallet RPC interface. Underneath, the endpoint uses relay.flashbots.net
- · to submit transactions.

relay.flashbots.net

- For Advanced Users
- Purpose
- : Designed for advanced users, including searchers, applications, and Telegram bots. It accepts both transactions and bundles.
- Features
- : Support allFlashbots specific JSON RPC methods
- . Does not support regular Ethereum JSON RPC methods
- Performance
- · : Offers a highrate limit
- of 10,000 requests per second per IP address.
- Recommendation
- : Ideal for activities beyond simple transaction submissions via wallets.

Choosing the Right JSON-RPC Method

Withrelay.flashbots.net identified as the go-to for advanced operations, the choice of JSON-RPC methods is as follows:

- For Single Transactions
- : Useeth sendPrivateTransaction
- · For Bundles of Transactions
- :* Use
 - :mev sendBundle
 - o for more flexibility and power, like leveraging thenew bundle format
- ,MEV-Share
- - · , and multiplexing to multiple builders
- ο.

- Use
- :eth_sendBundle
- if you want something simple and quick! The OG way of sending bundles. <u>Edit this page</u> Last updatedonJan 30,
 2024 <u>Previous Code of Conduct Next Overview</u>