

eth_syncing

Returns an object with data about the sync status or false .

Parameters

None.

Returns

- sync status
- : (boolean) Returns false
- only when not syncing.
- sync blocks
- : * startingBlock
- - : A hexadecimal equivalent the integer indicating the block at which the import started (will only be reset after the sync reaches the head).
- - currentBlock
- - : A hexadecimal equivalent the integer indicating the current block, same as [eth_blockNumber](#)
- - .
- - highestBlock
- - : A hexadecimal equivalent the integer indicating the highest block.

Example

Replace YOUR-API-KEY with an API key from your [Infura dashboard](#) .

Request

- cURL
- WSS

```
curl https://zksync-mainnet.infura.io/v3/YOUR-API-KEY \-X POST \-H "Content-Type: application/json" \-d '{"jsonrpc": "2.0", "method": "eth_syncing", "params": [], "id": 1}' wscat -c wss://zksync-mainnet.infura.io/ws/v3/YOUR-API-KEY -x '{"jsonrpc": "2.0", "method": "eth_syncing", "params": [], "id": 1}'
```

Response

- JSON

```
{ "jsonrpc": "2.0", "id": 1, "result": false }
```

Last updated on Nov 5, 2024 [Previous eth_submitWork](#) [Next net_listening](#)