

get-address)

- [Bulk get addresses](#)

Cluster → Address

To enable testnet querying on Sepolia, add?testnet=true to the end of the URL

Get address

GET /v0.1/address/:name

GET /v0.1/address/:name/:addressName

Get the wallet associated to a cluster name. You can pass just the cluster name or also include the address name as shown in the 2 examples.

Name Description name Name of the cluster addressName (optional) Address name of the cluster Example

...

Copy <https://api.clusters.xyz/v0.1/address/clusters> <https://api.clusters.xyz/v0.1/address/clusters/main>

...

Response

200 404 ``

Copy { "type": "evm", "address": "0x5755d1dcea21caa687339c305d143e6e78f96adf", "name": "clusters/main", "isVerified": true } }

Copy null

...

Bulk get addresses

POST /v0.1/address/names

Get the wallets associated to a cluster name. You can pass just the cluster name or also include the address name.

Name Description POSTbody Array of cluster names (with or without address name) Example

...

Copy curl-XPOST\ 'https://api.clusters.xyz/v0.1/address/names' --data-raw["clusters/", "clusters/main", "layerzero/", "layerzero/main"]'

...

Response

Any names in the array that are not found will be omitted from the response.

200 500 ``

Copy [{ "name": "clusters/", "type": "evm", "address": "0x5755d1dcea21caa687339c305d143e6e78f96adf", "isVerified": true }, { "name": "clusters/main", "type": "evm", "address": "0x5755d1dcea21caa687339c305d143e6e78f96adf", "isVerified": true }, { "name": "layerzero/", "type": "evm", "address": "0xccdead94e8cf17de32044d9701c4f5668ad0bef9", "isVerified": true }, { "name": "layerzero/main", "type": "evm", "address": "0xccdead94e8cf17de32044d9701c4f5668ad0bef9", "isVerified": true }]

Copy []

...

[Previous Address → Cluster](#) [Next Cluster → Metadata](#) Last updated 4 months ago