

## seid query gov proposals

Query for all paginated proposals that match optional filters:

Example: `query gov proposals --depositor cosmos1skjwj5whet0lpe65qaq4rpq03hxlwd9nf39lk` `query gov proposals --voter cosmos1skjwj5whet0lpe65qaq4rpq03hxlwd9nf39lk` `query gov proposals --status (DepositPeriod|VotingPeriod|Passed|Rejected)` `query gov proposals --page=2 --limit=100`

Usage: `seid query gov proposals [flags]`

Flags: `--count-total` count total number of records in proposals to query for `--depositor` string (optional) filter by proposals deposited on by depositor `--height` int Use a specific height to query state at (this can error if the node is pruning state) `-h, --help` help for proposals `--limit` uint pagination limit of proposals to query for (default 100) `--node` string : to Tendermint RPC interface for this chain (default "tcp://localhost:26657") `--offset` uint pagination offset of proposals to query for `-o, --output` string Output format (text|json) (default "text") `--page` uint pagination page of proposals to query for. This sets offset to a multiple of limit (default 1) `--page-key` string pagination page-key of proposals to query for `--reverse` results are sorted in descending order `--status` string (optional) filter proposals by proposal status, status: `deposit_period/voting_period/passed/rejected` `--voter` string (optional) filter by proposals voted on by voted

Global Flags: `--chain-id` string The network chain ID `--home` string directory for config and data (default "~/.sei") `--log_format` string The logging format (json|plain) `--log_level` string The logging level (trace|debug|info|warn|error|fatal|panic) `--trace` print out full stack trace on errors Last updated on July 1, 2024 [proposal proposer](#)