

seid query staking unbonding-delegations-from

Query delegations that are unbonding *from* a validator.

Example: `query staking unbonding-delegations-from seivaloper1gghjut3ccd8ay0zduzj64hwre2fxs9ldmqhffj`

Usage: `seid query staking unbonding-delegations-from [validator-addr] [flags]`

Flags: `--count-total` count total number of records in unbonding delegations to query for `--height` int Use a specific height to query state at (this can error if the node is pruning state) `-h, --help` help for unbonding-delegations-from `--limit` uint pagination limit of unbonding delegations to query for (default 100) `--node` string : to Tendermint RPC interface for this chain (default "tcp://localhost:26657") `--offset` uint pagination offset of unbonding delegations to query for `-o, --output` string Output format (text|json) (default "text") `--page` uint pagination page of unbonding delegations to query for. This sets offset to a multiple of limit (default 1) `--page-key` string pagination page-key of unbonding delegations to query for `--reverse` results are sorted in descending order

Global Flags: `--chain-id` string The network chain ID `--home` string directory for config and data (default "~/sei") `--log_format` string The logging format (json|plain) `--log_level` string The logging level (trace|debug|info|warn|error|fatal|panic) `--trace` print out full stack trace on errors Last updated on July 1, 2024 [unbonding-delegation](#) [unbonding-delegations](#)