

Marketplace Frontend

Unlock Your NFT Storefront: Clone & Customize Your Path to Blockchain Success with this whitelabel marketplace template!

Mintbase Templates This is part of the [Mintbase Templates](#) , a collection of templates that you can use to scaffold your own project

Project Walkthrough

This guide will take you step by step through the process of creating a basic marketplace frontend where you can purchase tokens and filter your selection by store. It uses [mintbase-js/data](#) for retrieving data and [mintbase-js/sdk](#) for executing marketplace methods on the [mintbase marketplace contract](#) .

The mintbase-js/data package provides convenient functions for retrieving nft data from the mintbase indexer. In this example, you will be able to view and purchase NFTs from a specific nft contract.

You can find more information on Github [Github link](#)

A live demo of the marketplace can be found here [Live demo link](#)

Setup

install dependencies

```
pnpm install
```

run the project

```
pnpm dev
```

Step 1: Connect Wallet

Before proceeding, it is important to have a wallet connection feature implemented in your application in order to interact with the contract. To do this, you can check our guide [Wallet Connection Guide](#) .

Step 2: Get NFTs from Store

In this example, we utilized react-query to manage the loading state when retrieving NFTs from the contract via the storeNfts method. This method returns all listed NFTs from the specified contract, allowing you to display them in the user interface.

```
// src/hooks/useStoreNfts.ts import
```

```
{ useQuery }
```

```
from
```

```
'react-query' ; import
```

```
{ storeNfts }
```

```
from
```

```
'@mintbase-js/data' ;
```

```
const
```

```
useStoreNfts
```

```
=
```

```
( store ? :
```

```
string )
```

```
=>
```

```

{ const defaultStores = process . env . NEXT_PUBLIC_STORES
||
MAINNET_CONFIG . stores ; const formattedStores = defaultStores . split ( / [ , ] + / ) ;
const
{ isLoading , error , data }
=
useQuery ( [ 'storeNfts' , store ] ,
( )
=>
storeNfts ( store || formattedStores ,
true ) ,
{ retry :
false , refetchOnWindowFocus :
false , select : mapStoreNfts , } ) ;
return
{
... data , error , loading : isLoading } ; } ;
export
{ useStoreNfts } ;

```

Step 3: Get Store Data

To control the tabs, we need to retrieve store data using the `storeData` method. This method returns the data from the specified contract, enabling you to display it in the user interface.

```

// src/hooks/useStoreData.ts import
{ useQuery }
from
'react-query' ; import
{ storeData }
from
'@mintbase-js/data' ;
const
useStoreData
=
( )
=>
{ const defaultStores = process . env . NEXT_PUBLIC_STORES
||
MAINNET_CONFIG . stores ; const formattedStores = defaultStores . split ( / [ , ] + / ) ;
const

```

```

{ isLoading , error , data }

=

useQuery ( 'storeData' ,

( )

=>

storeData ( formattedStores ) ,

{ retry :

false , refetchOnWindowFocus :

false , select : mapStoreData , } ) ;

return

{

... data , error , loading : isLoading } ; } ;

export

{ useStoreData } ;

```

Step 4: Get Metadata from an NFT

To display NFT pricing information, available quantities, and other details in the user interface, it is necessary to access the NFT metadata using the `metadataByMetadataId` method.

```
// src/hooks/useMetadataByMetadataId.ts import
```

```

{ useQuery }

from

'react-query' ; import

{ metadataByMetadataId }

from

'@mintbase-js/data' ;

const

useMetadataByMetadataId

=

( { metadataId } )

=>

{ const

{ isLoading , data : metadata }

=

useQuery ( 'metadataByMetadataId' ,

( )

=>

metadataByMetadataId ( metadataId ) ,

{ retry :

false , refetchOnWindowFocus :

```

```

false , select : mapMetadata , } ) ;

return

{

... metadata , isTokenListLoading : isLoading } ; } ;

export

{ useMetadataByMetadataId } ;

```

Step 5: Get Current NEAR Price

To obtain the current price of the NFT in USD, it is necessary to retrieve the current Near price. We accomplish this by using the `nearPrice` method.

```

// src/hooks/useNearPrice.ts import

{ useEffect , useState }

from

'react' ; import

{ nearPrice }

from

'@mintbase-js/data' ;

const

useNearPrice

=

( )

=>

{ const

[ nearPriceData , setNearPriceData ]

=

useState ( '0' ) ;

useEffect ( ( )

=>

{ const

getNearPrice

=

async

( )

=>

{ const

{ data : priceData , error }

=

await

nearPrice ( ) ; setNearPriceData ( error ?

```

```
'0'

: priceData ) ; } ;

getNearPrice ( ) ; } ,

[ ] ) ;

return nearPriceData ; } ;

export

{ useNearPrice } ;
```

Step 6: Execute the Contract Call - Buy

The execute method accepts one or more contract call objects and executes them using a specified wallet instance. In this example, we need to use the execute method to execute the "buy" call, allowing the user to purchase the desired NFT.

```
const

singleBuy

=

async

( )

=>

{ const wallet =

await selector . wallet ( ) ;

if

( tokenId )

{ ( await

execute ( { wallet , callbackArgs : callback } , { ... buy ( { contractAddress : nftContractId , tokenId , affiliateAccount : process

. env . NEXT_PUBLIC_AFFILIATE_ACCOUNT

|| MAINNET_CONFIG . affiliate , marketId , price :

nearToYocto ( currentPrice ?. toString ( ) )

||

"0" , } ) , } ) )

as

FinalExecutionOutcome ; } } ;
```

Set ENV variables

Once that's done, copy the .env.example file in this directory to .env.local (which will be ignored by Git):

cp .env.example .env.local if you use windows without powershell or cygwin:

copy .env.example .env.local To get your api key visit :

[Mintbase Developers Page for Mainnet](#) [Mintbase Developers Page for testnet](#) :

NEXT_PUBLIC_DEVELOPER_KEY=your_mintbase_api_key NEXT_PUBLIC_NETWORK could be testnet or mainnet

NEXT_PUBLIC_NETWORK=testnet NEXT_PUBLIC_STORES is your store's ids

NEXT_PUBLIC_STORES=latium.mintspace2.testnet,mufasa.mintspace2.testnet NEXT_PUBLIC_AFFILIATE_ACCOUNT is your near account where you should get your market fee

NEXT_PUBLIC_AFFILIATE_ACCOUNT=your_near_account.near

Extending

This project is setup using Next.js + @mintbase/js You can use this project as a reference to build your own, and use or remove any library you think it would suit your needs.

Get in touch You can get in touch with the mintbase team using the following channels:

- Support: [Join the Telegram](#)
- Twitter: [@mintbase](#) [Edit this page](#) Last updated on Apr 29, 2024 by Guille Was this page helpful? Yes No Need some help? [Chat with us](#) or check our [Dev Resources](#) ! [Twitter](#) [Telegram](#) [Discord](#) [Zulip](#)

[Previous NFT minter](#) [Next Onchain Blog](#)