

Client

Queries

In this section we describe the queries required on grpc server.

```
// Query defines the gRPC querier service. service
```

```
Query
```

```
{ // Parameters queries the parameters of the module. rpc
```

```
Params ( QueryParamsRequest )
```

```
returns
```

```
( QueryParamsResponse )
```

```
{ option
```

```
( google . api . http ) . get =
```

```
"/neutron-org/neutron/feerefunder/params" ; } rpc
```

```
FeeInfo ( FeeInfoRequest )
```

```
returns
```

```
( FeeInfoResponse )
```

```
{ option
```

```
( google . api . http ) . get =
```

```
"/neutron-org/neutron/feerefunder/info" ; } }
```

fee-info[port-id][channel-id][sequence]

Returns list of all failures.

```
neutrond query feerefunder fee-info [ port-id ]
```

```
[ channel-id ]
```

```
[ sequence ] Example Returns fee info by port id, channel id and sequence:neutrond query feerefunder fee-info icacontroller-  
neutron14hj2tavq8fpesdwxxcu44rty3hh90vhujrvcmstl4zr3txmfvw9s5c2epq_1 channel_1 1 Output:
```

```
fee_info : -
```

```
payer : neutron1nc5tatafv6eyq7llkr2gv50ff9e22mnf70qgjlv737ktmt4eswrqcd0mrx packet_id : -
```

```
channel_id : channel_1 port_id : icacontroller - neutron14hj2tavq8fpesdwxxcu44rty3hh90vhujrvcmstl4zr3txmfvw9s5c2epq_1  
sequence :
```

```
1 fee : -
```

```
recv_fee : -
```

```
denom :
```

```
"untrn" amount :
```

```
"0" ack_fee : -
```

```
denom :
```

```
"untrn" amount :
```

```
"500" timeout_fee : -
```

```
denom :
```

"untrn" amount :

"500" [Previous](#) [Overview](#) [Next](#) [State](#)