Interface: TwapStruct

Parameters for a TWAP order, as expected by the contract's static Input .

Hierarchy

- TwapDataBase
- 4TwapStruct

Properties

appData

Readonly appData :string

Meta-data associated with the order. Normally would be the keccak256 hash of the document generated in http://github.com/cowprotocol/app-data

This hash should have been uploaded to the APhttps://api.cow.fi/docs/#/default/put_api_v1_app_data_app_data_hash_and potentially to other data availability protocols like IPFS.

Inherited from

TwapDataBase.appData

Defined in

external/cow-sdk/src/composable/orderTypes/Twap.ts:63

buyToken

Readonly buyToken :string

which token to buy

Inherited from

TwapDataBase.buyToken

Defined in

external/cow-sdk/src/composable/orderTypes/Twap.ts:50

minPartLimit

•Readonly minPartLimit :BigNumber

minimum amount of buyToken that must be bought in each part

Defined in

external/cow-sdk/src/composable/orderTypes/Twap.ts:78

n

•Readonly n :BigNumber

number of parts

Defined in

external/cow-sdk/src/composable/orderTypes/Twap.ts:88

partSellAmount

 Readonly partSellAmount :BigNumber amount of sellToken to sell in each part

Defined in

external/cow-sdk/src/composable/orderTypes/Twap.ts:73

receiver

•Readonly receiver :string

who to send the tokens to

Inherited from

TwapDataBase.receiver

Defined in

external/cow-sdk/src/composable/orderTypes/Twap.ts:55

sellToken

•Readonly sellToken :string

which token to sell

Inherited from

TwapDataBase.sellToken

Defined in

external/cow-sdk/src/composable/orderTypes/Twap.ts:45

span

•Readonly span :BigNumber

whether the TWAP is valid for the entire interval or not

Defined in

external/cow-sdk/src/composable/orderTypes/Twap.ts:98

t

•Readonly t :BigNumber

duration of the TWAP interval

Defined in

external/cow-sdk/src/composable/orderTypes/Twap.ts:93

t0

•Readonly t0 :BigNumber

start time of the TWAP

Defined in

external/cow-sdk/src/composable/orderTypes/Twap.ts:83 Previous TwapData Next Readme