

seid tx

Transactions subcommands

Usage: seid tx [flags] seid tx [command]

Available Commands:

accesscontrol accesscontrol transactions subcommands authz Authorization transactions subcommands bank Bank transaction subcommands broadcast Broadcast transactions generated offline crisis Crisis transactions subcommands decode Decode a binary encoded transaction string dex dex transactions subcommands distribution Distribution transactions subcommands encode Encode transactions generated offline epoch epoch transactions subcommands evidence Evidence transaction subcommands evm evm transactions subcommands feegrant Feegrant transactions subcommands gov Governance transactions subcommands ibc IBC transaction subcommands ibc-transfer IBC fungible token transfer transaction subcommands multisign Generate multisig signatures for transactions generated offline oracle Oracle transaction subcommands sign Sign a transaction generated offline sign-batch Sign transaction batch files slashing Slashing transaction subcommands staking Staking transaction subcommands tokenfactory tokenfactory transactions subcommands validate-signatures validate transactions signatures vesting Vesting transaction subcommands wasm Wasm transaction subcommands

Flags: --chain-id string The network chain ID -h, --help help for tx

Global Flags: --home string directory for config and data (default "~/sei") --log_format string The logging format (json|plain) - --log_level string The logging level (trace|debug|info|warn|error|fatal|panic) --trace print out full stack trace on errors

Additional help topics: seid tx upgrade Upgrade transaction subcommands

Use "seid tx [command] --help" for more information about a command. Last updated on July 1, 2024 [scan-tx accesscontrol](#)