

# AaveOracle

## AaveOracle

Contract to get asset prices, manage price sources and update the fallback oracle.

Protocol V3 uses Chainlink Aggregators as the source of all asset prices.

The fallback oracles from V1 and V2 of the protocol are now deprecated and no longer maintained.

## Methods

### View

#### getAssetPrice

```
function getAssetPrice(address asset)
```

Returns the price of the supportedasset inBASE\_CURRENCY of the Aave Market. All V3 markets use USD based oracles which return values with 8 decimals.

#### Return Value

Type Description uint256 Price in BASE\_CURRENCY of the Aave market.

#### getAssetsPrices

```
function getAssetsPrices(address[] calldata assets)
```

Returns the prices of the supportedassets inBASE\_CURRENCY of the Aave Market. All V3 markets use USD based oracles which return values with 8 decimals.

## Call Params

Name Type Description assets address[] The addresses of the assets for which price is being queried. Return Value

Type Description uint256[] Prices in BASE\_CURRENCY of the Aave market.

#### getSourceOfAsset

```
function getSourceOfAsset(address asset)
```

Returns the address of the price source forasset .

#### getFallbackOracle

```
function getFallbackOracle()
```

Returns the address of the fallback oracle.

### Write

#### setAssetSources

```
function setAssetSources(address[] calldata assets, address[] calldata sources)
```

Sets the price source for given list of assets.

This method can be called only byPOOL\_ADMIN orASSET\_LISTING\_ADMIN . Check[ACLManager](#) for details on system roles. Call Params

Name Type Description assets address[] The addresses of the assets for which source is being set. sources address[] The address of the source of each asset. Length of assets and sources array should be same.

#### setFallbackOracle

```
function setFallbackOracle(address fallbackOracle)
```

Sets/updates the fallback oracle.

This method can be called only by POOL\_ADMIN or ASSET\_LISTING\_ADMIN . Check [ACLManager](#) for details on system roles. Call Params

Name Type Description fallbackOracle address The address of the fallback oracle.

ABI

AaveOracle ABI ```

```
Copy [ { "inputs": [ { "internalType": "contract IPoolAddressesProvider", "name": "provider", "type": "address" }, {
"internalType": "address[]", "name": "assets", "type": "address[]" }, { "internalType": "address[]", "name": "sources", "type":
"address[]" }, { "internalType": "address", "name": "fallbackOracle", "type": "address" }, { "internalType": "address", "name":
"baseCurrency", "type": "address" }, { "internalType": "uint256", "name": "baseCurrencyUnit", "type": "uint256" } ],
"stateMutability": "nonpayable", "type": "constructor" }, { "anonymous": false, "inputs": [ { "indexed": true, "internalType":
"address", "name": "asset", "type": "address" }, { "indexed": true, "internalType": "address", "name": "source", "type":
"address" } ], "name": "AssetSourceUpdated", "type": "event" }, { "anonymous": false, "inputs": [ { "indexed": true,
"internalType": "address", "name": "baseCurrency", "type": "address" }, { "indexed": false, "internalType": "uint256", "name":
"baseCurrencyUnit", "type": "uint256" } ], "name": "BaseCurrencySet", "type": "event" }, { "anonymous": false, "inputs": [ {
"indexed": true, "internalType": "address", "name": "fallbackOracle", "type": "address" } ], "name": "FallbackOracleUpdated",
"type": "event" }, { "inputs": [], "name": "ADDRESSES_PROVIDER", "outputs": [ { "internalType": "contract
IPoolAddressesProvider", "name": "", "type": "address" } ], "stateMutability": "view", "type": "function" }, { "inputs": [], "name":
"BASE_CURRENCY", "outputs": [ { "internalType": "address", "name": "", "type": "address" } ], "stateMutability": "view",
"type": "function" }, { "inputs": [], "name": "BASE_CURRENCY_UNIT", "outputs": [ { "internalType": "uint256", "name": "",
"type": "uint256" } ], "stateMutability": "view", "type": "function" }, { "inputs": [ { "internalType": "address", "name": "asset",
"type": "address" } ], "name": "getAssetPrice", "outputs": [ { "internalType": "uint256", "name": "", "type": "uint256" } ],
"stateMutability": "view", "type": "function" }, { "inputs": [ { "internalType": "address[]", "name": "assets", "type": "address[]" } ],
"name": "getAssetsPrices", "outputs": [ { "internalType": "uint256[]", "name": "", "type": "uint256[]" } ], "stateMutability": "view",
"type": "function" }, { "inputs": [], "name": "getFallbackOracle", "outputs": [ { "internalType": "address", "name": "", "type":
"address" } ], "stateMutability": "view", "type": "function" }, { "inputs": [ { "internalType": "address", "name": "asset", "type":
"address" } ], "name": "getSourceOfAsset", "outputs": [ { "internalType": "address", "name": "", "type": "address" } ],
"stateMutability": "view", "type": "function" }, { "inputs": [ { "internalType": "address[]", "name": "assets", "type": "address[]" }, {
"internalType": "address[]", "name": "sources", "type": "address[]" } ], "name": "setAssetSources", "outputs": [],
"stateMutability": "nonpayable", "type": "function" }, { "inputs": [ { "internalType": "address", "name": "fallbackOracle", "type":
"address" } ], "name": "setFallbackOracle", "outputs": [], "stateMutability": "nonpayable", "type": "function" } ]
```

```

[Previous PoolConfigurator](#) [Next RewardsController](#) Last updated 6 months ago On this page \* [AaveOracle](#) \* [Methods](#) \* [View](#) \* [Write](#) \* [ABI](#)

Was this helpful?