

Voting

After a proposal's deposit reaches the `MinDeposit` value, the voting period opens. Bonded SCRT holders can then cast vote on it:

...

Copy `secretclitxgovvote \ [proposal-id] \ [option] \ [flags]`

...

...

Copy

Example

`secretclitxgovvote 1 yes --from [mykey]`

...

Flags

...

Copy

Flags: `-a, --account-number uint The account number of the signing account (offline mode only)` `-b, --broadcast-mode string Transaction broadcasting mode (sync|async|block) (default "sync")` `--dry-run ignore the --gas flag and perform a simulation of a transaction, but don't broadcast it` `--fee-account string Fee account pays fees for the transaction instead of deducting from the signer` `--fees string Fees to pay along with transaction; eg: 1.0uscrt` `--from string Name or address of private key with which to sign` `--gas string gas limit to set per-transaction; set to "auto" to calculate sufficient gas automatically (default 200000)` `--gas-adjustment float adjustment factor to be multiplied against the estimate returned by the tx simulation; if the gas limit is set manually this flag is ignored (default 1)` `--gas-prices string Gas prices in decimal format to determine the transaction fee (e.g. 0.1uscrt) (default "0.25uscrt")` `--generate-only Build an unsigned transaction and write it to STDOUT (when enabled, the local Keybase is not accessible)` `-h, --help help for vote` `--keyring-backend string Select keyring's backend (os|file|kwallet|pass|test|memory) (default "os")` `--keyring-dir string The client Keyring directory; if omitted, the default 'home' directory will be used` `--ledger Use a connected Ledger device` `--node string: to tendermint rpc interface for this chain (default "tcp://localhost:26657")` `--note string Note to add a description to the transaction (previously --memo)` `--offline Offline mode (does not allow any online functionality)` `-s, --sequence uint The sequence number of the signing account (offline mode only)` `--sign-mode string Chooses sign mode (direct|amino-json), this is an advanced feature` `--timeout-height uint Set a block timeout height to prevent the tx from being committed past a certain height` `-y, --yes Skip tx broadcasting prompt confirmation`

...

Last updated 1 year ago On this page Was this helpful? [Edit on GitHub](#) [Export as PDF](#)