

Namespace: v0_7_0

Interfaces

- [AppDataRootSchema](#)
- [Metadata](#)
- [OrderClass](#)
- [Quote](#)
- [Referrer](#)
- [UTMCodes](#)

Type Aliases

AppCode

TAppCode :string

The code identifying the CLI, UI, service generating the order.

Defined in

generatedTypes/v0.7.0.ts:15

Environment

TEnvironment :string

Environment from which the order came from.

Defined in

generatedTypes/v0.7.0.ts:19

OrderClass1

TOrderClass1 : "market" | "limit" | "liquidity" | "twap"

Indicator of the order class.

Defined in

generatedTypes/v0.7.0.ts:60

ReferrerAddress

TReferrerAddress :string

Defined in

generatedTypes/v0.7.0.ts:24

SlippageBips

TSlippageBips :string

Slippage tolerance that was applied to the order to get the limit price. Expressed in Basis Points (BPS)

Defined in

generatedTypes/v0.7.0.ts:52

UTMCampaign

TUTMCampaign :string

Track the performance of a specific campaign

Defined in

generatedTypes/v0.7.0.ts:36

UTMContent

TUTMContent :string

Track which link was clicked

Defined in

generatedTypes/v0.7.0.ts:40

UTMKeywordTerm

TUTMKeywordTerm :string

Track which keyword term a website visitor came from

Defined in

generatedTypes/v0.7.0.ts:44

UTMMedium

TUTMMedium :string

Tracks in which medium the traffic originated from (mail, CPC, social, etc.)

Defined in

generatedTypes/v0.7.0.ts:32

UTMSource

TUTMSource :string

Tracks in which medium the traffic originated from (twitter, facebook, etc.)

Defined in

generatedTypes/v0.7.0.ts:28

Version

TVersion :string

Semantic versioning of document.

Defined in

generatedTypes/v0.7.0.ts:11

Version1

TVersion1 :string

Semantic versioning of document.

Defined in

generatedTypes/v0.7.0.ts:23

Version2

TVersion2 :string

Semantic versioning of document.

Defined in

generatedTypes/v0.7.0.ts:48

Version3

TVersion3 :string

Semantic versioning of document.

Defined in

generatedTypes/v0.7.0.ts:56 [Previous v0_6_0](#) [Next v0_8_0](#)