1 Consider the SAT on PTA that you attempted.

If your roll number ends in an even number use Delta T_min =9 C,

If your roll number ends in an odd number use Delta T_min =11 C,

Design a HEN using

- 1. spaghetti design
- 2. MER using PDM rules

Compare the cost/area that you get with the cost/area that you calculated in HW 1

You may use the following information

U=0.001 MW/m^2 C

Heating is available at 300 C (Steam)

cooling is provided by cooling water at 15 C with a maximum return temperature of 30 C


Cost of heat exchanger 40000 + 500 A, where A is area in sq m

Cost of steam =1,20,000 (/MW/y)

Cost of cooling water= 10,000 (/MW/y)

Use annualization factor =0.25

Q2 Refer to the figure below. Evolve the HEN and reduce it to the absolute minimum number of HENs.



Legend: Process heat exchangers: A-A, B-B, C-C, D-D, E-E, F-F

Cooling utility: CU

Heating utility: HU

Heat duties in kW

Temperatures in °C are shown over the respective segments

Upload a single, neatly written/formatted pdf file. If you have scanned a file using a cell phone camera, make sure the final version is readable.

Name the file rollnumber_hw2.pdf.

eg. if your roll number is CH18B001, name your file as

CH18B001_hw2.pdf