

Getting Started with [Application 1] Platform Services API

The Consumption API enables a CRUD mechanism to consume [Application 1] data from the [Application 1] platform services, allowing requestors with on-demand [Application 1] data consumption.

In this guide, you'll learn how to request an access token and make a simple API call.

1. Prerequisites

Complete the following items before continuing with this guide:

- Get a program to make requests, such as [Postman](#) (preferred) or [Insomnia](#).
- [Request the \[PERMISSION LEVEL\]](#) `permission_type` .

2. Create an OAuth Application

This section shows how to create an OAuth Application with the required scopes for the API authorization mechanisms.

1. Go to your [\[BRAND\]'s Developer Portal OAuth Apps](#)
2. Create a new OAuth app with the following custom scopes:
 - `program:service.global::create:`
 - `program:service.global::read:`
 - `program:service.global::update:`
 - `program:service.global::delete:`

3. Request an Access Token

This section shows how to generate an access token for the API.

3.1 Okta Domains

The [Application 1] platform services leverage Okta credentials to authenticate requests.

Find the Host URL based on the development environment of your choice:

Okta Domain	Host
Prod	<code>https://brand.okta.com/url</code>
QA	<code>https://brand.okta.com/url</code>
Dev	<code>https://brand.okta.com/url</code>

3.2 Query Parameters

The host URL accepts the following query parameters:

- `client_id` : Specifies the application client ID.
- `client_secret` : Specifies the application's environment secret.
- `grant_type` : Specifies the authentication method.
- `scope` : Specifies the request method type for your access token.

3.2.1 Get client_id

1. Go to [\[BRAND\]'s Developer Portal OAuth Applications](#)
2. Copy the value from the "Client ID" column associated to the OAuth Application that you created on [step 2](#).
3. Paste the value on the `client_id` query parameter.

3.2.2 Get client_secret

1. Go to [VAULT SYSTEM](#).
2. Under Applications, Select PROGRAM-[Application 1]-APP
3. If you're requesting access to the production environment, click on **prod**. Otherwise, click on **preprod**.
4. Copy the value `okta_client_secret`
5. Paste the value on the `client_secret` query parameter.

3.2.3 Get grant_type

Enter "`client_credentials`".

3.2.4 Get scope

1. Go to [\[BRAND\]'s Developer Portal OAuth Applications](#).
2. Click on the OAuth Application that you created on [step 2](#).
3. Under Custom Scopes, copy one or more scopes for your access token.

NOTE

The authorization type variable locates at the end of the scope string, example:

```
program:service.global::create:
-----~~~~~~
```

4. Paste the value on the `scope` query parameter.

3.3 Query the Host

This is an example to request a QA read access token:

POST

```
https://[BRAND].okta.com/token?client_id=[client_id]&client_secret=[client_secret]&grant_type=c
```

This is the structure of the query:

- Host: `https://[BRAND].okta.com`
- Endpoint: `/token`
- Query Parameters: `?client_id=[client_id]&client_secret=[client_secret]&grant_type=client_credentials&scope=program:service.global::read:`
- Content-Type: `application/x-www-form-urlencoded`
- Cache-Control: `max-age=1800`

Replace the variables from the query parameters with the data from [step 3.2](#).

This is an example of the access token:

```
r
```

```

1
"token_type": "Bearer",
"expires_in": 3600,
"access_token": {yourAccessToken},
"scope": "{scope1} {scope2} ... {scopeN}"
}

```

To see more details about your access token, use a tool like jwt.io.

4. Stack Mapping

The PROGRAM-[Application 1] GraphQL API deploys in:

Platform Stack	AppSync URL (Native)	CDN URL
PROD		
UAT	<code>https://id.region.amazonaws.com/graphql</code>	<code>https://url.com</code>
STG	<code>https://id.region.amazonaws.com/graphql</code>	<code>https://url.com</code>
QA	<code>https://id.region.amazonaws.com/graphql</code>	<code>https://url.com</code>
DEV	<code>https://id.region.amazonaws.com/graphql</code>	<code>https://url.com</code>

NOTE

The URLs might change in newer release versions, if you're having issues visit the [Changelog](#).

5. Request Sample Query

Follow the steps to request a sample query:

1. Go to Postman or Insomnia
2. Create a new POST request
3. Enter a CDN URL from the [Stack Mapping](#) table.

NOTE

Ensure your access token matches the CDN URL Platform Stack environment.

4. Enable bearer authentication and enter your `access_token`.
5. Enter the following data in Query:

```

query SearchPetStore($limit: Int! $offset: Int!) {
  searchPetStore(limit: $limit, offset: $offset) {
    count
    total_count
    next_available
    last_id
    Records {
      pet {
        name
        isAvailable
      }
    }
  }
}

```

```
}
```

6. Enter the following GraphQL variables:

```
{  
  "limit": 3,  
  "offset": 0  
}
```

7. Submit the request, you must receive the following response:

```
{  
  "data": {  
    "searchPetStore": {  
      "count": 3,  
      "total_count": 1020,  
      "next_available": null,  
      "last_id": "a123b456-c789-012d-345e-678f9g0h1i2j",  
      "Records": [...]  
    }  
  }  
}
```

Good work, you're ready to explore API.