

SIO 207A: Fundamentals of Digital Signal Processing

Class 9

Florian Meyer

Scripps Institution of Oceanography
 Electrical and Computer Engineering Department
 University of California San Diego




UC San Diego
 JACOBS SCHOOL OF ENGINEERING

0

Time Domain Convolution

- By implementing a time domain convolution via multiplication in the frequency domain computational savings can be achieved




1


Linear Convolution vs Circular Convolution

- Sampling in one domain implies periodicity in the other domain. Thus by representing the signals using a DFT (or FFT) we imply that the underlying signals are periodic
- Recall that multiplication of DFTs/FFTs implies the resulting convolution to be circular and not linear

Linear Convolution




Circular Convolution (via 4-point DFTs/FFTs)




2

Convolution via Multiplication in Frequency Domain

- Convolution via multiplication in frequency domain using 8-point DFTs/FFTs by zero padding of the sequences




- DFT/FFT implies periodic extension of sequence



- Recall thinking of circular convolution as if one is painting the two functions on circular cans which are stacked on top of each other and rotated

3


Convolution by Segments



4

4


Convolution by Segments



5

5


Convolution by Segments



6

6


Convolution by Segments



7


7

Convolution by Segments




8

Convolution by Segments



9

Convolution by Segments




- Similar pictures describe the circular convolution from the 1st segment, 2nd segment, etc; where each segment has a length of L points
- Partial results at the end of one segment are completed by the partial results at the beginning of the next segment. $y[n]$ is obtained by adding together the overlapped segment convolutions

10

10


Convolution by Segments (Alternative Method)



11

11


Convolution by Segments (Alternative Method)



12

12


Convolution by Segments (Alternative Method)



13

13


Convolution by Segments (Alternative Method)



14


14

Convolution by Segments (Alternative Method)



15

Convolution by Segments (Alternative Method)



see also Section 8.7 in
Oppenheim & Schafer, 1999

- $y[n]$ is obtained by discarding the first $M-1$ points in each segment convolution and then concatenating the resulting time series together

16

16