

SIO 207A: Fundamentals of Digital Signal Processing

Class 16

Florian Meyer

Scripps Institution of Oceanography
Electrical and Computer Engineering Department
University of California San Diego




UC San Diego
JACOBS SCHOOL OF ENGINEERING

0

Windowing

- Windows are applied only before we perform a DFT/FFT for analysis in the frequency domain
- We always apply the window if the DFT/FFT length is shorter than the length of the signal
- We never apply the window if the DFT/FFT length is longer than the length of the signal (transient signal case)
- Windows are never applied if we perform a DFT/FFT for filtering purposes, i.e., to replace the convolution in the time domain by multiplication in the frequency domain



$$\text{DFT/FFT: } X(k) = \sum_{n=0}^{N-1} \boxed{w[n]} x[n] e^{-j \frac{2\pi}{N} nk}$$

window function

1


1

IIR Filters

Homework 7 – Matlab functions

“buttord”, “butter”,
 “cheb1ord”, “cheby1”,
 “cheb2ord”, “cheby2”,
 “ellipord”, “ellip”

see also Sections 7.1.1,
 7.1.2, 7.1.3, and Appendix B
 in *Oppenheim & Schaffer,*
 1999





$$y[n] = \sum_{k=1}^N a_k y[n-k] + \sum_{r=0}^M b_r x[n-r]$$

Matlab filter design functions will provide coefficients a_k and b_r .

2

Transformation Techniques


- **Transformation Techniques:** Take advantage of an analog filter design and transform it into discrete time domain
 - **Impulse invariant design** (sample continuous-time impulse response)



Sampling causes aliasing; thus, this approach is never used in practice


- **Bilinear transformation**

$$H(z) = H_a(s) \Big|_{s = \frac{2}{T} \frac{1-z^{-1}}{1+z^{-1}}}$$



3


Bilinear Transformation



- Specify filter in discrete-time domain
- Map desired frequency response at critical frequencies to continuous time-domain
- Choose analog filter that meets filter specifications
- Transform continuous-time filter to discrete-time using bilinear transformation

4

Butterworth Filter



Nth order filter

Critical parameters N and Ω_c

$$|H_a(j\Omega)|^2 = \frac{1}{1 + \left(\frac{\Omega}{\Omega_c}\right)^{2N}}$$


Note: No ripples passband or stopband

5

Chebyshev Filter

$$|H_a(\Omega)|^2 = \frac{1}{1 + \epsilon^2 V_n^2\left(\frac{\Omega}{\Omega_c}\right)} \quad (\epsilon > 0)$$


V_n are Chebyshev polynomials



6

Elliptic Filter

$$|H_a(\Omega)|^2 = \frac{1}{1 + \epsilon^2 U_n^2(\Omega)} \quad \text{where } U_n(\Omega) \text{ is a Jacobian elliptic function}$$



7