

Clean Deploy — Quick Install Guide

Get a Dynatrace MCP workspace running in 5 minutes.

Prerequisites

- Node.js 18+ — nodejs.org
- VS Code with GitHub Copilot (Chat enabled)
- Dynatrace Platform Token with required scopes

Works on macOS, Windows, and Linux. Platform-specific commands are noted below.

1. Download the Template

Download a clean copy of the working folder, using web download or commands, from:

<https://github.com/mf-dynatrace/MCP-cleanDeploy>

macOS / Linux (Terminal):

```
git clone https://github.com/mf-dynatrace/MCP-cleanDeploy.git my-client-workspace
cd my-client-workspace
```

Windows (PowerShell or CMD):

```
git clone https://github.com/mf-dynatrace/MCP-cleanDeploy.git my-client-workspace
cd my-client-workspace
```

2. Create Your .env

macOS / Linux:

```
cp .env.example .env
```

Windows (PowerShell):

```
Copy-Item .env.example .env
```

Windows (CMD):

```
copy .env.example .env
```

Open `.env` in any text editor and fill in these three values:

```
DT_ENVIRONMENT=https://YOUR_TENANT_ID.apps.dynatrace.com
DT_PLATFORM_TOKEN=dt0s16.XXXXXXXX.XXXXXXXX...
MCP_USER_ID=your.email@company.com
```

3. Token Scopes

Create a **Platform Token** in Dynatrace with:

Scope	Required For
app-engine:apps:run	MCP server
storage:logs:read	Log queries
storage:events:read	Event queries
storage:spans:read	Trace/span queries
storage:bizevents:read	Business events
storage:metrics:read	Metric queries
storage:entities:read	Entity lookups
storage:user.sessions:read	RUM sessions (optional)
storage:user.events:read	RUM events (optional)

4. Open in VS Code

macOS / Linux / Windows:

```
code .
```

If `code` is not recognised on macOS, open VS Code → `Cmd+Shift+P` → "Shell Command: Install 'code' command in PATH".
On Windows, the VS Code installer adds `code` to PATH automatically.

The MCP server auto-starts via `.vscode/mcp.json` — no install step needed.
It runs: `npx -y @dynatrace-oss/dynatrace-mcp-server@latest`

5. Verify Connection

In Copilot Chat, ask:

```
"What Dynatrace environment am I connected to?"
```

If it responds with your tenant ID, you're connected.

6. Replace Placeholders

Search and replace across all files:

Placeholder	Replace With
[CLIENT_NAME]	Customer name
[TENANT_ID]	Dynatrace tenant ID
[INDUSTRY]	Customer industry
[WEBSITE_URL]	Customer website URL

Tip: You can ask your LLM to mass-change these by prompting:
"Replace all placeholders with the correct information, prompt with discovered values before writing to files"

Feature Flags (Optional)

All default to `yes`. Set to `no` in `.env` to disable:

Flag	Effect when <code>no</code>
MCP_GRAIL_ONLY	Enables Gen 2 USQL/classic APIs
MCP_USE_USER_VARIABLE	Skips user identity on events
MCP_SEND_TRACKING_EVENTS	Disables query tracking

File Structure (Key Files)

`.env`
`.vscode/mcp.json`
`.github/copilot-instructions.md`
`CLAUDE.md`
`reference/`
`skills/`
`example/`

← Your credentials (git-ignored)

← MCP server config (auto-starts)

← Copilot behaviour rules

← Claude/Anthropic instructions

← Self-updating knowledge base

← DQL domain knowledge (12 files)

← Sample dashboards & workflows

First Session Checklist

- ☐ `.env` configured and connection verified
- ☐ Placeholders replaced in `CLAUDE.md` and `copilot-instructions.md`
- ☐ Run `find_entity_by_name` to discover key services (FREE)
- ☐ Update `reference/Entities_Reference.md` with discovered IDs
- ☐ Run a BizEvents summary to discover event types
- ☐ Update `reference/BizEvents_Reference.md`

Troubleshooting

Problem	Fix
MCP not connecting	Check <code>DT_ENVIRONMENT</code> URL format (must be <code>*.apps.dynatrace.com</code>)
Auth errors	Verify token scopes match table above
"Not authorized for table"	Add missing <code>storage:*.read</code> scope to token
Copilot ignoring instructions	Ensure <code>.github/copilot-instructions.md</code> exists at workspace root
High query costs	Read <code>reference/MCP_Query_Optimization_Guide.md</code>