

TECHNICAL DEVELOPMENT CENTER

Bluetooth protocol, 13.10.2017 For Fish Feeder DOMOVOY V.4.0.2

Use protocol Bluetooth 2.0. Data transfer speed: 9600 bod. The data is transmitted by ASCII characters. End of line is character decimal code 10. After sending the command, the feeder returns a response specific to each command. Commands and answers are given below.

Time settings:

settime:*hh*:*mm hh*-hour 00-24; *mm*-minutes 00-59

Possible responses:

Error:timeHour is not valid Error:timeMin is not valid

OK:time set

Feeding time settings:

setalarm*N*:*hh*:*mm* N-feeding number 1-4; *hh*-hour 00-24; *mm*-minutes 00-59

Possible responses:

Error:N is not valid Error:alHour is not valid Error:alMin is not valid OK:alarm set

Retraction settings:

setretraction: N - 0..1; 0 – do not use retraction; 1 – use retraction

Possible responses:

Error:Retract can be 0 or 1

OK:retraction set

Feeding dose settings:

setmotorturn: NNN NNN- the number of revolutions of the screw 0...MaxTurn. MaxTurn=100

Possible responses:

Error:Turn less or equal 0 Error:Turn is too large OK:motorturn set

Test feeding mode:

motortest

Possible responses:

OK:Test feeding

Request of current time:

gettime

Possible responses:

OK:time: hh:mm:ss hh-hour 00-24; mm-minutes 00-59; ss-seconds 00-59

Request of feeding time:

getalarmN

Possible responses:

Error:N is not valid

OK:alarm*N:hh:mm* N-feeding number 1-4; hh-hour 00-24; mm-minutes 00-59

Request of retraction:

getretraction

Possible responses:

OK:retraction: N - 0..1; 0 - do not use retraction; 1 - use retraction

Request of feeding dose:

getmotorturn

Possible responses:

OK:motorturn:*NNN NNN*- the number of revolutions of the screw 0..MaxTurn. MaxTurn=100