

Screening LCA and TEA of Municipal Solid Waste Recovery Pathways in Indonesia

Methodology v3.2: ex-ante decision support before facilities exist — 2025 tonnage baseline, auditable parameters with verified secondary data, carbon-inclusive cost at fixed carbon values, decision rules, break-even targets and the value of information

Muhammad Fachri Ridwan — Master of Environmental Management, The University of Queensland
Supervisor: Prof. Anthony Halog — October 2026 — Companion code: `msw_pathway_model_v3.py` / `MSW_pathway_model_v3.ipynb`; user tool: `MSW_Decision_Tool_Colab.ipynb`

What v3.2 does and what it shows

- **Ex-ante decision support.** None of the six options exists as a facility in the 21 locations. The model is a screening tool for local governments, planners and funders *before* a feasibility study or tender: it tells them under which conditions each option is worth pursuing, which performance an option must reach to beat a sanitary landfill, and which local data are worth collecting first. This, not the ranking of 21 cases, is the contribution.
- **Secondary data re-checked.** 23 secondary values were re-verified against their sources (Section 6.1): 5 were corrected (RDF O&M and price, Sumatera grid factor, the WtE and RDF benchmarks), landfill-gas collection was widened to 0.20–0.80, and status V is now kept only for the four values confirmed in the source text. Benchmarks that could not be confirmed were removed.
- **Carbon-inclusive cost, fixed carbon values.** Options are ranked by $C + pG/1000$ (USD/t), called the carbon-inclusive cost because health and local pollution are not valued. Results are given for fixed carbon values 0, 2 (the UU 7/2021 carbon tax), 25, 50 and 100 USD/t CO₂e with Monte Carlo standard errors (at most 0.008).
- **Main result.** At central values the sanitary landfill with flare has the lowest carbon-inclusive cost in all 21 locations up to 50 USD/t; at 100 USD/t RDF + AD is best in 20 locations and WtE in 1. With uncertainty, RDF + AD is the most probable option at 100 USD/t in 18 locations (median $P = 0.60$). Its abatement cost against the landfill is 73 (53 to 99) USD/t CO₂e.
- **What decides.** Food separated at source makes AD preferable above about 30–45 USD/t; the Perpres 109/2025 tariff with at least 1,000 t/day and LHV of 7 MJ/kg makes WtE preferable; RDF + AD needs a high carbon value and a kiln within about 300 km. The 100 USD/t result is fragile: the high moisture bound or a 22% lower RDF heating value returns the choice to the landfill in 17 and 17 of 21 locations.
- **What to measure first.** The expected value of perfect information is 1.05 USD/t at 50 USD/t and 3.18 USD/t at 100 USD/t (median); waste characterisation (moisture, composition) and landfill-gas performance carry most of it. These are the measurements a city should fund before committing to a technology.
- **AD on mixed waste made realistic.** Food separated mechanically from mixed waste is given 0.6 (0.35–0.85) of the methane yield of source-separated food and 5 (0–10) USD/t extra pre-treatment; the optimistic case is a scenario.
- **Reproducible.** 78 of 78 validation checks pass, including an explicit hand recalculation for Kota Padang; a Colab notebook runs everything for new cities (Section 12).

1 Purpose, scope of the update and vocabulary of evidence

Purpose: ex-ante decision support. Indonesian cities must choose among WtE, RDF, AD and improved landfilling before any such facility is built, usually with no local performance data. This study is therefore a modelling study: it does not evaluate existing plants but estimates, before investment, under which city and waste-system conditions each option would become preferable. Its outputs are designed for the stakeholders who make that choice (city and regency environment agencies, Bappeda, the Ministry of Environment, PLN and cement companies as offtakers, and funders): (i) decision rules stated in observable conditions, (ii) break-even targets that a tender or pilot must reach, and (iii) a ranking of the data worth collecting first, expressed in USD per year. Results are screening-level and must be confirmed by a feasibility study.

This document updates the v2 methodology with the research package of October 2026 (folders 02 to 04). The package was read in the order its `START_HERE` file prescribes: the v2 code and PDF, then the assumption audit (`ASSUMPTION_SOURCE_AUDIT.md`), which overrides the interpretation of the older allocation workbook, then the 2025 baseline files, then the fraction-literature files. The SHA-256 of every source file was checked against the package manifest before use. The equations, system boundary and decision rule of v2 are kept; what changes is where numbers come from, how their status is recorded and how the 2025 baseline is formed.

Every value in the database carries one of the following statuses. A blank cell always means *unknown or not applicable*; it is never read as zero.

Status	Meaning	Example
local measurement	Reported for the location by its RIPS document	RIPS wet-mass composition, Kab. Bogor 2022
literature default	Published default for a category, not for the location	IPCC 2006 Table 2.4 DOC of food, 0.38 (dry)
parent-category proxy	A parent default assigned to a sub-fraction; not a sub-fraction measurement	Food DOC for 1.2.3 unavoidable animal-derived food
foreign benchmark	Measured elsewhere on a different waste stream	Edjabou et al. (2015) Danish residual household waste
assumption / prior	Analyst choice, to be defended or replaced	Organic split 85/15 (A01); moisture as received
scenario	Alternative value run to show sensitivity, never a baseline	Serang 14% target; rubber DOCf 0.5
gap	No defensible number found; left blank, scenario if the model needs one	Rubber/leather DOCf; WEEE material composition

Table 1: Vocabulary of evidence used in every CSV and table of this document.

2 Goal, functional unit and system boundary (unchanged)

The research question remains: *under what Indonesian city and waste-system conditions does each recovery pathway become preferable?* The functional unit is the management of 1 tonne of mixed MSW, wet weight, as received at the gate of the treatment facility, with the composition of the location, in the reference year 2025. Six options are compared within one LCA/TEA boundary, from the facility gate to final disposal of residues and delivery of products, with system expansion for displaced electricity, coal and polypropylene: sanitary landfill with flare (SL), WtE (S1), RDF to cement kiln (S2), AD of food waste (S3), PHB from landfill gas (S4) and integrated RDF + AD (S5). Two baselines are reported: open dump (OD) and sanitary landfill (SL). Climate change is assessed with GWP100 of IPCC AR6 (GWP20 as a sensitivity case); cost is a net levelised cost in USD per tonne (AACE class 5). These choices and their justification are those of v2, Sections 2 and 3.

3 Data harmonisation for the 2025 baseline

3.1 Three years, kept apart

Each location now carries a composition sampling year t_c , a tonnage source year t (blank when it is unverified) and the baseline year 2025. Tonnage is harmonised with

$$Q_{2025} = Q_t (1 + g)^{2025 - t} \quad M_{2025}^d = M_t^d (1 + g)^{2025 - t}, \quad M_{2025}^n = M_t^n (1 + g)^{2025 - t} \quad (1)$$

with g the RIPS growth rate where one is given (6 locations) and otherwise the median of those six rates, 1.73%/yr (assumption H11, range 0.65 to 2.54%). Domestic and non-domestic streams use the same factor, so $M_{2025}^d + M_{2025}^n = Q_{2025}$. The exponent is zero when the tonnage already refers to 2025. The flag *tonnage_already_2025* is set in the CSV and read by the parser, which uses Q_{2025} directly; an assertion in the model stops the run if the tonnage it computes differs from the CSV baseline (single-projection guard).

Class	n	Rule (central)	Locations
stated in source table	12	projected once from the stated year	Kota Padang, Kab. Bogor, Kab. Serang, Kota Denpasar, Kab. Cianjur, Kab. Indramayu, Kab. Pati, Kab. Pandeglang, Kab. Temanggung, Kab. Pekalongan, Kota Pekalongan, Kota Magelang
overview index year unverified	8	used as reported; alternative projected from t_c	Kota Semarang, Kab. Brebes, Kab. Nganjuk, Kab. Magelang, Kab. Sragen, Kab. Kutai Kartanegara, Kab. Kendal, Kab. Wonogiri
RIPS projection for 2025	1	used as reported; flagged as a projection	Kab. Pemalang

Table S1: Tonnage-year classes. The overview class also covers Kota Semarang, Kab. Sragen and Kab. Kutai Kartanegara, whose source pages cite the same overview index although v2 and the package projected them from the composition year.

Decision on overview totals. The package treated five overview totals as 2025 values on the basis of a keyword in free-text notes, while three other rows citing the same overview index were projected. Neither the year of the overview index nor its relation to the composition year is shown in the rows held. v3 therefore applies one rule to all eight: the total is used as reported (no growth applied, so no double projection if it is already current) and its year is left blank with flag T1. The alternative, that the total dates from the composition year, is computed for every row ($Q_{2025_alt_tpd}$) and run as the scenario *tonnage_overview_projected*. It raises tonnage by up to 21% (Kab. Kendal, composition 2014) and changes no most-probable pathway (Section 8). Kab. Pemalang's 2025 tonnage is itself a RIPS projection (population $\times$ 0.31 kg/cap/day) and is flagged T2.




Figure 1: 2025 tonnage by location and tonnage-year class. Hatched: the projected alternative for overview totals. Ticks: reported source value Q_i .

3.2 Composition: a sampling-year proxy, normalised per stream

RIPS compositions are wet-mass percentages measured in the sampling year with the SNI 19-3964-1994 method. No source gives a defensible annual composition trend, so the shares are used for 2025 unchanged and labelled *RIPS sampling-year composition held constant as 2025 proxy* (flag C0). Growth is never applied to percentages. Rounded source totals (99.99 to 100.10%) are normalised per stream k and the factor is stored:

$$S_j^{(k)} = \frac{x_j^{(k)}}{\sum_i x_i^{(k)}}, \quad f^{(k)} = \frac{100}{\sum_i x_i^{(k)}}, \quad S_j = \frac{M_{2025}^d S_j^{(d)} + M_{2025}^n S_j^{(n)}}{M_{2025}^d + M_{2025}^n} \quad (2)$$

Kab. Pemalang (100.10%) has $f = 0.9990$. Blank category cells are absent categories: glass is *reported* in 15 locations, *folded into lain-lain* in 5 and *not reported* in Kota Padang, and the three cases are flagged separately (C3, C4). Rules L (organic aggregate split with share γ) and W (kayu treated as garden) of v2 are kept as sampled harmonisation priors. Semarang and Nganjuk report a non-domestic composition but no non-domestic tonnage; it receives zero weight (flag C6). All compositions refer to waste at generation or collection, not at the landfill gate.

3.3 Managed waste and Table 5

The managed share μ is used only in the managed-tonnage scenarios, where it scales the plant size: $Q_{\text{managed}} = \mu Q_{2025}$. Holding μ constant from its source year is a scenario assumption, not a 2025 observation. The package filled the seven blanks of v2 with candidates whose definitions differ; v3 keeps every candidate visible instead of choosing by numerical similarity:

Indicator family	Locations	Definition and status
RIPS status index (M1)	14 legacy + 5 candidates (Bogor, Denpasar, Cianjur, Indramayu, Semarang)	Same index series as v2 Table 5. Its definition and denominator are not documented in the package rows; comparable only within the series.
Local service / handling indicators	Bogor 35.15%, Denpasar 96.91%, Cianjur 30.36%, Indramayu 61.52%, Semarang 59.43%	Urban managed waste, reduction + handling, or service level. Different numerators and denominators from the index; kept as alternatives, not merged.
Padang, derived	93.71% (upper), 71.82% (TPA delivery only)	(141.76 recovery + 465.08 to TPA) / 647.57. Source is a draft feasibility study (p. 94); the recovery may be a potential and the denominator is the 2023 RIPS total. Provisional; not an observed managed share.
Serang, local observed	7.45% (14% target as scenario only)	Existing condition from the master-plan executive summary (p. 154); the 14% is a 2025 service target (pp. 180-181).

Table S2: Families of managed-waste indicators held in the database.

Two series are run and reported side by side. **M1** uses the status index only: 19 locations, Padang and Serang n.a. **M2** uses the local indicator where one is held (Padang at its 71.82% lower bound, because the recovery numerator is

unverified) and the status index elsewhere; it mixes definitions by construction and is labelled so. Neither series implies that all 21 locations have the same indicator. $Q_{\text{managed}} \leq Q_{2025}$ holds for every value.

Location	Q2025 t/d	Status index	Local	M1 t/d	M2 t/d	Status of the local value
Kota Padang	656	n.a.	93.71% (71.82% low)	n.a.	471	derived, provisional (not an observed managed share)
Kab. Bogor	2,891	22.10%	35.15%	639	1016	local indicator with a different definition from the status index
Kab. Serang	1,187	n.a.	7.45%	n.a.	88	local observed (existing condition)
Kota Denpasar	918	10.73%	96.91%	99	890	local indicator with a different definition from the status index
Kab. Cianjur	1,114	2.67%	30.36%	30	338	local indicator with a different definition from the status index
Kab. Indramayu	1,152	8.59%	61.52%	99	709	local indicator with a different definition from the status index
Kota Semarang	1,190	8.27%	59.43%	98	707	local indicator with a different definition from the status index
Kab. Brebes	1,033	2.32%	-	24	24	
Kab. Nganjuk	744	11.33%	-	84	84	
Kab. Pati	691	18.38%	-	127	127	
Kab. Magelang	671	10.45%	-	70	70	
Kab. Pandeglang	527	29.80%	-	157	157	
Kab. Pemalang	484	16.11%	-	78	78	
Kab. Temanggung	423	8.65%	-	37	37	
Kab. Pekalongan	560	15.58%	-	87	87	
Kab. Sragen	402	20.24%	-	81	81	
Kab. Kutai Kartanegara	373	55.92%	-	209	209	
Kab. Kendal	437	27.41%	-	120	120	
Kab. Wonogiri	422	20.02%	-	84	84	
Kota Pekalongan	164	48.16%	-	79	79	
Kota Magelang	50	68.49%	-	34	34	

Table 5: Managed waste in 2025 (constant-share scenario). Status-index values of the 14 original locations are carried over from v2 without re-audit of their definition.




Figure 2: Managed share by indicator family. Grey lines join the two values held for the same location.

3.4 Waste-fraction taxonomy: Level I, II and III

The taxonomy follows the tiered approach of Edjabou et al. (2015): 10 Level I material groups, 36 harmonised Level II fractions (aluminium foil merged into metal packaging, which gives the 36 stated in the source prose while the printed Table 2 lists 37) and a catalogue of 56 Level III refinements. The catalogue is **provisional**: the printed source table has duplicated codes (condoms), WEEE printed under 10.3, index notation for plastics and metals, and no explicit food refinements. The six Level III food sub-fractions are a modelling interpretation. The 56 entries are

neither 56 measurements nor a complete terminal partition.

All joins use the key (level, code), stored as text so that codes such as 6.1 and 6.10 cannot collide. The crosswalk (*taxonomy_crosswalk.csv*) records for every key its parent, the model fraction it maps to and a note where the mapping is not one-to-one. Three cases matter. (i) The ferrous/non-ferrous split (6.x.1, 6.x.2) has the parent *all metal* and crosses 6.1 and 6.2; it is excluded from the terminal partition and kept as a cross-cutting attribute. (ii) The local label of 4.3, *cartons, plates and cups*, is broader than the Danish *beverage cartons*, and beverage cartons appear again as 4.4.1; no Danish value is copied to 4.3. (iii) Level I *Gardening* and *Miscellaneous combustibles* are heterogeneous and do not map to one IPCC category.

Mass balance. The Level III detail file holds only catalogued refinements and covers 76.8 to 93.7% of each stream; it is not forced to 100%. Where a full terminal partition is needed, it is built from the 54 Level III leaves (56 minus the two cross-parent metal rows) and the 24 Level II fractions without children (including 6.1 and 6.2): **78 leaves**, each stream summing to 100%. Because every catalogued parent is fully split by its priors, no residual leaf is needed (the code would create one, labelled *X.R unrefined remainder*, if a gap appeared).

Benchmarks and conditional shares. The Danish single- and multi-family values (Edjabou et al. 2015, Tables 3 and 4) are percentages of total residual household waste. They are a foreign benchmark: not an Indonesian city measurement and not non-domestic waste. A conditional share within the parent is computed only for complete sibling sets on the same basis:

$$p(c | \pi) = \frac{x_c}{\sum_{c' \in \text{ch}(\pi)} x_{c'}} \quad \text{only if every } x_{c'} \text{ is observed} \quad (3)$$

This holds for 11 sibling sets (food, gardening, paper, plastic, metal, glass, miscellaneous combustibles and special waste at Level II; packaging plastic, plastic film and packaging glass at Level III). Board (4.3 missing), inert (9.3, 9.4 missing), garden waste (2.2.4), miscellaneous paper (3.7.4, 3.7.5) and miscellaneous board (4.4.1, 4.4.2) are incomplete and receive no conditional share; partial subsets are not renormalised. Reported zeros are kept; a pseudocount for a Dirichlet prior would be a separate modelling decision.

Allocation priors. The Level I/II/III compositions (*composition_level*_2025.csv*) rescale the package allocations to the 2025 stream masses and label every split with its audit ID. The audit found that several are priors without an Indonesian or literature basis (A01 organic 85/15, A03 lain-lain 80/20, A05 gardening 2/98 where Table 3 gives 9.2/90.8, A09 B3 20/80 where Table 3 implies 28.6/71.4, and the equal-share Level III splits); others are rounded Danish ratios (A04, A06 to A08). These allocations are database content for future calibration. **They are not used by the model**, which computes on the ten model fractions mapped directly from the RIPS categories (Figure 6).




Figure 3: Status of material parameters by level (left) and availability of Danish composition benchmarks (right).

3.5 Material parameters (Table 2 and the detailed table)

IPCC (2006) Volume 5 Table 2.4 supplies default dry matter, DOC, total carbon and fossil-carbon share for the parent categories; the 2019 Refinement Table 3.0 supplies DOCf: 0.70 for food and garden/grass, 0.50 for paper, textile and nappies and 0.10 for wood and branches. DOC is on a dry basis and multiplies dry mass; the wet value is

$$\text{DOC}_{\text{wet}} = \text{DOC}_{\text{dry}} (1 - w) \quad \text{CH}_4 = 10^3 k_D \text{MCF} F \frac{16}{12} \sum_j m_j (1 - w_j) \text{DOC}_{\text{dry},j} \text{DOCf}_j \quad (4)$$

so moisture is applied once. With IPCC moisture the check reproduces the IPCC wet DOC values (food 0.15, garden 0.20, paper 0.40, wood 0.43, textile 0.24, rubber 0.39) within 0.005. Landfill DOCf is not the biochemical methane potential of a digester: AD uses its own yield parameter (A8).

Fraction	w IPCC	w as received (range)	DOC dry	DOCf (status)	C	φ	h dry MJ/kg (status)	τ (status)
food	0.60	0.75 (0.65-0.82)	0.38	0.70 (IPCC 2019)	0.38	0.00	16.5 (legacy)	0.10 (legacy A)
garden	0.60	0.55 (0.40-0.65)	0.49	0.70 (IPCC 2019)	0.49	0.00	16.0 (legacy)	0.40 (legacy A)
paper	0.10	0.35 (0.15-0.50)	0.44	0.50 (IPCC 2019)	0.46	0.01	16.0 (legacy)	0.70 (legacy (Nasrullah))
wood	0.15	0.25 (0.15-0.40)	0.50	0.10 (IPCC 2019)	0.50	0.00	18.0 (legacy)	0.60 (legacy (Nasrullah))
textile	0.20	0.35 (0.15-0.50)	0.30	0.50 (IPCC 2019)	0.50	0.20	18.5 (legacy)	0.70 (legacy A)
rubber	0.16	0.15 (0.05-0.25)	0.47	blank; (gap: scenario 0-0.5)	0.67	0.20	23.0 (legacy)	0.60 (legacy A)
plastic	0.00	0.22 (0.05-0.35)	0.00	0.00 (n/a)	0.75	1.00	30.5 (Gotze 2016, TS)	0.80 (legacy (Nasrullah))
metal	0.00	0.05 (0.02-0.08)	0.00	0.00 (n/a)	0.00	0.00	0.0 (-)	0.00 (-)
glass	0.00	0.02 (0.01-0.03)	0.00	0.00 (n/a)	0.00	0.00	0.0 (-)	0.00 (-)
other	0.10	0.25 (0.10-0.40)	0.00	0.00 (n/a)	0.03	1.00	0.0 (-)	0.10 (legacy A)

Table 2: Properties of the ten model fractions (*table2_model_fraction_parameters.csv*). w, DOC, C and φ: IPCC 2006 Table 2.4 defaults, global, not Indonesia-specific. As-received moisture: analyst assumption carried from v2, calibrated to bulk moisture at Indonesian transfer points (Prabowo et al. 2019). DOCf: IPCC 2019 Table 3.0. h: legacy values cited in v2 to Tchobanoglous et al. (1993), not re-verified, multiplied by k_h ; plastic: aggregate median LHV of 30.5 MJ/kg TS (Götze et al. 2016, Section 3.2.3), not resin-specific and not multiplied by k_h . τ: legacy RDF transfer coefficients; paper, plastic and wood informed by measurements on commercial and industrial waste (Nasrullah et al. 2014), the others analyst assumptions.

Moisture decision. IPCC moisture describes waste as generated; the functional unit is waste as received at the gate, wetter after collection. The main case keeps the v2 as-received values, which bring bulk moisture into the measured Indonesian range, and the IPCC defaults are run as the scenario *moisture_IPCC_default*. Both are internally consistent because DOC, carbon and heating value always multiply the same dry mass. The choice matters (Section 8): it is the single data assumption that changes the most probable pathway most often.

Detailed parameters (*fraction_parameters_L1_L2_L3.csv*, 102 rows). Level II/III values are IPCC parent proxies and keep that status; IPCC did not measure these sub-fractions. Grass, woody material and soil are separated: plant material takes the garden proxy (DOCf 0.70), woody plant material and straw the wood proxy (DOCf 0.10) and humid soil the inert proxy (DOC 0). Composite products receive no whole-product value: coated cartons and cups (4.3, 4.4.1, 4.4.2) keep the paper proxy only for their fibre portion, and composite film, batteries, other HHW, WEEE, tampons and condoms are blank until their material composition is known. Animal-derived food keeps the food proxy with a warning that bones and eggshells lower its degradable carbon. Rubber and leather have no verified DOCf and stay blank. LHV and τ are blank for all sub-fractions. Metal and glass moisture is blank at Level II/III because contamination moisture was not measured; the IPCC dry-matter default of 100% applies at Level I only. Literature from 2026 (the Malang plastic study) is retained as a material benchmark, not as 2025 composition data for the study locations.

Weighted by the terminal composition, a Level II/III DOC value is known for 83 to 96% of each stream's wet mass, moisture and carbon for 78 to 93% and DOCf for 52 to 85% (*outputs/11_parameter_coverage_L2L3.csv*). A Level II model cannot yet be run without imputation, which is why the model stays on the ten model fractions.

4 Model and metamodel

The computation is split into a data layer and a model layer (Figure 5). The data layer turns the package into status-labelled CSV files; the model layer reads them, harmonises, characterises, evaluates the six options, applies the gates and the decision rule, and propagates uncertainty. Figure 6 is the metamodel: the data entities and which of them feed results.




Figure 5: Model flow. Every arrow into the model layer is a CSV file.




Figure 6: Metamodel. The upper chain produces results; the lower chain (Level I/II/III) is reporting and calibration content and never changes a result.

4.1 Equations

Symbols as in v2: s_j share of fraction j ; w_j moisture; m_j tonnes of fraction j sent to a unit per tonne MSW; h_j dry-matter LHV; C_j dry carbon; ϕ_j fossil share. Characterisation:

$$M = \sum_j s_j w_j \quad H = \max \left[0, \sum_j k_{h,j} s_j h_j (1 - w_j) - \lambda M \right] \quad E_{fos}(m) = 10^3 \frac{44}{12} \sum_j m_j (1 - w_j) C_j \phi_j \quad (5)$$

with $k_{h,j} = k_h$ for legacy heating values and $k_{h,plastic}$ for plastic (register C10, C10b). Landfill (both baselines and every residue landfill):

$$G_{LF}(m, m_{in}) = CH_4(m, MCF) (1 - \eta)(1 - OX) GWP_{CH_4} + a_{LF} \left(\sum_j m_j + m_{in} \right) \quad (6)$$

Pathways (S5 combines the S2 and S3 units; rejects and digestate go to the residue landfill):

$$G_1 = E_{fos}(s) + n_{N_2O} GWP_{N_2O} + a_W - E_{el} EF_{grid} + G_{LF}(0, \alpha_{ash}), \quad E_{el} = \frac{10^3}{3.6} H \eta_W \quad (7)$$

$$G_2 = E_{fos}(r) + e_R EF_{grid} + a_R + M_{del} def_{truck} - \psi E_{net} EF_{coal} + G_{LF}(s - r), \quad r_j = \tau_j k_{\tau} s_j \quad (8)$$

For AD the methane volume of food separated from mixed waste is $V = 10^3 a (1 - w_{food}) (VS/TS) y_{CH_4} k_{mech}$, where $k_{mech} = 0.6$ (0.35–0.85) is the yield of mechanically separated food relative to source-separated food (Seruga et al. 2020, full scale, about 0.84; Basinas et al. lower), and the cost includes $c_{pre} = 5$ (0–10) USD per tonne of feed for depackaging and grit removal. Both are 1 and 0 in the scenarios *AD_feed_optimistic* and *food_separated_at_source*.

$$G_3 = V \rho_{CH_4} f_{AD} GWP_{CH_4} + a a_A + \pi (e_R EF_{grid} + a_R) - E_{AD} EF_{grid} + G_{LF}(s - a e_{food}, \delta a) \quad (9)$$

$$G_4 = G_{SL} + P (ef_{PHB} - \sigma ef_{PP}), \quad P = \eta CH_4(s, 1)/R \quad G_5 = G_{AD}(a) + G_{RDF}(s - a e_{food}) + G_{LF}(rej, \delta a) \quad (10)$$

Techno-economic assessment and decision:

$$CRF = \frac{r(1+r)^n}{(1+r)^n - 1}, \quad C_u^{cap} = \frac{CRF K_{ref}(q/0.85/q_{ref})^b}{365 q}, \quad CIC_k = C_k + p G_k / 10^3, \quad MAC_k = 10^3 \frac{C_k - C_0}{G_0 - G_k} \quad (11)$$

The gates G_1 to G_6 (WtE LHV ≥ 7 MJ/kg and $Q \geq 150$ t/d, PSEL tariff at $Q \geq 1,000$ t/d, RDF NCV ≥ 12.56 MJ/kg, kiln within 300 km road distance, PHB ≥ 500 t/yr) are read from *model_constants.csv*. Feasible options are screened by Pareto dominance on (G, C). The best option is the feasible option with the lowest **carbon-inclusive cost** CIC_k (USD per tonne MSW). CIC is not a full social cost: it values only greenhouse gases, at a carbon value p that is a *policy choice*. p is therefore not sampled as an uncertain parameter; results are reported at fixed values $p = 0, 2$ (Indonesian carbon tax, Rp 30/kg CO_2e , UU 7/2021), 25, 50 and 100 USD/t CO_2e . For each p the probability of being best is the share of $N = 4,000$ Monte Carlo draws in which an option has the lowest CIC , reported with its Monte Carlo standard error $\sqrt{(P(1-P)/N)} \leq 0.008$. A small lead between two options is not a statistical tie: the standard error is small, and the lead measures how much the choice depends on inputs that are still uncertain (decision uncertainty), which Section 9 decomposes.

5 Uncertainty: priors, sampling noise and scenarios kept apart

Three kinds of uncertainty are distinguished. (1) **Composition**: a Dirichlet distribution around the RIPS proxy, $S \sim \text{Dir}(\alpha_0 s)$, with $\alpha_0 = 80$, or 40 where the data are flagged. These concentrations are *heuristics*, not statistically calibrated: no replicate sorting campaigns exist for these locations to estimate them. The Dirichlet therefore represents prior uncertainty about how well an 8-day sample of a past year represents 2025, not measured sampling variability. (2) **Parameters**: triangular distributions from the register (Section 6), a common wetness draw for moisture, the harmonisation priors γ and yard, the rubber DOCf gap (0 to 0.5) and the realism parameters of AD on mixed waste. (3) **Data scenarios and stress tests**: discrete alternatives that are not given probabilities (Table S4). The carbon value is a policy setting and is fixed, not sampled (Section 4.1).

Missing categories. A category that a RIPS does not report (glass in Kota Padang) has zero share in the main case. This is a modelling assumption, not a measurement of zero. The scenario *glass_imputed* gives such a location a glass share drawn from the 15 locations that report glass (median 1.2%, 10th–90th percentile 0.7–4.5%), and *dirichlet_pseudocount* adds 0.5 to every Dirichlet concentration so that no fraction can be exactly zero in a draw. Neither changes the most probable option at any carbon value (Table S6).

Option	G: composition only	G: parameters only	G: both	C: composition only	C: parameters only	C: both
SL landfill + flare	203	573	622	0	13	13
S1 WtE	212	138	271	12	39	42
S2 RDF	132	359	391	4	15	15
S3 AD	251	443	523	2	17	17
S4 PHB	198	576	630	5	42	42
S5 RDF + AD	108	242	281	5	17	18

Table S3: Median width of the 90% interval over 21 locations when only one source of uncertainty is sampled (G in kg CO_2e/t , C in USD/t; 2,000 draws, market case).

Parameter uncertainty dominates cost; composition contributes a large share of the spread in GHG for WtE (through the plastic share) but less than the parameters for the landfill-based options, where gas collection efficiency dominates.

Scenario	What changes	Status
market	Main case: market prices, no support, residues to sanitary landfill, GWP100, as-received moisture	main
perpres109	WtE electricity at USD 0.20/kWh where $Q \geq 1,000$ t/d	policy
food_separated_at_source	Food arrives separated: no front-end sorting ($\pi = 0$), $k_{\text{mech}} = 1$, $c_{\text{pre}} = 0$	what-if
AD_feed_optimistic	Mixed-waste AD as good as source-separated food ($k_{\text{mech}} = 1$, $c_{\text{pre}} = 0$)	what-if
residues_to_open_dump	Residues dumped instead of landfilled (illegal; sensitivity only)	what-if
managed_M1_status_index	Plant size = status-index share $\times$ Q2025 (19 locations)	data scenario
managed_M2_local_first	Plant size = local indicator where held, else status index (21; mixed definitions)	data scenario
GWP20	20-year horizon for methane	method
moisture_IPCC_default	IPCC moisture (as generated) instead of as-received values	data scenario
tonnage_overview_projected	Overview totals projected from the composition year	data scenario
docf_rubber_0.5	Rubber/leather DOCf at the IPCC 2006 generic default 0.5	data gap
glass_imputed	Glass share imputed where glass is not reported	data gap
dirichlet_pseudocount	Pseudocount 0.5 added to every Dirichlet concentration	method
moisture_high_bound	Moisture as received at the upper end of every fraction range	stress test
rdf_ncv_stress	RDF energy $\times$ 0.78 (NCV about 13–14 MJ/kg, below the 15–16.7 reported at Cilacap)	stress test
phb_large_scale_cost	PHB at an aspirational large-scale cost (1.3 USD/kg, no scale penalty)	what-if

Table S4: Scenarios. Each uses the same random numbers per location, so differences come only from what the scenario changes. With 4,000 draws the Monte Carlo standard error of a probability is at most 0.008.

6 Assumption register

Status: V = confirmed against the source text in the October 2026 verification (Section 6.1); L = literature value with a cited source that was not, or only partly, confirmed; A = analyst assumption. Evidence type follows Table 1. The register is *data/assumption_register.csv*; the table below is generated from it.

ID	Key	Meaning	Central (range)	Unit	Source	St.
H11	g_default	Tonnage growth rate where the RIPS gives none (median of six RIPS rates)	0.0173 (0.0065 to 0.0254)	1/yr	RIPS of six locations	A
H12	gamma	Garden share of lumped 'organik' (median and range of 8 locations reporting both)	0.27 (0.04 to 0.62)	-	input_kota; Edjabou et al. 2017	A
H13	yard	Share of 'kayu' treated as garden where kayu $\geq 10\%$ and no leaf category exists	1 (0.5 to 1)	-	RIPS notes	A
H14	alpha_hi	Dirichlet concentration, unflagged composition (heuristic, not statistically calibrated)	80	-	Analyst heuristic	A
H15	alpha_lo	Dirichlet concentration, flagged composition (heuristic, not statistically calibrated)	40	-	Analyst heuristic	A
C8	F	Methane fraction of landfill gas	0.5 (0.475 to 0.525)	-	IPCC 2006 V5 Ch3	L
C9	doc_k	Multiplier on DOC $\times$ DOCf (default uncertainty $\pm 20\%$)	1 (0.8 to 1.2)	x	IPCC 2006 V5 Ch3 Table 3.5	L
C10	h_k	Calibration factor on legacy dry-matter LHV (not applied to the Gotze plastic value)	0.9 (0.78 to 1.02)	x	Prabowo et al. 2019 (bulk HHV)	L
C10b	h_plastic_k	Uncertainty multiplier on plastic dry LHV (aggregate median, resin mix unknown)	1 (0.9 to 1.1)	x	Analyst range around Gotze et al. 2016 median	A
C11	efg_k	Multiplier on grid emission factor (lower bound = decarbonising grid)	1 (0.7 to 1.1)	x	ESDM factors via JCM 2022	A
C12	docf_rubber	DOCf of rubber/leather: gap scenario (0 = not degradable; 0.5 = IPCC 2006 generic default)	0 (0 to 0.5)	-	IPCC 2006 V5 Ch3 (generic DOCf 0.5); no fraction-specific value	A
B5	mcf_od	Methane correction factor, open dump	0.8 (0.4 to 0.8)	-	IPCC 2006 V5 Ch3 Table 3.1	L
B6	mcf_sl	Methane correction factor, managed anaerobic landfill	1	-	IPCC 2006 V5 Ch3 Table 3.1	L
B7	ox	Oxidation in cover soil, sanitary landfill	0.1 (0 to 0.1)	-	IPCC 2006 V5 Ch3 Table 3.2	L
B8	cap	Lifetime landfill-gas collection efficiency, sanitary landfill	0.5 (0.2 to 0.8)	-	Range bounded by literature: 50–95% in US landfills with effective covers (Barlaz et al. 2009, as cited by US EPA); often below 20–30% in high-food-waste landfills (China, search snippets). Central value is an assumption for a new Indonesian sanitary landfill	A
B9	anc_od	Diesel for dump operation	1 (0 to 3)	kg CO2e/t	Manfredi et al. 2009	L

ID	Key	Meaning	Central (range)	Unit	Source	St.
B10	anc_sl	Diesel and materials for sanitary landfill operation	5 (2 to 10)	kg CO2e/t	Manfredi et al. 2009	L
W4	eta_wte	Net electrical efficiency of grate incinerator on low-LHV waste	0.18 (0.14 to 0.22)	-	Astrup et al. 2015; Rand et al. 2000; Indonesian design study: 26% efficiency and 15% own use, i.e. about 22% net (Yuliani et al. 2022, abstract)	L
W5	n2o_wte	N2O from continuous stoker incineration	0.05 (0.02 to 0.08)	kg N2O/t	IPCC 2006 V5 Ch5 Table 5.6	L
W6	anc_wte	Auxiliary fuel and flue-gas reagents	10 (5 to 30)	kg CO2e/t	Astrup et al. 2009	L
W7	ash	Bottom ash and APC residue sent to landfill	0.25 (0.15 to 0.3)	t/t	Rand et al. 2000	L
R6	tau_k	Multiplier on RDF transfer coefficients	1 (0.85 to 1.1)	x	Nasrullah et al. 2014	L
R7	omega	Target moisture of RDF (off-taker limit 20-25%)	0.2 (0.15 to 0.25)	-	GIZ ERIc-DKTI 2023	L
R8	q_dry	Heat to evaporate water in the dryer (self-supplied by burning RDF)	3.2 (2.6 to 4)	GJ/t water	Engineering range for rotary dryers	L
R9	e_rdf	Electricity for shredding, screening, baling	40 (20 to 70)	kWh/t	Engineering range for MT plants	A
R10	psi	GJ coal displaced per GJ RDF in the kiln	0.9 (0.8 to 1)	-	Silva et al. 2021; Khandelwal et al. 2019	L
R11	ef_coal	Combustion emission factor of displaced coal (sub-bituminous)	96.1 (94.6 to 101)	kg CO2/GJ	IPCC 2006 V2 Ch2 Table 2.3	L
R12	ef_truck	Truck transport of RDF incl. empty return	0.1 (0.06 to 0.15)	kg CO2e/t-km	GLEC Framework	L
R13	tort	Road distance / straight-line distance to nearest kiln	1.3 (1.2 to 1.5)	x	Analyst assumption	A
R14	anc_rdf	Diesel for loaders at the RDF plant	3 (1 to 6)	kg CO2e/t	Analyst assumption	A
A6	kappa	Share of food waste captured into the digester	0.7 (0.5 to 0.9)	-	Mayer et al. 2019	L
A7	vs_ts	Volatile solids / total solids of food waste	0.87 (0.8 to 0.92)	-	Zhang et al. 2007	L
A8	y_ch4	Methane yield of source-separated food waste realised in a digester (BMP-type parameter, not landfill DOCf)	0.36 (0.28 to 0.44)	Nm3 CH4/kg VS	Zhang et al. 2007: 348 mL/g VS after 10 d and 435 mL/g VS after 28 d in batch tests (abstract confirmed)	V
A9	eta_chp	Electrical efficiency of biogas engine	0.36 (0.32 to 0.4)	-	Mayer et al. 2019	L
A10	par_ad	Own electricity use (pulpung, mixing, dewatering)	0.2 (0.1 to 0.3)	-	Mayer et al. 2019	L
A11	fug_ad	Fugitive methane from the biogas plant (share of methane produced)	0.05 (0.01 to 0.1)	-	IPCC 2006 V5 Ch4 (unintentional leakage); Table 4.1 default 0.8 g CH4/kg wet waste (range 0-8) seen in search snippet: the 5% used here (about 2.8 kg/t feed) is conservative for AD	L
A12	anc_ad	Diesel for loaders at the AD plant (per t feed)	3 (1 to 6)	kg CO2e/t	Analyst assumption	A
A13	pre	Front-end separation of food from mixed waste: share of RDF-line cost and electricity	0.4 (0.25 to 0.6)	-	Analyst assumption	A
A14	dig	Dewatered digestate sent to the residue landfill	0.2 (0.1 to 0.35)	t/t feed	Analyst assumption	A
P6	r_phb	Methane per tonne PHB (1.79 as carbon + 0.52 for process energy)	2.3 (2 to 2.8)	t CH4/t PHB	Chidambarampadmavathy et al. 2017	L
P7	ef_phb	Nutrients and extraction chemicals	0.5 (0 to 1.5)	kg CO2e/kg	Rostkowski et al. 2012	L
P8	ef_pp	Cradle-to-gate footprint of displaced polypropylene	1.9 (1.6 to 3.4)	kg CO2e/kg	PlasticsEurope; Chidambarampadmavathy et al. 2017	L
P9	sub_pp	kg PP displaced per kg PHB	1 (0.7 to 1)	kg/kg	Chidambarampadmavathy et al. 2017	L
T7	r	Real discount rate, same for all pathways	0.1 (0.08 to 0.12)	1/yr	Analyst assumption	A
T8	n	Economic lifetime, same for all pathways	20 (15 to 30)	yr	Analyst assumption	A
T9	b	Capacity exponent for CAPEX scaling, same for all units	0.7 (0.6 to 0.85)	-	Tsilemou & Panagiotakopoulos 2006	L
T10	K_wte	WtE CAPEX at reference capacity	120 M (100 M to 200 M)	USD @1000 t/d	Azis et al. 2021: USD 102.2 M for 1,000 t/d; Yuliani et al. 2022: Rp 2.2 bn per t/d, about USD 135 M per 1,000 t/d (abstracts confirmed)	V
T11	o_wte	WtE O&M;	27 (21 to 37)	USD/t	Azis et al. 2021: USD 12.1 M/yr at 1,000 t/d (about 33 USD/t); Yuliani et al. 2022: Rp 167 M/yr per t/d (about 28 USD/t) (abstracts confirmed)	V
T12	K_rdf	RDF plant CAPEX at reference capacity	12.3 M (9 M to 16 M)	USD @300 t/d	GIZ ERIc-DKTI 2023 (report exists; its figure not verified). Cross-check: Cilacap TPST/RDF Rp 81.2 bn for 120 t/d, scaled to 300 t/d with b = 0.7 = about USD 9.5 M (search snippet)	L

ID	Key	Meaning	Central (range)	Unit	Source	St.
T13	o_rdf	RDF plant O&M;	18.4 (12 to 24.5)	USD/t	CORRECTED: Indonesian comparative data give Rp 300,000-400,000 per t processed (COSTING journal, search snippet) = 18.4-24.5 USD/t; low bound = previous central (12 USD/t)	L
T14	K_ad	AD plant CAPEX at reference feed capacity	7 M (4 M to 14 M)	USD @100 t/d	GIZ 2017 in UNDP 2021; Aleluia & Ferrao 2017	L
T15	o_ad	AD plant O&M;	14 (10.6 to 30)	USD/t feed	GIZ 2017 in UNDP 2021	L
T16	c_sl	Full cost of sanitary landfill with gas collection and flare	20 (9 to 30)	USD/t @500 t/d	World Bank 2024 guidelines (figure not verified); Indonesia: controlled landfill about Rp 145,000/t (Kulon Progo 2025) and central-government standard Rp 400,000/t (BPK news, search snippet); Cointreau-Levine 2000: 8-15 USD/t for middle-income countries	L
T17	e_sl	Scale elasticity of landfill cost per tonne	0.3 (0.2 to 0.4)	-	Tsilemou & Panagiotakopoulos 2006	L
T18	c_od	Cost of operating an open dump	4 (2 to 8)	USD/t	Analyst assumption	A
T19	c_phb	PHB production cost excl. methane feedstock	6.8 (4.8 to 9.6)	USD/kg @500 t/a	Listewnik et al. in Chidambarampadmavathy 2017; Levett et al. 2016	A
T20	e_phb	Scale elasticity of PHB unit cost	0.083 (0.05 to 0.15)	-	Levett et al. 2016	A
T21	p_el	Market value of electricity (grid generation cost)	0.07 (0.05 to 0.1)	USD/kWh	Kepmen ESDM 169/2021 (BPP; figure not verified); Zeng et al. 2024: current Indonesian electricity price 0.069 USD/kWh (abstract confirmed)	V
T22	p_rdf	Price of RDF at kiln gate	1.15 (0.58 to 1.34)	USD/GJ	CORRECTED: Rp 150,000-350,000 per t RDF reported for Bantargebang/DKI and Rp 300,000/t elsewhere (news, search snippets), converted at 16 GJ/t (Cilacap RDF about 16.7 MJ/kg) and IDR 16,300/USD	L
T23	p_phb	Selling price of PHB	4 (2.5 to 6)	USD/kg	Market reports; Levett et al. 2016	L
T24	c_truck	Cost of trucking RDF	0.1 (0.05 to 0.15)	USD/t-km	Analyst assumption	A

Table 3: Assumption register (61 entries; CED/LU factors in Table 8, realism and scenario parameters in data/scenario_parameters.csv). New or changed in v3: H14-H15 (heuristic Dirichlet concentrations made explicit), C10b (plastic LHV range), C12 (rubber DOCf gap scenario). Changed in v3.2: see Table 3a.

6.1 Verification of secondary data (October 2026)

Every secondary value that drives a result or a benchmark was re-checked against its source. Full texts could not be downloaded in the working environment, so the check used publisher abstracts, indexed records and search-engine extracts of the sources; the method of each check is recorded in *data/secondary_data_verification.csv*. A value was *confirmed* when the number appeared in the source record, *corrected* when the source gave a different number, and *not verified* when it could not be found; unverified benchmark values were removed rather than kept. The previous value is kept in the file for audit.

Item	Value used (v3.2)	Previous value	Result	Evidence
WtE capital cost	USD 120 M (100-200) per 1,000 t/d	same	confirmed	USD 102.2 M for 1,000 t/d; Yuliani et al. 2022: Rp 2.2 bn per t/d
WtE O&M;	27 (21-37) USD/t	same	confirmed	USD 12.1 M/yr at 1,000 t/d; Yuliani: Rp 167 M/yr per t/d
WtE net efficiency	0.18 (0.14-0.22)	same	consistent	Indonesian design: 26% efficiency, 15% own use (about 22% net), Yuliani et al. 2022
WtE net electricity benchmark	-	632 kWh/t from 750 t/day at 35% (Azis 2021)	corrected	Abstract: about 19.7 MW from 1,000 t/day, i.e. about 473 kWh/t; Yuliani 2022: 24.08 MW net from 1,500 t/day, i.e. about 385 kWh/t net
MSW calorific value as received	-	HHV 6.9-9.0 MJ/kg (Prabowo 2019)	partly confirmed	6,860 and 8,970 kJ/kg as received (abstract does not say HHV or LHV); Yuliani 2022: 6,276 kJ/kg
MSW moisture at transfer points	-	0.53-0.56 (Prabowo 2019)	not verified	Moisture not in the abstract; replaced by Cilacap raw MSW 55.44% moisture before biodrying (Presipitasi/UPN Jatim, search snippet)

Item	Value used (v3.2)	Previous value	Result	Evidence
Landfill waste moisture	-	0.64-0.66 (Fiki et al. 2022)	not verified	Paper confirmed (Jatibarang, biodrying to 44.65% moisture in 21 days); the initial moisture is not in the snippet
RDF heating value	-	12.6-13.8 MJ/kg (GIZ 2023)	corrected	Cilacap RDF: 3,991 kcal/kg (16.7 MJ/kg), 24.2% moisture, 17.3% ash; about 15 MJ/kg after biodrying (search snippets)
RDF O&M;	18.4 (12-24.5) USD/t	12 (8-21)	corrected	Rp 300,000-400,000 per t processed (COSTING journal, search snippet)
RDF price at kiln	1.15 (0.58-1.34) USD/GJ	1.6 (1.0-2.6)	corrected	Rp 150,000-350,000/t (DKI Bantargebang), Rp 300,000/t (news snippets)
RDF plant capital cost	USD 12.3 M (9-16) per 300 t/d	same	partly confirmed	GIZ report exists; Cilacap Rp 81.2 bn for 120 t/d (scaled: about USD 9.5 M per 300 t/d)
Sanitary landfill cost	20 (9-30) USD/t	20 (12-30)	partly confirmed	Rp 145,000/t controlled landfill, Rp 400,000/t standard (BPK news); Cointreau-Levine 2000: 8-15 USD/t middle-income
Landfill gas collection	0.50 (0.20-0.80)	0.50 (0.30-0.80)	bounded by literature	50-95% in US landfills with effective covers; often below 20-30% in high-food-waste landfills; Wei et al. 2024 not found
Grid factor Jamali	0.877	0.87	confirmed	ESDM 2018, JCM Case 1 (grid only): 0.877 t CO ₂ /MWh
Grid factor Sumatera	0.832	0.94	corrected	ESDM 2018, JCM Case 1: 0.832 t CO ₂ /MWh
Grid factor Mahakam	1.128	1.14	confirmed (rounded before)	ESDM 2018, JCM Case 1: 1.128 t CO ₂ /MWh
Electricity price	0.07 (0.05-0.10) USD/kWh	same	confirmed	Zeng et al. 2024: 0.069 USD/kWh
Food-waste methane yield	0.36 (0.28-0.44) Nm ³ /kg VS	same	confirmed	348 (10 d) and 435 (28 d) mL/g VS
Fugitive methane AD	5% (1-10%) of CH ₄ produced	same	partly confirmed	Table 4.1: 0.8 g CH ₄ /kg wet waste (0-8); model value conservative
Mechanically separated food: methane yield	0.60 (0.35-0.85) x source-separated	1 (not modelled)	literature range	Seruga 2020 (full scale, ratio about 0.84); Basinas 2020, 2021 (0.11-0.18 vs 0.30-0.40 m ³ /kg VS); Ebner 2021
PHB production cost	6.8 USD/kg at 500 t/a, falling with scale	same	partly confirmed	Abstract: cost could fall to AUD 1.5-2.0/kg with centralised large-scale extraction (aspirational); see scenario phb_large_scale_cost
WtE at small scale in Indonesia	-	-	observation	Bantargebang pilot (100 t/d design, 70.6 t/d average, 2022): 956 MWh generated vs 1,369 MWh own demand (Febijanto et al. 2024); consistent with the 150 t/d scale gate
RIPS composition and tonnage	21 RIPS extracts	-	not re-verified	Source PDFs not available in this session; row-level locators kept in the input file

Table 3a: Secondary-data verification. Status V in the register is kept only for the four values confirmed in the source record (food-waste methane yield, WtE CAPEX and O&M, electricity price); other values formerly marked V are now L. The 21 RIPS compositions and tonnages were not re-verified because the source PDFs were not available; their row-level page locators are kept in the input file.

7 Verification and validation

Because the facilities do not exist, the model cannot be validated against their measured performance. Four layers are therefore kept apart, following the usual distinction between verification (is the model computed as specified?) and validation (does it represent the system well enough for its purpose?).

(a) Verification of the code and data. `validate_v3.py` ran 78 checks; 78 passed. They include an explicit hand recalculation of every result for Kota Padang (the worked example), which must reproduce the model to 10⁻⁶.

Group	Checks	Examples of what is tested
blank vs zero	6/6	blank DOCf stays blank; parser treats blank and reported-zero glass without imputation; old file rejected
taxonomy	7/7	(level, code) unique in 3 tables; 10/36/56 counts; every parent exists; 6.* documented
mass balance	6/6	M_dom + M_nd = Q2025; Level I = 100%; Level II = parent; terminal partition = 100% (78 leaves)
parent-child	5/5	Level III = Level II parent; detail file partial (76.8-93.7%); conditional shares only for complete sets
projection	6/6	Q2025 = Qt(1+g)^expo once; exponent 0 when already 2025; overview year blank and flagged
Qmanaged	5/5	M1, M2 <= Q2025; Serang 7.45% not 14%; Padang provisional with lower bound
wet/dry	7/7	DOC_dry(1-w) = IPCC wet DOC; LHV dry basis, LHV not HHV; DOCf separate from AD yield; soil/wood separated
provenance	7/7	every row has source, locator and status; proxies keep proxy status; heuristics labelled
CED/LU	7/7	factors have source and status; land take non-negative; landfill area = 1/(rho H) x gross; G and C unchanged
template	4/4	user-template round trip reproduces results; invalid input rejected; blank glass not zero; single projection
v3.2 data	7/7	corrected values in use; ESDM 2018 grid factors; status V only where confirmed; every item has evidence

Group	Checks	Examples of what is tested
v3.2 model	5/5	AD penalty changes only S3/S5; glass imputation only where not reported; RDF NCV stress applied
v3.2 decision	5/5	P(best) sums to 1; standard errors bounded; EVPI ≤ EVPI; break-even closes the gap; Padang hand calculation
v3.2 wording	1/1	no 'statistical tie' or 'social cost' as decision metric in code and tool

Table S5: Verification checks by group (full list in *outputs/validation_report.md*). The model also asserts the single projection for every location, the S5 mass balance and that biogas carbon is below food carbon.

(b) Benchmark validation. Intermediate outputs that do not depend on a facility existing (moisture, heating value, RDF yield and quality, WtE electricity per tonne) were compared with independent Indonesian values from the verified sources. The verdict is computed, not judged (Table 4).

Quantity	Model, 21 locations	Reference (verified source)	Verdict
bulk moisture (-)	0.39 to 0.60 (median 0.51)	0.554, raw MSW at Cilacap before biodrying (single site); the 0.53-0.56 and 0.64-0.66 values cited in v3.1 could not be confirmed and were removed	median within reference
LHV as received (MJ/kg)	5.0 to 9.5 (median 7.2)	6.28 (Yuliani et al. 2022, design basis) and 6.86-8.97 as received (Prabowo et al. 2019, HHV/LHV basis not stated in the abstract)	median within reference
HHV of dry matter (MJ/kg)	15.3 to 20.3 (median 18.1)	not compared: no reference with a stated dry basis	no reference (reported for transparency)
L0 at MCF = 1 (kg CH ₄ /t)	34 to 65 (median 45)	no Indonesian measurement	no reference (reported for transparency)
RDF yield (t/t MSW)	0.17 to 0.38 (median 0.27)	0.20-0.42, Indonesian RDF plants (GIZ 2023; not re-verified in v3.2)	median within reference
RDF heating value (MJ/kg)	15.0 to 19.8 (median 17.5)	15-16.7, Cilacap RDF (3,991 kcal/kg at 24% moisture; about 15 after biodrying)	range overlaps reference
WtE net electricity (kWh/t)	248 to 474 (median 360)	385 net (Yuliani et al. 2022: 24.08 MW from 1,500 t/d) to 473 (Azis et al. 2021: 19.7 MW from 1,000 t/d); v3.1 quoted 632 kWh/t, which is not in the source	range overlaps reference
carbon in biogas / carbon in food	0.74	must be below 1 (mass balance)	median within reference

Table 4: Benchmark validation (main case). The RDF heating value lies at the upper end of, and partly above, the Cilacap range; WtE electricity overlaps the Indonesian design values at their lower end. Both are tested further in the stress tests.

(c) Stress tests. Assumptions without a local measurement were pushed to the ends of their plausible range and the number of locations whose most probable option changes was counted at each carbon value (Table S6).

Stress test or scenario	0 USD/t	2 USD/t	25 USD/t	50 USD/t	100 USD/t
AD feed optimistic	0	0	0	0	2
Pseudocount 0.5	0	0	0	0	2
Glass imputed	0	0	0	0	0
IPCC moisture	0	0	0	7	7
Moisture high	0	0	0	0	17
PHB large-scale (what-if)	20	20	20	20	20
RDF NCV -22%	0	0	0	0	17

Table S6: Number of the 21 locations whose most probable option changes relative to the market case. The PHB row is an aspirational what-if, not a stress test.

No stress test changes the decision up to 25 USD/t. At 100 USD/t the RDF + AD lead is fragile: the high moisture bound and a 22% lower RDF heating value each return 17 and 17 locations to the landfill. The drier IPCC moisture moves 7 locations away from the landfill at 50 USD/t. Glass imputation and the pseudocount change at most two locations, at 100 USD/t only.

(d) Field validation, ex ante. When a city moves towards a facility, the model should be checked against (i) a local waste characterisation with proximate analysis (moisture, ash, heating value as received) and (ii) performance data from analogous Indonesian facilities: the Cilacap and Jeranjang RDF plants for RDF yield and quality, the Bantargebang and Putri Cempo pilots for WtE output, and landfill-gas collection measured at a sanitary landfill. Section 9 ranks these measurements by their value of information, so that the field work is ordered by how much it can change the decision.

8 Results for the 21 locations (2025 baseline)

LHV as received is 5.0 to 9.5 MJ/kg (median 7.2). At central values 12 locations pass the WtE heating-value gate G1 and 11 pass G1 and the scale gate G2. 6 locations reach 1,000 t/day on generated waste; on managed waste none does in series M1 and 1 does in series M2 (Kab. Bogor, whose local indicator gives 1,016 t/d).

Option	G	ΔG vs open dump	ΔG vs landfill	C	MAC vs OD	MAC vs SL	Pass
SL landfill + flare	557 (424 to 793)	425 (322 to 609)	-	18 (12 to 40)	34 (21 to 81)	-	21
S1 WtE	130 (-29 to 238)	880 (549 to 1406)	441 (209 to 798)	58 (42 to 120)	62 (36 to 131)	98 (47 to 181)	11
S2 RDF	319 (136 to 421)	661 (454 to 998)	251 (109 to 389)	42 (31 to 70)	56 (39 to 87)	98 (58 to 194)	20
S3 AD	389 (192 to 696)	582 (451 to 758)	161 (96 to 232)	37 (28 to 66)	55 (40 to 107)	112 (74 to 201)	21
S4 PHB	543 (414 to 773)	439 (332 to 628)	14 (10 to 20)	38 (23 to 75)	78 (54 to 154)	1449 (993 to 2412)	20
S5 RDF + AD	153 (23 to 304)	810 (639 to 1098)	408 (294 to 509)	47 (37 to 78)	50 (39 to 84)	73 (53 to 99)	20

Table 6: Pathway results per tonne of MSW, central values, market case: median (minimum to maximum) over the 21 locations, including those failing a gate (last column: number that pass). G, ΔG in kg CO₂e/t; C in USD/t; MAC in USD/t CO₂e.

Location	Flags	Central best: 0 / 25 / 50 / 100	P(SL) at 50	P(S5) at 50	P(SL) at 100	P(S5) at 100	P(S1) at 100	Most probable at 100
Kota Padang	N	SL / SL / SL / S5	0.80 ± 0.01	0.10 ± 0.01	0.21 ± 0.01	0.65 ± 0.01	0.11 ± 0.01	S5 (0.65)
Kab. Bogor	G	SL / SL / SL / S5	0.75 ± 0.01	0.05 ± 0.01	0.21 ± 0.01	0.50 ± 0.02	0.04 ± 0.01	S5 (0.50)
Kab. Serang	G	SL / SL / SL / S5	0.85 ± 0.01	0.02 ± 0.00	0.37 ± 0.01	0.32 ± 0.01	0.11 ± 0.01	SL (0.37)
Kota Denpasar	G	SL / SL / SL / S5	0.57 ± 0.02	0.07 ± 0.01	0.07 ± 0.01	0.47 ± 0.02	0.41 ± 0.02	S5 (0.47)
Kab. Cianjur	LG	SL / SL / SL / S5	0.76 ± 0.01	0.09 ± 0.01	0.20 ± 0.01	0.59 ± 0.02	0.12 ± 0.01	S5 (0.59)
Kab. Indramayu	LG	SL / SL / SL / S5	0.78 ± 0.01	0.09 ± 0.01	0.21 ± 0.01	0.62 ± 0.02	0.09 ± 0.01	S5 (0.62)
Kota Semarang	LT	SL / SL / SL / S5	0.75 ± 0.01	0.06 ± 0.01	0.20 ± 0.01	0.54 ± 0.02	0.19 ± 0.01	S5 (0.54)
Kab. Brebes	T	SL / SL / SL / S5	0.82 ± 0.01	0.08 ± 0.01	0.29 ± 0.01	0.60 ± 0.02	0.07 ± 0.01	S5 (0.60)
Kab. Nganjuk	T	SL / SL / SL / S5	0.80 ± 0.01	0.06 ± 0.01	0.20 ± 0.01	0.60 ± 0.02	0.17 ± 0.01	S5 (0.60)
Kab. Pati	R	SL / SL / SL / S5	0.56 ± 0.02	0.23 ± 0.01	0.08 ± 0.01	0.83 ± 0.01	0.04 ± 0.01	S5 (0.83)
Kab. Magelang	T	SL / SL / SL / S5	0.80 ± 0.01	0.07 ± 0.01	0.19 ± 0.01	0.62 ± 0.02	0.15 ± 0.01	S5 (0.62)
Kab. Pandeglang		SL / SL / SL / S5	0.92 ± 0.01	0.02 ± 0.00	0.36 ± 0.01	0.41 ± 0.02	0.03 ± 0.01	S5 (0.41)
Kab. Pemasang		SL / SL / SL / S5	0.91 ± 0.01	0.05 ± 0.01	0.31 ± 0.01	0.62 ± 0.02	0.03 ± 0.01	S5 (0.62)
Kab. Temanggung		SL / SL / SL / S5	0.94 ± 0.01	0.02 ± 0.00	0.48 ± 0.02	0.41 ± 0.02	0.07 ± 0.01	SL (0.48)
Kab. Pekalongan	L	SL / SL / SL / S5	0.66 ± 0.01	0.15 ± 0.01	0.12 ± 0.01	0.66 ± 0.01	0.18 ± 0.01	S5 (0.66)
Kab. Sragen	LT	SL / SL / SL / S5	0.81 ± 0.01	0.09 ± 0.01	0.20 ± 0.01	0.62 ± 0.02	0.12 ± 0.01	S5 (0.62)
Kab. Kutai Kartanegara	WT	SL / SL / SL / S1	0.82 ± 0.01	0.00 ± 0.00	0.45 ± 0.02	0.00 ± 0.00	0.48 ± 0.02	S1 (0.48)
Kab. Kendal	WT	SL / SL / SL / S5	0.86 ± 0.01	0.07 ± 0.01	0.20 ± 0.01	0.67 ± 0.01	0.06 ± 0.01	S5 (0.67)
Kab. Wonogiri	WRT	SL / SL / SL / S5	0.80 ± 0.01	0.11 ± 0.01	0.15 ± 0.01	0.70 ± 0.01	0.10 ± 0.01	S5 (0.70)
Kota Pekalongan	L	SL / SL / SL / S5	0.87 ± 0.01	0.07 ± 0.01	0.27 ± 0.01	0.59 ± 0.02	0.09 ± 0.01	S5 (0.59)
Kota Magelang	W	SL / SL / SL / S5	0.92 ± 0.01	0.05 ± 0.01	0.37 ± 0.01	0.50 ± 0.02	0.00 ± 0.00	S5 (0.50)

Table 7: Decision results per location, market case. Central best: lowest carbon-inclusive cost at central values for carbon values of 0, 25, 50 and 100 USD/t CO₂e. P(k) at p: probability that option k has the lowest carbon-inclusive cost at the fixed carbon value p, ± the 95% Monte Carlo interval (4,000 draws). At 0, 2 and 25 USD/t the landfill is most probable everywhere (outputs/15_p_best_fixed_carbon_value.csv). Flags: L lumped organics, W kayu as garden, R rounded percentages, G glass in lain-lain, N glass not reported, T tonnage year unverified.




Figure 7: Probability of being the best feasible option at fixed carbon values (top) and in three scenarios at 50 USD/t (bottom).




Figure 8: Most probable option per location in each scenario at 100 USD/t CO2e (colour) and its probability (number).

What the numbers say.

- **Landfill first.** Sanitary landfill with flare has the lowest carbon-inclusive cost at central values in all 21 locations at 0, 25 and 50 USD/t, and is the most probable option everywhere up to 50 USD/t (median $P = 0.80$ at 50 USD/t). At the current carbon tax (about 2 USD/t) no recovery option is preferred.
- **RDF + AD at a high carbon value.** At 100 USD/t RDF + AD is best at central values in 20 locations and most probable in 18 (median $P = 0.60$, range 0.00 to 0.83). Its abatement cost against the landfill is 73 (53 to 99) USD/t CO₂e, so it becomes preferable only above that carbon value.
- **WtE** needs a heating value of at least 7 MJ/kg, 1,000 t/day and the Perpres 109/2025 tariff together; with the tariff it is most probable at 50 USD/t in 3 locations. Without the tariff it wins only where the grid is coal-heavy and the waste dry (Kab. Kutai Kartanegara at 100 USD/t).
- **AD alone** becomes most probable in 20 locations at 50 USD/t if food arrives separated at source. For mixed waste it never does, even when the mixed-waste penalty is removed (*AD_feed_optimistic*: landfill most probable in 21 locations at 50 USD/t). Source separation, not digester technology, is the condition for AD.
- **PHB** is not preferred at the cost assumed for a first plant. Only the aspirational large-scale cost (1.3 USD/kg) would make it most probable in 20 locations; that is a research target, not a planning value.
- **Managed tonnage.** On the status-index series (M1) the landfill is most probable at 50 USD/t in 19 of 19 locations, on the local-first series (M2) in 21 of 21.
- **Climate metric.** With GWP20 the landfill loses its lead at 50 USD/t everywhere (RDF + AD 15, WtE 6): the choice of time horizon is as consequential as the carbon value.




Figure 9: GHG avoided against extra cost, Monte Carlo medians, one dot per location and option.




Figure 10: Inputs that drive the results: mean absolute Spearman rank correlation over the locations.

For climate the landfill-gas collection efficiency dominates every option that landfills residues, followed by the plastic share (fossil CO₂ from WtE), the garden share and moisture. For cost: landfill cost, WtE and AD CAPEX, RDF O&M, the AD front-end share and PHB cost and price. These are the values to verify first.

9 Break-even targets and the value of information

Facilities do not yet exist, so their performance is uncertain. Two analyses turn that uncertainty into guidance for stakeholders. **Break-even targets:** with all other inputs central, one input is swept and the value at which an option's carbon-inclusive cost equals the landfill's is found (*mswpath.thresholds*). These are targets a tender, a pilot or an offtake contract must reach. **Value of information:** for a fixed carbon value the net benefit of option k in draw i is $NB_{ik} = -CIC_{ik}$. The expected value of perfect information,

$$EVPI = E_i \left[\max_k NB_{ik} \right] - \max_k E_i[NB_{ik}], \quad EVPPI(X) = E_X \left[\max_k E(NB_k | X) \right] - \max_k E[NB_k] \quad (12)$$

is the most a city should pay, per tonne, to remove all uncertainty before choosing; EVPPI is the same for one group of inputs X that one measurement campaign would resolve. $E(NB_k | X)$ is estimated by regression on X (Strong et al. 2014; quadratic, additive in the inputs of a group), and the EVPPI of random noise is subtracted as a bias floor. Multiplied by the 2025 tonnage, the values are in USD per year.

Input (S5 RDF + AD vs SL, 100 USD/t)	Central	Better if	Break-even: median (range)	n crossing	never	already
y_pen_mech	0.6	higher	0.436 (0.346 to 0.526)	2	0	19
pre_ofmsw	5	lower	20.1 (6.94 to 29.5)	6	0	15
p_rdf	1.15	higher	0.137 (0.0211 to 1.05)	5	0	16
o_rdf	18.4	lower	28.8 (18.8 to 38.6)	21	0	0
cap	0.5	lower	0.656 (0.508 to 0.818)	21	0	0
Input (S5 RDF + AD vs SL, 50 USD/t)	Central	Better if	Break-even: median (range)	n crossing	never	already
y_pen_mech	0.6	higher	0.916 (0.916 to 0.916)	1	20	0
pre_ofmsw	5	lower	-	0	21	0
p_rdf	1.15	higher	3.42 (1.35 to 5.22)	21	0	0
o_rdf	18.4	lower	9.46 (2.19 to 17)	21	0	0
cap	0.5	lower	0.248 (0.16 to 0.457)	17	4	0

Table 7a: Break-even values for RDF + AD against the landfill over the 21 locations (units as in the register: k_{mech} –; c_{pre} and RDF O&M USD/t; RDF price USD/GJ; collection efficiency –). 'never': no value in the tested range closes the gap; 'already': RDF + AD is cheaper over the whole range; 'n crossing': locations where a break-even exists. Other options in outputs/17_break_even_thresholds_vs_SL.csv.

At 50 USD/t RDF + AD matches the landfill only if RDF O&M falls well below the verified 18.4 USD/t, the RDF price rises several-fold above today's 1.15 USD/GJ, or landfill-gas collection is poor (below about 0.25). At 100 USD/t it is already cheaper in most locations and stays so unless RDF O&M exceeds about 29 USD/t or collection exceeds about 0.66. For a city these are concrete conditions to write into a tender: a maximum gate fee for RDF processing, a minimum kiln price, and a measured collection efficiency for the landfill alternative.

Measurement group	25 USD/t	50 USD/t	100 USD/t	Max over locations at 100, USD/yr
Waste characterisation (moisture, composition)	0.000	0.057	0.773	1,302,097
Landfill gas performance (collection, DOC, F, oxidation)	0.000	0.012	0.654	1,182,715
WtE performance and cost	0.000	0.000	0.036	712,320
RDF line and off-take (O&M, CAPEX, price, coal substitution, sorting)	0.000	0.000	0.003	417,964
AD on mixed waste (yield, penalty, capture, costs, pre-treatment)	0.000	0.000	0.002	440,030
Finance (discount rate, lifetime, scale exponent)	0.000	0.000	0.000	110,849
Grid and electricity price	0.000	0.000	0.000	50,471
Landfill cost	0.000	0.000	0.000	92,063
EVPI (all inputs), median USD/t	0.24	1.05	3.18	3,357,725

Table 7b: Value of information, median EVPPI over 21 locations in USD per tonne MSW (market case, 4,000 draws). The last column multiplies by the location's 2025 tonnage.




Figure 10a: Value of information by measurement group at three carbon values: median over 21 locations (bar) and maximum (dot).

Uncertainty is worth little at 25 USD/t (EVPI 0.24 USD/t), because the landfill wins almost regardless. At 100 USD/t the EVPI rises to 3.18 USD/t, about 686,273 USD per year for the median location, and waste characterisation (as-received moisture and composition) and landfill-gas performance carry most of it, followed by WtE performance and cost. Group values are conservative (additive regression within a group, noise floor subtracted), so they need not add up to the EVPI. The rule for a city is direct: if a local waste-characterisation campaign with proximate analysis, or a landfill-gas pumping test, costs less than its EVPI for one year, it should be done before any technology commitment. AD-specific data matter only where food can be separated at source.

10 Fossil energy (CED) and land take (v3.1)

Two indicators are added to climate change and cost. Both reuse the inventory of the existing model, so they add no new flows, only conversion factors (*data/lcia_factors.csv*, drawn after all v3 parameters so that G and C are unchanged; validation check). **CED** is the non-renewable (fossil) cumulative energy demand in MJ per tonne MSW; biogenic energy is not counted and a negative value is a net saving:

$$CED_k = \sum kWh_{in} PEF + \sum_{el} \frac{a_i}{\rho_{SL} H_{SL}} (1 + u_d) - E_{el} PEF - \psi E_{net} (1 + u_c) - P \sigma CED_{pp}, \quad PEF = \frac{3.6}{\eta_{fossil}} (1 + u_f) k_{EF} \quad (12)$$

PEF is the primary fossil energy per kWh of grid electricity, scaled with the same multiplier k_{EF} as the grid emission factor so that a decarbonising grid lowers both. Diesel-type ancillary burdens a_i (kg CO₂e) are converted with the IPCC diesel factor. **Land take** is the landfill area consumed permanently plus plant footprints over their lifetime, in m² per tonne MSW:

$$LU_k = \left(\frac{m_{LF}}{\rho_{SL} H_{SL}} + \frac{m_{inert}}{\rho_{inert} H_{SL}} \right) f_{gross} + \sum_u \frac{fp_u m_u}{0.85 \cdot 365 n}, \quad LU_{OD} = \frac{m}{\rho_{OD} H_{OD}} \quad (13)$$

Key	Meaning	Central (range)	Unit	Source	St.
pef_eta	Net thermal efficiency of the fossil generation displaced or consumed (primary energy = 3.6 / eta MJ per kWh)	0.32 (0.28 to 0.36)	-	PT PLN Indonesia Power fleet thermal efficiency 32.09% in 2022 (annual report, seen as a search-result quotation only); Indramayu CFPP net heat rate about 2,460 kcal/kWh (= 35%) at full load	L
up_fuel	Upstream supply energy of power-plant fuel (mining, processing, transport) as a share of fuel energy	0.08 (0.03 to 0.15)	-	Analyst assumption	A
ef_diesel	Converts diesel-type ancillary burdens (kg CO ₂ e) to diesel energy; the ancillary terms also contain materials, so this is an approximation	0.0741	kg CO ₂ /MJ	IPCC 2006 Vol. 2 Ch. 1 Table 1.4 (gas/diesel oil 74,100 kg CO ₂ /TJ)	L
up_diesel	Upstream (refinery, crude supply) energy of diesel as a share of its energy	0.15 (0.1 to 0.25)	-	Analyst assumption	A
up_coal	Upstream (mining, transport) energy of the kiln coal displaced by RDF	0.05 (0.02 to 0.1)	-	Analyst assumption	A
ef_natgas	Converts the PHB nutrient/chemical burden (kg CO ₂ e) to fossil MJ as if natural-gas based (proxy)	0.0561	kg CO ₂ /MJ	IPCC 2006 Vol. 2 Ch. 1 Table 1.4 (natural gas 56,100 kg CO ₂ /TJ); use as proxy is an assumption	A
ced_pp	Cradle-to-gate fossil CED of displaced polypropylene incl. feedstock energy	75 (65 to 85)	MJ/kg	Order of magnitude of PlasticsEurope PP eco-profile; value not verified in this session	L
rho_sl	In-place density of compacted MSW in a sanitary landfill	0.8 (0.6 to 1)	t/m ³	Engineering range (analyst)	A
h_sl	Effective fill height of a sanitary landfill	20 (10 to 30)	m	Engineering range (analyst)	A
f_gross_sl	Gross site area / fill area (roads, leachate ponds, buffer)	1.3 (1.1 to 1.5)	-	Engineering range (analyst)	A

Key	Meaning	Central (range)	Unit	Source	St.
rho_inert	In-place density of ash, digestate cake and other inert residues	1.3 (1 to 1.6)	t/m ³	Engineering range (analyst)	A
rho_od	Density of uncompacted waste in an open dump	0.5 (0.35 to 0.7)	t/m ³	Engineering range (analyst)	A
h_od	Average heap height of an open dump	5 (3 to 10)	m	Engineering range (analyst)	A
fp_wte	Site footprint of a WtE plant per t/d nameplate capacity	40 (20 to 80)	m ² per t/d	Analyst assumption	A
fp_rdf	Site footprint of an RDF plant (incl. drying and storage) per t/d	50 (25 to 100)	m ² per t/d	Analyst assumption	A
fp_ad	Site footprint of an AD plant (incl. digestate handling) per t/d feed	60 (30 to 120)	m ² per t/d	Analyst assumption	A

Table 8: CED and land-use factors. Most land-use factors are analyst engineering ranges; the thermal efficiency and the polypropylene CED are literature values still to be verified against their originals (status L). An Indonesian TPA design study (Talumelito, Gorontalo) implies about 0.045 m²/t, below the central 0.081 m²/t used here.

Option	CED, GJ/t: median (range)	Saving vs open dump, GJ/t	Land take, m ² /t: median (range)	Saved vs open dump, m ² /t
SL landfill + flare	0.08 (0.08 to 0.08)	-0.06	0.081 (0.081 to 0.081)	0.319
S1 WtE	-4.20 (-5.58 to -2.84)	4.21	0.019 (0.019 to 0.019)	0.381
S2 RDF	-3.80 (-5.77 to -1.81)	3.82	0.061 (0.053 to 0.066)	0.339
S3 AD	-0.17 (-0.35 to 0.00)	0.18	0.067 (0.059 to 0.073)	0.333
S4 PHB	-0.57 (-0.85 to -0.42)	0.59	0.081 (0.081 to 0.081)	0.319
S5 RDF + AD	-4.18 (-6.07 to -2.37)	4.20	0.045 (0.042 to 0.051)	0.355

Table 9: Fossil CED and land take per tonne MSW, central values, market case, 21 locations.

WtE, RDF and RDF + AD save 4.2, 3.8 and 4.2 GJ of fossil energy per tonne (displaced grid electricity and kiln coal), AD alone 0.2 GJ and PHB 0.6 GJ (displaced polypropylene); the sanitary landfill consumes 78 MJ for operation. Land take is dominated by landfilling: an open dump uses about 0.40 m²/t, a sanitary landfill 0.081, RDF + AD 0.045 and WtE 0.019 m²/t, mostly for ash. The energy ranking follows the climate ranking; land take adds a reason to divert waste from landfill where land is scarce, such as Java.




Figure 11: Fossil CED and land take of each option, Monte Carlo medians over the 21 locations.

11 Conditions under which each option becomes preferable: scenario discovery

The research question asks for conditions, not for a ranking of 21 cases. The model was therefore run over 40,000 combinations of conditions that a planner can observe or choose: carbon value (0 to 100 USD/t CO₂e), waste to the facility (50 to 3,000 t/day, log-uniform), road distance to a cement kiln (10 to 400 km), grid region, availability of the Perpres 109/2025 tariff, source separation of food, composition, moisture, landfill-gas collection and landfill cost; all other parameters were sampled from the register. Composition was drawn from a Dirichlet distribution centred on the mean of the 21 RIPS compositions with concentration 46 fitted to their between-city spread (method of moments), so the rules describe compositions like those observed and are extrapolations outside them. For each draw the best feasible option (lowest carbon-inclusive cost) was recorded. A classification tree of depth 4 reproduces that choice in 78% of held-out draws (majority-class baseline 51%); PRIM (Friedman and Fisher 1999) searched for boxes of conditions in which one option is best with high density.

Rule (conditions)	Best option	Purity	Share of draws
food separated = no and Q tpd ≤ 999 and carbon value ≤ 59.3	SL landfill + flare	0.97	22%
food separated = yes and carbon value > 44.4 and Q tpd ≤ 1e+03	S3 AD	0.83	20%
food separated = no and Q tpd ≤ 999 and carbon value > 73.6 and kiln km ≤ 300	SL landfill + flare	0.53	7%

Rule (conditions)	Best option	Purity	Share of draws
food separated = yes and carbon value ≤ 16.9 and Q tpd ≤ 971	SL landfill + flare	0.88	6%
food separated = yes and $28.4 < \text{carbon value} \leq 44.4$ and Q tpd $\leq 1\text{e}+03$	S3 AD	0.61	6%
food separated = yes and carbon value > 28.4 and Q tpd $> 1\text{e}+03$ and LHV > 7	S1 WtE	0.56	6%
food separated = no and Q tpd ≤ 999 and $59.3 < \text{carbon value} \leq 73.6$	SL landfill + flare	0.81	5%
food separated = yes and carbon value > 28.4 and Q tpd $> 1\text{e}+03$ and LHV ≤ 7	S3 AD	0.87	4%
food separated = no and Q tpd > 999 and LHV ≤ 7 and carbon value ≤ 66.9	SL landfill + flare	0.87	4%
food separated = no and Q tpd > 999 and LHV > 7 and tariff = no	SL landfill + flare	0.59	4%
food separated = no and Q tpd > 999 and LHV > 7 and tariff = yes	S1 WtE	0.98	4%
food separated = yes and $16.9 < \text{carbon value} \leq 28.4$ and Q tpd ≤ 639	SL landfill + flare	0.65	4%

Table 10: Leaves of the decision tree covering at least 3% of draws (outputs/discovery_cart_rules.csv). Purity: share of the draws in the leaf where the predicted option is indeed best. Q tpd: t/day to the facility; kiln km: road distance.

Option	Base rate	Coverage	Density	Box (conditions)
SL landfill + flare	0.513	0.30	0.90	carbon_value: 0.00119 to 70.1; tariff = 0; food_separated = 0
S1 WtE	0.100	0.32	0.99	Q_tpd: 1.02e+03 to 3e+03; tariff = 1; food_separated = 0; LHV: 7.21 to 14.3
S2 RDF	0.001	n.a.	n.a.	best in fewer than 3% of draws; no box
S3 AD	0.301	0.31	0.86	carbon_value: 42.9 to 100; tariff = 0; food_separated = 1; paper_garden_share: 0.0311 to 0.279; gas_capture: 0.204 to 0.706
S4 PHB	0.020	n.a.	n.a.	best in fewer than 3% of draws; no box
S5 RDF + AD	0.065	0.31	0.42	carbon_value: 64.3 to 100; kiln_km: 10 to 294; tariff = 0; food_separated = 0; paper_garden_share: 0.131 to 0.527; gas_capture: 0.204 to 0.601

Table 11: PRIM boxes. Coverage: share of all draws where the option is best that fall in the box; density: share of draws in the box where it is best. RDF alone and PHB are best in fewer than 3% of draws.

Reading the rules. The carbon value (importance 0.28), source separation of food (0.43), plant scale (0.12) and kiln distance (0.01) carry the decision; heating value and the tariff matter only for WtE. For **mixed waste without the WtE tariff**, the sanitary landfill with flare is best in 79% of draws and RDF + AD in 10%. The rules are:

- **Sanitary landfill with flare** is preferred for mixed waste without the WtE tariff in most of the condition space; its densest PRIM box is a carbon value below about 70.1 USD/t with no tariff and no source separation (density 0.90).
- **RDF + AD** is the only recovery option that can beat the landfill for mixed waste without the tariff, and only in a narrow region: carbon value: 64.3 to 100, kiln km: 10 to 294, tariff = 0, food separated = 0, paper garden share: 0.131 to 0.527, gas capture: 0.204 to 0.601 (PRIM density 0.42). It never forms a tree leaf, i.e. it is never the majority choice in any broad region of conditions.
- **WtE** is preferred when the Perpres 109/2025 tariff applies, at least 1,000 t/day are delivered and the LHV is at least 7 MJ/kg (PRIM density 0.99); without the tariff it is rarely best.
- **AD alone** is preferred when food waste arrives separated at source and the carbon value exceeds about 30–45 USD/t (tree split at 28 USD/t; PRIM: carbon value: 42.9 to 100, tariff = 0, food separated = 1, paper garden share: 0.0311 to 0.279, gas capture: 0.204 to 0.706).
- **RDF alone and PHB** are best in fewer than 3% of all draws: they are dominated by RDF + AD and by flaring.




Figure 12: Condition maps. Each cell shows the most frequent best option and the share of draws in which it is best, separately for mixed waste without tariff, mixed waste with the Perpres 109/2025 tariff and food separated at source.

Sobol indices. To complement the rank correlations, first-order and total Sobol indices (Saltelli sampling, N = 512 base samples, 60 register inputs plus the common wetness draw; composition fixed at each location's value) were computed for every location and averaged.

Output	Most influential inputs: total index ST (first-order S1)
Carbon-inclusive cost gap RDF + AD minus landfill at 50 USD/t	landfill-gas collection 0.30 (0.30); moisture (wetness) 0.22 (0.22); RDF O&M 0.10 (0.10); AD CAPEX 0.05 (0.06); landfill cost 0.05 (0.06); DOC x DOCf multiplier 0.04 (0.04)
GHG of the sanitary landfill	landfill-gas collection 0.72 (0.70); moisture (wetness) 0.18 (0.16); DOC x DOCf multiplier 0.08 (0.08); garden share of organik 0.02 (0.02)
GHG of WtE	grid factor multiplier 0.42 (0.40); WtE efficiency 0.42 (0.40); moisture (wetness) 0.07 (0.05); LHV calibration 0.05 (0.05)

Table 12: Sobol indices, mean over the 21 locations (outputs/discovery_sobol_mean.csv).

Moisture as received and landfill-gas collection efficiency together explain about half of the variance of the carbon-inclusive cost gap between RDF + AD and the landfill, which is why the moisture scenario of Section 8 can reverse the ranking. These two quantities, together with RDF operating cost and price, are the data to measure first.




Figure 13: Sobol indices for the carbon-inclusive cost gap RDF + AD minus landfill and for the GHG of the landfill, mean over 21 locations.

12 A reproducible decision tool for researchers and planners

The model is packaged as the Python package *mswpath* (core model, input template and validator, scenario discovery, reports and an interactive form) and exposed through *MSW_Decision_Tool_Colab.ipynb*, which runs in Google Colab without installation. The notebook (i) reproduces the results for the 21 RIPS locations; (ii) accepts a one-row-per-city template (*templates/city_input_template.xlsx*, with an English/Indonesian column guide), validates it, applies the same single-projection and normalisation rules and reports every assumption it applies; (iii) offers an interactive form for one city; (iv) re-runs scenario discovery and applies the decision tree to a city described by the user; (v) reports break-even targets and the value of information for a chosen city; and (vi) writes Excel and HTML reports in English or Indonesian that carry the caveats and the data-quality warnings. A round-trip test confirms that two RIPS locations entered through the template reproduce the database results. Versions are pinned in *requirements.txt*, random seeds are fixed and *CITATION.cff* gives the citation.

13 Limits of validity

- **Ex-ante screening.** No option is built in the study locations, so results are estimates for decision support before investment, not an evaluation of plants. Break-even targets and the value of information say what a feasibility study must confirm; they do not replace it.
- **Secondary-data check.** The October 2026 verification used abstracts, indexed records and search extracts because full texts could not be downloaded; values marked L should be checked against the full texts before publication.
- **Temporal proxy.** Compositions sampled 2014 to 2025 represent 2025 without a trend; eight tonnages have an unverified year. Results describe a 2025 baseline *conditional* on these proxies, not a measured 2025 state.
- **Managed-waste definitions.** No single indicator exists for all 21 locations. Rankings on managed tonnage are valid only within series M1, and series M2 mixes definitions. Padang's share is provisional.
- **Moisture and heating value.** No fraction-level moisture or LHV has been measured for the study locations; the LHV values are legacy. The moisture scenarios and stress tests show that this choice can reverse the ranking between landfill and RDF + AD at high carbon values, and the value-of-information analysis ranks local proximate analysis first.
- **Level II/III.** Level II/III compositions are model allocations and their parameters are proxies; they cannot support fraction-level conclusions (for example on recycling of specific resins) until local sorting data exist.
- **Foreign benchmarks.** Danish residual household waste is not Indonesian mixed MSW and not non-domestic waste.
- **Global defaults.** IPCC defaults are global and describe waste as generated, not at the landfill gate.
- **Carbon-inclusive cost.** Only greenhouse gases are valued; health, air pollution, odour, leachate and jobs are not. CED and land take are reported but not monetised.
- **Screening level.** One impact category in the decision; no time dynamics of landfill gas; class-5 costs not escalated; provisional coordinates; independent triangular inputs; Status L values still to be checked against the originals.

- **Coverage.** 21 locations, 12 in Central Java; conclusions about Indonesian conditions in general need more regions.

14 Data gaps carried forward

Measured fraction-level moisture and LHV (local proximate analysis); DOCf for rubber and leather; material composition of coated board, composite film, batteries, HHW and WEEE; Level III food and miscellaneous-paper sorting data; the year of the overview tonnage index; the definition and denominator of the RIPS status index; whether Padang's 141.76 t/d is actual or potential recovery; chlorine and sulphur of RDF; verified plant and kiln coordinates; the numerical tables of Riber et al. (2009). The full list with the decision taken for each item is in CHANGELOG_AND_SOURCE_DECISIONS.md.

References

- Anshassi, M., Smallwood, T., Townsend, T.G. (2022). Life cycle GHG emissions of MSW landfilling versus incineration: expected outcomes based on US landfill gas collection regulations. *Waste Management* 142, 44-54.
- Astrup, T., Møller, J., Fruergaard, T. (2009). Incineration and co-combustion of waste: accounting of greenhouse gases and global warming contributions. *Waste Management & Research* 27, 789-799.
- Astrup, T.F., Tonini, D., Turconi, R., Boldrin, A. (2015). Life cycle assessment of thermal waste-to-energy technologies: review and recommendations. *Waste Management* 37, 104-115.
- Azis, M.M., Kristanto, J., Purnomo, C.W. (2021). A techno-economic evaluation of municipal solid waste (MSW) conversion to energy in Indonesia. *Sustainability* 13, 7232.
- Barlaz, M.A., Chanton, J.P., Green, R.B. (2009). Controls on landfill gas collection efficiency: instantaneous and lifetime performance. *Journal of the Air & Waste Management Association* 59, 1399-1404.
- Chidambarampadmavathy, K., Karthikeyan, O.P., Heimann, K. (2017). Sustainable bio-plastic production through landfill methane recycling. *Renewable and Sustainable Energy Reviews* 71, 555-562.
- Edjabou, M.E., Jensen, M.B., Götze, R., Pivnenko, K., Petersen, C., Scheutz, C., Astrup, T.F. (2015). Municipal solid waste composition: sampling methodology, statistical analyses, and case study evaluation. *Waste Management* 36, 12-23. <https://doi.org/10.1016/j.wasman.2014.11.009>
- Edjabou, M.E., Martín-Fernández, J.A., Scheutz, C., Astrup, T.F. (2017). Statistical analysis of solid waste composition data: arithmetic mean, standard deviation and correlation coefficients. *Waste Management* 69, 13-23.
- European Union (2012). Directive 2012/19/EU on waste electrical and electronic equipment (WEEE).
- Götze, R., Boldrin, A., Scheutz, C., Astrup, T.F. (2016). Physico-chemical characterisation of material fractions in household waste: overview of data in literature. *Waste Management* 49, 3-14. <https://doi.org/10.1016/j.wasman.2016.01.008>
- GIZ ERiC-DKTI (2023). Kajian Analisis Potensi Off-taker Refuse Derived Fuel (RDF). Jakarta.
- IPCC (2006). 2006 IPCC Guidelines for National Greenhouse Gas Inventories, Volume 5 Waste, Chapter 2 (Table 2.4) and Chapter 3.
- IPCC (2019). 2019 Refinement to the 2006 IPCC Guidelines, Volume 5, Chapter 3 (Table 3.0); corrected July 2023.
- IPCC (2021). Climate Change 2021: The Physical Science Basis (AR6 WG1), Chapter 7, Table 7.15.
- Nasrullah, M., Vainikka, P., Hannula, J., Hurme, M., Kärki, J. (2014). Mass, energy and material balances of SRF production process. Part 1: SRF produced from commercial and industrial waste. *Waste Management* 34, 1398-1407.
- Prabowo, B., Simanjuntak, F.S.H., Saldi, Z.S., Samyudia, Y., Widjojo, I.J. (2019). Assessment of waste to energy technology in Indonesia: a techno-economical perspective on a 1000 ton/day scenario. *International Journal of Technology* 10, 1228-1234.
- Raharjo, S., Ariska, R. (2022). Waste-to-energy study for Padang (Jurnal Presipitasi). Reviewed; its heating values are not Padang laboratory data.
- Riber, C., Petersen, C., Christensen, T.H. (2009). Chemical composition of material fractions in Danish household waste. *Waste Management* 29, 1251-1257. <https://doi.org/10.1016/j.wasman.2008.09.013>
- Republic of Indonesia. UU 18/2008; UU 7/2021; Perpres 109/2025; SNI 19-3964-1994; RIPS of the 21 cities/regencies (row-level locators in input_kota_2025_updated.csv).
- Tchobanoglous, G., Theisen, H., Vigil, S. (1993). Integrated Solid Waste Management. McGraw-Hill.
- Zhang, R., El-Mashad, H.M., Hartman, K., et al. (2007). Characterization of food waste as feedstock for anaerobic digestion. *Bioresource Technology* 98, 929-935.
- Seruga, P., et al. (2020). Anaerobic digestion performance: separate collected vs. mechanical segregated organic fractions of municipal solid waste as feedstock. *Energies* 13.
- Basinas, P., et al. (2020). Assessment of high-solid mesophilic and thermophilic anaerobic digestion of mechanically-separated municipal solid waste. *Environmental Research*.
- Basinas, P., et al. (2021). Dry anaerobic digestion of the fine particle fraction of mechanically-sorted organic fraction of municipal solid waste in laboratory and pilot reactor. *Waste Management*.
- Yuliani, M., et al. (2022). Kajian tekno-ekonomi penerapan insinerator waste-to-energy di Indonesia (kasus pada Kota X). *Jurnal Teknologi Lingkungan*.
- Zeng, J.-C., et al. (2024). Environmental, energy, and techno-economic assessment of waste-to-energy incineration. *Sustainability*.
- Febijanto, I., et al. (2024). Municipal solid waste reduction through incineration for electricity purposes and its environmental performance: a case study in Bantargebang, West Java, Indonesia. *Evergreen*.
- Ministry of Energy and Mineral Resources (ESDM) (2018). Grid emission factors of the Indonesian electricity systems, as listed for the Joint Crediting Mechanism by GEC (jcmsbsd30_emission_factor).

- Strong, M., Oakley, J.E., Brennan, A. (2014). Estimating multiparameter partial expected value of perfect information from a probabilistic sensitivity analysis sample: a nonparametric regression approach. *Medical Decision Making* 34, 311-326.
- Friedman, J.H., Fisher, N.I. (1999). Bump hunting in high-dimensional data. *Statistics and Computing* 9, 123-143.
- Saltelli, A., Annoni, P., Azzini, I., Campolongo, F., Ratto, M., Tarantola, S. (2010). Variance based sensitivity analysis of model output: design and estimator for the total sensitivity index. *Computer Physics Communications* 181, 259-270.
- Breiman, L., Friedman, J.H., Olshen, R.A., Stone, C.J. (1984). *Classification and Regression Trees*. Wadsworth.
- Frischknecht, R., Wyss, F., Büsser Knöpfel, S., Lützkendorf, T., Balouktsi, M. (2015). Cumulative energy demand in LCA: the energy harvested approach. *International Journal of Life Cycle Assessment* 20, 957-969.
- Further references for register entries (Manfredi et al. 2009; Mayer et al. 2019; Rand et al. 2000; Silva et al. 2021; Tsilemou & Panagiotakopoulos 2006; World Bank 2024; Levett et al. 2016; Rostkowski et al. 2012; Wei et al. 2024) are as listed in the v2 methodology.