CS317 Information Retrieval Week 05

> Muhammad Rafi March 11, 2021

Computing Scores in Complete Search Systems(VSM)- Optional

Chapter No. 7

Agenda

- Efficient scoring and ranking
- Inexact Top k documents
- Index Elimination
- Champion Lists
- Static Quality Scores
- Impact Ordering
- Cluster Pruning
- Conclusion

| Efficient Scoring and Ranking

- Modified Cosine computation as discussed in the last lecture.
 - Only compute the partial scores for each q term and document d (only common dimensions will add values to score).
 - Should we go for all N document- obviously not.
 - We ae only interested in k top ranked documents
 - How we can make it efficient?
 - If we know in advance that which documents are high-scoring for a given query?
 - If we can arrange all the documents score in an efficient top retrieval data structures (Max. Heap)
 - Any rough estimates of ranking which can be computed quickely will be helpful.

Fast Cosine Scores

FASTCOSINESCORE(q)

- 1 float Scores[N] = 0
- 2 for each d
- 3 **do** Initialize Length[d] to the length of doc d
- 4 for each query term t
- 5 **do** calculate $w_{t,q}$ and fetch postings list for t
- 6 for each pair(d, $tf_{t,d}$) in postings list
- 7 **do** add $wf_{t,d}$ to Scores[d]
- 8 Read the array *Length*[*d*]
- 9 for each d
- 10 **do** Divide *Scores*[*d*] by *Length*[*d*]
- 11 **return** Top *K* components of *Scores*[]

Index Elimination

- Only Consider high-Idf query terms
- Only Consider doc containing many query terms.

Champion List

- Precompute for each dictionary term t, k documents of highest weight in t's postings.
 - Call it champion list for term t
 - Only compute the scores for k documents.
 - This k may not be same for every term t.
 - □ Pick the top (10-20 documents based on scores)

Static Quality Scores


- Top ranking documents should be both "Relevant" and "Authoritative"
 - □ Relevant Terms / cosine scores
 - Authoritative document host (PageRank)
- Modeling Authority
 - Assign a query independent score to each document quality score (0-1)
- NET Score
 - \square NET-score (q,d) = g(d) + cos(q,d)
 - May be weighted combination
 - Return top K documents on NET-Score

Impact Ordering

- Early Termination
 - Process t posting list with fixed k documents.
 - □ Stop for documents having wf(t,d) < alpha
 - □ For each term in query terminate early and get a union for all selected documents.
- idf ordering terms
 - High idf contribute more to score
 - Stop if the doc score is relatively unchanged for next documents.

Cluster Pruning

- Preprocessing
 - Pick some landmark documents for each term
 - From all other documents apply knn to link these documents to a landmark document. (Leader <-> Followers)
- Query Processing
 - Given a q find the nearest leader (landmark document)
 - Get the k nearest document to this leader.
 - Apply Cosine similarity to these



Conclusion

- Large Scale search systems perform a lot of optimizations
- If we can make a user HAPPY we can present results in a Proxy form.
- She will never feel the difference