UNIVERSITY OF BRISTOL

School of Mathematics

Algorithms and Programming in C(++) and R
MATH10017
(Paper code MATH-10017W)

Winter 2026 2 hour 30 minutes

This paper contains two sections: Section A and Section B.
Each section should be answered in a separate booklet.

Section A contains FIVE questions and Section B contains TWO questions.
All SEVEN answers will be used for assessment.

Calculators are not permitted.

MOCK EXAM 2

Do not turn over until instructed.

Section A: Short Questions

A1. (**8 marks**)

(a) (**2 marks**) Which one of the following statements is **wrong**?

(A) In C, the name of an array can be used as a pointer to its first element.

(B) In C, memory obtained with `malloc` is taken from the heap.

(C) In C, the local variables of a function live on the stack.

(D) In C, the stack can never run out of space, so a program can recurse as deeply as it likes.

(E) In R, all the elements of a vector have the same type.

(b) (**3 marks**) Explain the difference between **stack** and **heap** memory in C. State one advantage of each.

(c) (**3 marks**) What is printed by this R code? Briefly justify your answer.

```
x <- seq(2, 10, by = 2)
print(x[x > 5])
```

A2. (**8 marks**)

Read the following C program and answer the questions.

```
#include <stdio.h>

int mystery(int n){
    int r = 0;
    for(int i = 1; i <= n; i++){
        r = r + i;
    }
    return r;
}

int main(void){
    printf("%d\n", mystery(4));
}
```

(a) (**3 marks**) What is the printed output of the program?

(b) (**3 marks**) For a positive integer `n`, what quantity does `mystery(n)` compute?

(c) (**2 marks**) Change the program so that `mystery(n)` instead computes the **product** $1 \times 2 \times \cdots \times n$. State only the lines you have changed.

A3. (**8 marks**)

The following program uses a one-dimensional C array to store a 3 by 3 matrix in **column-major** order. Indices start at zero.

```
#include <stdio.h>

int elem(int M[], int i, int j){
    /* YOUR CODE HERE */
}

int col_total(int M[], int j){
    int total = 0;
    for(int i = 0; i < 3; i++){
        /* YOUR CODE HERE */
    }
    return total;
}

int main(void){
    int M[] = {1,2,3, 4,5,6, 7,8,9};
    printf("%d\n", elem(M, 0, 2));
    printf("%d\n", col_total(M, 1));
}
```

(a) (**2 marks**) Complete `elem` using one line of code, so that it returns the (i, j) entry of a 3 by 3 matrix stored in **column-major** order.

(b) (**4 marks**) Complete the body of the loop in `col_total`, which should return the sum of column `j`, using one line of code. Then state the two numbers printed by the completed program.

(c) (**2 marks**) Suppose the matrix instead has `m` rows and the indexing function and loop bound are changed accordingly. How many additions does `col_total` perform, and what is its time complexity in $O(\cdot)$ notation?

A4. (**8 marks**)

Answer the following questions in R.

(a) (**3 marks**) What is printed by this code?

```
v <- c(3, 8, 1, 6)
print(v[c(TRUE, FALSE, TRUE, FALSE)])
```

(b) (**3 marks**) The function below should return the sum of the **positive** elements of `v`. Assume that `v` contains at least one element. Complete the two missing expressions.

```
sum_pos <- function(v){
  s <- 0
  for(ii in 1:length(v)){
    if(____________________){
      ____________________
    }
  }
  return(s)
}
```

(c) (**2 marks**) Write a vectorised version of `sum_pos` using a single line in the function body.

A5. (**8 marks**)

Consider the following R matrix.

```
X <- matrix(1:6, nrow = 2)
```

(a) (**3 marks**) Write down the first row `X[1, ]` and the second column `X[ , 2]`.

(b) (**3 marks**) Complete the function below so that it returns the largest value in each **column** of `X`. Also state the value returned when it is called on `X`.

```
col_max <- function(X){
  ----------------------
}
```

(c) (**2 marks**) What would `apply(X, 1, max)` return instead, and why is it different?

Section B: Longer Questions

Please use a new booklet for this Part.

B1. (**30 marks**)

A weather service records the midday temperature (in whole degrees Celsius) at three stations over five days. The entry $T_{i,j}$ is the temperature at station i on day j. The matrix is stored in a one-dimensional C array in **row-major** order. Use zero-based indexing throughout this question.

You may use functions from earlier parts of this question even if you did not answer those parts.

```
#include <stdio.h>

/* YOUR FUNCTIONS GO HERE */

int main(void){
    int T[] = {18,20,21,19,17,
               22,23,22,24,25,
               15,14,16,15,13};

    printf("%d\n", station_total(T, 1));
    printf("%d\n", warm_days(T, 0, 19));
    printf("%d\n", warmest_station(T));
}
```

(a) (**10 marks**) Write:

- a function `int reading(int T[], int i, int j)` that returns $T_{i,j}$; and
- a function `int station_total(int T[], int i)` that returns the sum of the five temperatures recorded at station i.

(b) (**10 marks**) Write a function `int warm_days(int T[], int i, int k)` that returns the number of days on which station i recorded a temperature of at least k degrees.

(c) (**10 marks**) Write a function `int warmest_station(int T[])` that returns the index of the station with the largest total. If several stations are tied, returning any one of them is acceptable.

B2. (**30 marks**)

An R data frame stores information about the products sold in a shop: their name, unit price, and the number of units currently in stock.

```
products <- data.frame(
  name  = c("pen", "pad", "clip", "tape"),
  price = c(4, 5, 2, 3),
  stock = c(20, 16, 30, 25)
)
```

Treat each part independently, starting from the original data frame shown above.

You may use functions from earlier parts of this question even if you did not answer those parts.

(a) (**10 marks**) Using the data frame above, write one R expression for each of the following:

(i) return the whole `price` column;

(ii) return the stock of `"clip"` (the third product);

(iii) return the names of the products whose price is at least 3; and

(iv) change the stock of `"clip"` to 90.

(b) (**10 marks**) In both parts below, `df` has the same columns as `products`. Your functions must not use an explicit `for` or `while` loop.

(i) (**5 marks**) Write a function `find_products(df, p, s)` that returns the names of products whose price is at most `p` and whose stock is less than `s`. Both conditions must hold.

(ii) (**5 marks**) Write a function `restock(df, s, amount)` that increases the stock of every product currently holding fewer than `s` units by `amount`. Stocks of other products must remain unchanged. Return the updated data frame.

(c) (**10 marks**) Write an R function `most_valuable(df)` that returns the names of **all** products whose value is the largest. The value of a product is defined as its `price` times its `stock`. Your function must also work when several products tie for the largest value.