

>>> Feature Extraction

>>> GRSS Summer School

Name: Mathieu Fauvel (UMR Dynafor)

Date: [2017-04-26 Wed 10:30]–[2017-04-26 Wed 12:00]

1. Motivations

2. Physical Indices

 Introduction

 Vegetation Indices

 Case study

 Question

3. Statistical Feature Extraction

 Unsupervised

 Supervised

 Questions

4. Spatial feature extraction

 Spatial filters

 Mathematical morphology

 Extension to multivalued images

 Questions

5. References

1. Motivations

2. Physical Indices

 Introduction

 Vegetation Indices

 Case study

 Question

3. Statistical Feature Extraction

 Unsupervised

 Supervised

 Questions

4. Spatial feature extraction

 Spatial filters

 Mathematical morphology



 Extension to multivalued images

 Questions

5. References

- * **Curse of dimensionality:** it is not possible to get enough data to cover all the observation space.
High dimensional spaces are mostly empty !

- * **Curse of dimensionality:** it is not possible to get enough data to cover all the observation space.
High dimensional spaces are mostly empty !
- * Multivariate data live in a lower dimensional space, but which one ?



- ★ Feature extraction is important in remote sensing because:
 - ★ It reduces the size of the data,
 - ★ It limits the spatial and the spectral redundancy,
 - ★ It permits visualization of the data,
 - ★ It mitigates the *curse of dimensionality*.
- ★ Extraction techniques:
 - ★ Spectral
 - ★ Physically based method,
 - ★ Statistical methods.
 - ★ Spatial:
 - ★ Linear filters,
 - ★ Non linear techniques (Mathematical Morphology)

>>> Outline

1. Motivations

2. Physical Indices

Introduction

Vegetation Indices

Case study

Question

3. Statistical Feature Extraction

Unsupervised

Supervised

Questions

4. Spatial feature extraction

Spatial filters

Mathematical morphology

Extension to multivalued images

Questions

5. References

1. Motivations

2. Physical Indices

 Introduction

 Vegetation Indices

 Case study

 Question

3. Statistical Feature Extraction

 Unsupervised

 Supervised

 Questions

4. Spatial feature extraction

 Spatial filters

 Mathematical morphology

 Extension to multivalued images

 Questions

5. References

- ★ Spectral indices are a linear/non-linear combination of two (or more) spectral bands.
- ★ They provides information as a *single number* about:
 - ★ Plant structure,
 - ★ Biochemistry,
 - ★ Humidity,
 - ★ Stress.
- ★ Four main types [TLH11]:

Name	Formulae
Difference vegetation index	$R_{\lambda_1} - R_{\lambda_2}$
Ratio vegetation index	$\frac{R_{\lambda_1}}{R_{\lambda_2}}$
Normalized difference vegetation index	$\frac{R_{\lambda_1} - R_{\lambda_2}}{R_{\lambda_1} + R_{\lambda_2}}$
Soil-adjusted vegetation index	$(1 + L) \times \frac{R_{\lambda_1} - R_{\lambda_2}}{R_{\lambda_1} - R_{\lambda_2} + L}$

- ★ The three last indexes are invariant to a multiplicative factor

Index database : <http://www.indexdatabase.de/>

Name	Formulae (λ nm)
Normalized Difference Vegetation index	$\frac{R_{\lambda 800} - R_{\lambda 670}}{R_{\lambda 800} + R_{\lambda 670}}$
Modified Soil-Adjusted Vegetation Index	$\frac{1}{2} \left[2R_{\lambda 800} + 1 - \sqrt{(2R_{\lambda 800} + 1)^2 - 8(R_{\lambda 800} - R_{\lambda 670})} \right]$
Modified Chlorophyll Absorption Ratio Index	$[(R_{\lambda 700} - R_{\lambda 670}) - 0.2(R_{\lambda 700} - R_{\lambda 550})] \times \frac{R_{\lambda 700}}{R_{\lambda 670}}$
Normalized Difference Water Index	$\frac{R_{\lambda 858} - R_{\lambda 1240}}{R_{\lambda 858} + R_{\lambda 1240}}$
Datt Reflectance Index	$\frac{R_{\lambda 816} - R_{\lambda 2218}}{R_{\lambda 816} + R_{\lambda 2218}}$
Normalized Difference Redness Index	$\frac{R_{\lambda 540} - R_{\lambda 700}}{R_{\lambda 540} + R_{\lambda 700}}$
Soil Brightness Index	$0.406R_{\lambda 550} + 0.600R_{\lambda 650} + 0.645R_{\lambda 750} + 0.243R_{\lambda 950}$

1. Motivations

2. Physical Indices

Introduction

Vegetation Indices

Case study

Question

3. Statistical Feature Extraction

Unsupervised

Supervised

Questions

4. Spatial feature extraction

Spatial filters

Mathematical morphology

Extension to multivalued images


Questions

5. References

>>> Normalized difference vegetation index

$$\text{NDVI} = \frac{R_{\lambda_{800}} - R_{\lambda_{670}}}{R_{\lambda_{800}} + R_{\lambda_{670}}}$$

- ★ $-1 \leq \text{NDVI} \leq 1$
- ★ $\text{NDVI} < 0$: surfaces other than plant cover
- ★ $\text{NDVI} \approx 0$: bare soil
- ★ $\text{NDVI} \geq 0.1$: vegetation cover (higher values correspond to more dense covers)



1. Motivations

2. Physical Indices

Introduction

Vegetation Indices

Case study

Question

3. Statistical Feature Extraction

Unsupervised

Supervised

Questions

4. Spatial feature extraction

Spatial filters

Mathematical morphology

Extension to multivalued images

Questions

5. References



- ★ Peri-urban area
- ★ Rosis-3 sensor
- ★ 103 Spectral bands (400nm-900nm)
- ★ 1.5 meter per pixel spatial resolution
- ★ 610×340 pixels

- ★ OTB is a C++ library for remote sensing images processing.
- ★ It is free, open-source and available for most OS (window, apple, linux)
- ★ OTB-Applications are set of tools appropriated for big/large images
- ★ They are available from QGIS, Python and Bash
- ★ To compute the NDVI


```
# Computation of the NDVI
otbcli_BandMath -il ../Data/university.tif -out ../Data/university_ndvi.tif \
-exp "(im1b83-im1b56)/(im1b83+im1b56)"
```

```
# Computation of the SBI
otbcli_BandMath -il ../Data/university.tif -out ../Data/university_sbi.tif \
-exp "0.406*im1b31 + 0.6*im1b52 + 0.645*im1b73"
```

>>> University of Pavia - Spectral Indices




>>> Where is the vegetation 1/2 ?



Segmentation of the NDVI in three classes

```
otbcli_BandMath -il ../Data/university_ndvi.tif -out ../Data/university_ndvi_segmented.tif \
-exp "(im1b1<0.19?1:(im1b1<0.62?2:3))"
```

>>> Where is the vegetation 1/2 ?



Segmentation of the NDVI in three classes

```
otbcli_BandMath -il ../Data/university_ndvi.tif -out ../Data/university_ndvi_segmented.tif \
-exp "(im1b1<0.19?1:(im1b1<0.62?2:3))"
```

>>> Where is the vegetation 2/2 ?



1. Motivations

2. Physical Indices

Introduction

Vegetation Indices

Case study

Question

3. Statistical Feature Extraction

Unsupervised

Supervised

Questions

4. Spatial feature extraction

Spatial filters

Mathematical morphology

Extension to multivalued images


Questions

5. References

>>> Could you find the good one ?



Image



From the histogram, which one does correspond to the NDVI of the image ?

>>> Outline

1. Motivations

2. Physical Indices

Introduction

Vegetation Indices

Case study

Question

3. Statistical Feature Extraction

Unsupervised

Supervised

Questions

4. Spatial feature extraction

Spatial filters

Mathematical morphology

Extension to multivalued images

Questions

5. References

1. Motivations

2. Physical Indices

Introduction

Vegetation Indices

Case study

Question

3. Statistical Feature Extraction

Unsupervised

Supervised

Questions

4. Spatial feature extraction

Spatial filters

Mathematical morphology

Extension to multivalued images

Questions

5. References


>>> Principal Components Analysis

- ★ Linear transformation used to reduce the dimensionality of the data [Jol02].

$$z_i = \langle \mathbf{v}_i, \mathbf{x} \rangle$$

- ★ Find features \mathbf{z} that account for most of the variability of the data:

- ★ z_1, z_2, z_3, \dots are mutually uncorrelated,
- ★ $\text{var}(z_i)$ is as large as possible,
- ★ $\text{var}(z_1) > \text{var}(z_2) > \text{var}(z_3) > \dots$



>>> Maximization of the variance 1/2

- ★ Search \mathbf{v}_1 such as $\max \text{var}(z_1)$:

$$\begin{aligned}\text{var}(z_1) &= \text{var}(\langle \mathbf{v}_1, \mathbf{x} \rangle) \\ &= \mathbf{v}_1^\top \Sigma \mathbf{v}_1\end{aligned}$$

>>> Maximization of the variance 1/2

- ★ Search \mathbf{v}_1 such as $\max \text{var}(z_1)$:

$$\begin{aligned}\text{var}(z_1) &= \text{var}(\langle \mathbf{v}_1, \mathbf{x} \rangle) \\ &= \mathbf{v}_1^\top \Sigma \mathbf{v}_1\end{aligned}$$

- ★ Indetermined: if $\hat{\mathbf{v}}_1$ maximizes the variance, $\alpha \hat{\mathbf{v}}_1$ too! Add a constraint: $\langle \mathbf{v}_1, \mathbf{v}_1 \rangle = 1$

>>> Maximization of the variance 1/2

- ★ Search \mathbf{v}_1 such as $\max \text{var}(z_1)$:

$$\begin{aligned}\text{var}(z_1) &= \text{var}(\langle \mathbf{v}_1, \mathbf{x} \rangle) \\ &= \mathbf{v}_1^\top \Sigma \mathbf{v}_1\end{aligned}$$

- ★ Indetermined: if $\hat{\mathbf{v}}_1$ maximizes the variance, $\alpha \hat{\mathbf{v}}_1$ too! Add a constraint: $\langle \mathbf{v}_1, \mathbf{v}_1 \rangle = 1$
- ★ Lagrangian:

$$\mathcal{L}(\mathbf{v}_1, \lambda_1) = \mathbf{v}_1^\top \Sigma \mathbf{v}_1 + \lambda_1(1 - \mathbf{v}_1^\top \mathbf{v}_1)$$

>>> Maximization of the variance 1/2

- ★ Search \mathbf{v}_1 such as $\max \text{var}(z_1)$:

$$\begin{aligned}\text{var}(z_1) &= \text{var}(\langle \mathbf{v}_1, \mathbf{x} \rangle) \\ &= \mathbf{v}_1^\top \Sigma \mathbf{v}_1\end{aligned}$$

- ★ Indetermined: if $\hat{\mathbf{v}}_1$ maximizes the variance, $\alpha \hat{\mathbf{v}}_1$ too! Add a constraint: $\langle \mathbf{v}_1, \mathbf{v}_1 \rangle = 1$
- ★ Lagrangian:

$$\mathcal{L}(\mathbf{v}_1, \lambda_1) = \mathbf{v}_1^\top \Sigma \mathbf{v}_1 + \lambda_1(1 - \mathbf{v}_1^\top \mathbf{v}_1)$$

- ★ Compute the derivative w.r.t \mathbf{v}_1 :

$$\frac{\partial \mathcal{L}}{\partial \mathbf{v}_1} = 2\Sigma \mathbf{v}_1 - 2\lambda_1 \mathbf{v}_1$$

>>> Maximization of the variance 1/2

- ★ Search \mathbf{v}_1 such as $\max \text{var}(z_1)$:

$$\begin{aligned}\text{var}(z_1) &= \text{var}(\langle \mathbf{v}_1, \mathbf{x} \rangle) \\ &= \mathbf{v}_1^\top \Sigma \mathbf{v}_1\end{aligned}$$

- ★ Indetermined: if $\hat{\mathbf{v}}_1$ maximizes the variance, $\alpha \hat{\mathbf{v}}_1$ too! Add a constraint: $\langle \mathbf{v}_1, \mathbf{v}_1 \rangle = 1$
- ★ Lagrangian:

$$\mathcal{L}(\mathbf{v}_1, \lambda_1) = \mathbf{v}_1^\top \Sigma \mathbf{v}_1 + \lambda_1(1 - \mathbf{v}_1^\top \mathbf{v}_1)$$

- ★ Compute the derivative w.r.t \mathbf{v}_1 :

$$\frac{\partial \mathcal{L}}{\partial \mathbf{v}_1} = 2\Sigma \mathbf{v}_1 - 2\lambda_1 \mathbf{v}_1$$

- ★ \mathbf{v}_1 is an eigenvector of the covariance matrix of \mathbf{x} :

$$\Sigma \mathbf{v}_1 = \lambda_1 \mathbf{v}_1$$

>>> Maximization of the variance 1/2

- ★ Search \mathbf{v}_1 such as $\max \text{var}(z_1)$:

$$\begin{aligned}\text{var}(z_1) &= \text{var}(\langle \mathbf{v}_1, \mathbf{x} \rangle) \\ &= \mathbf{v}_1^\top \Sigma \mathbf{v}_1\end{aligned}$$

- ★ Indetermined: if $\hat{\mathbf{v}}_1$ maximizes the variance, $\alpha \hat{\mathbf{v}}_1$ too! Add a constraint: $\langle \mathbf{v}_1, \mathbf{v}_1 \rangle = 1$
- ★ Lagrangian:

$$\mathcal{L}(\mathbf{v}_1, \lambda_1) = \mathbf{v}_1^\top \Sigma \mathbf{v}_1 + \lambda_1(1 - \mathbf{v}_1^\top \mathbf{v}_1)$$

- ★ Compute the derivative w.r.t \mathbf{v}_1 :

$$\frac{\partial \mathcal{L}}{\partial \mathbf{v}_1} = 2\Sigma \mathbf{v}_1 - 2\lambda_1 \mathbf{v}_1$$

- ★ \mathbf{v}_1 is an eigenvector of the covariance matrix of \mathbf{x} :

$$\Sigma \mathbf{v}_1 = \lambda_1 \mathbf{v}_1$$

- ★ \mathbf{v}_1 is the eigenvector corresponding to the largest eigenvalues !

$$\text{var}(z_1) = \mathbf{v}_1^\top \Sigma \mathbf{v}_1 = \lambda_1 \mathbf{v}_1^\top \mathbf{v}_1 = \lambda_1$$

>>> Maximization of the variance 2/2

- ★ Search \mathbf{v}_2 such as $\max \text{var}(z_2)$ and $\langle \mathbf{v}_2, \mathbf{v}_2 \rangle = 1$ and $\langle \mathbf{v}_1, \mathbf{v}_2 \rangle = 0$

>>> Maximization of the variance 2/2

- ★ Search \mathbf{v}_2 such as $\max \text{var}(z_2)$ and $\langle \mathbf{v}_2, \mathbf{v}_2 \rangle = 1$ and $\langle \mathbf{v}_1, \mathbf{v}_2 \rangle = 0$
- ★ Lagrangian:

$$\mathcal{L}(\mathbf{v}_2, \lambda_2, \beta_1) = \mathbf{v}_2^\top \Sigma \mathbf{v}_2 + \lambda_2(1 - \mathbf{v}_2^\top \mathbf{v}_2) + \beta_1(0 - \mathbf{v}_2^\top \mathbf{v}_1)$$

>>> Maximization of the variance 2/2

- ★ Search \mathbf{v}_2 such as $\max \text{var}(z_2)$ and $\langle \mathbf{v}_2, \mathbf{v}_2 \rangle = 1$ and $\langle \mathbf{v}_1, \mathbf{v}_2 \rangle = 0$
- ★ Lagrangian:

$$\mathcal{L}(\mathbf{v}_2, \lambda_2, \beta_1) = \mathbf{v}_2^\top \Sigma \mathbf{v}_2 + \lambda_2(1 - \mathbf{v}_2^\top \mathbf{v}_2) + \beta_1(0 - \mathbf{v}_2^\top \mathbf{v}_1)$$

- ★ Compute the derivative w.r.t \mathbf{v}_2 :

$$\begin{aligned}\frac{\partial \mathcal{L}}{\partial \mathbf{v}_2} &= 2\Sigma \mathbf{v}_2 - 2\lambda_2 \mathbf{v}_2 - \beta_1 \mathbf{v}_1 \\ \Sigma \mathbf{v}_2 &= \lambda_2 \mathbf{v}_2 + 2\beta_1 \mathbf{v}_1\end{aligned}$$

>>> Maximization of the variance 2/2

- ★ Search \mathbf{v}_2 such as $\max \text{var}(z_2)$ and $\langle \mathbf{v}_2, \mathbf{v}_2 \rangle = 1$ and $\langle \mathbf{v}_1, \mathbf{v}_2 \rangle = 0$
- ★ Lagrangian:

$$\mathcal{L}(\mathbf{v}_2, \lambda_2, \beta_1) = \mathbf{v}_2^\top \Sigma \mathbf{v}_2 + \lambda_2(1 - \mathbf{v}_2^\top \mathbf{v}_2) + \beta_1(0 - \mathbf{v}_2^\top \mathbf{v}_1)$$

- ★ Compute the derivative w.r.t \mathbf{v}_2 :

$$\begin{aligned}\frac{\partial \mathcal{L}}{\partial \mathbf{v}_2} &= 2\Sigma \mathbf{v}_2 - 2\lambda_2 \mathbf{v}_2 - \beta_1 \mathbf{v}_1 \\ \Sigma \mathbf{v}_2 &= \lambda_2 \mathbf{v}_2 + 2\beta_1 \mathbf{v}_1\end{aligned}$$

- ★ At optimality, $\langle \mathbf{v}_1, \mathbf{v}_2 \rangle = 0$. Left-multiplying by \mathbf{v}_1^\top the above equation:

$$\begin{aligned}\mathbf{v}_1^\top \Sigma \mathbf{v}_2 &= 2\beta_1 \\ \lambda_1 \mathbf{v}_1^\top \mathbf{v}_2 &= 2\beta_1 \\ 0 &= 2\beta_1\end{aligned}$$

>>> Maximization of the variance 2/2

- ★ Search \mathbf{v}_2 such as $\max \text{var}(z_2)$ and $\langle \mathbf{v}_2, \mathbf{v}_2 \rangle = 1$ and $\langle \mathbf{v}_1, \mathbf{v}_2 \rangle = 0$
- ★ Lagrangian:

$$\mathcal{L}(\mathbf{v}_2, \lambda_2, \beta_1) = \mathbf{v}_2^\top \Sigma \mathbf{v}_2 + \lambda_2(1 - \mathbf{v}_2^\top \mathbf{v}_2) + \beta_1(0 - \mathbf{v}_2^\top \mathbf{v}_1)$$

- ★ Compute the derivative w.r.t \mathbf{v}_2 :

$$\begin{aligned}\frac{\partial \mathcal{L}}{\partial \mathbf{v}_2} &= 2\Sigma \mathbf{v}_2 - 2\lambda_2 \mathbf{v}_2 - \beta_1 \mathbf{v}_1 \\ \Sigma \mathbf{v}_2 &= \lambda_2 \mathbf{v}_2 + 2\beta_1 \mathbf{v}_1\end{aligned}$$

- ★ At optimality, $\langle \mathbf{v}_1, \mathbf{v}_2 \rangle = 0$. Left-multiplying by \mathbf{v}_1^\top the above equation:

$$\begin{aligned}\mathbf{v}_1^\top \Sigma \mathbf{v}_2 &= 2\beta_1 \\ \lambda_1 \mathbf{v}_1^\top \mathbf{v}_2 &= 2\beta_1 \\ 0 &= 2\beta_1\end{aligned}$$

- ★ Hence, we have

$$\Sigma \mathbf{v}_2 = \lambda_2 \mathbf{v}_2$$

>>> Maximization of the variance 2/2

- ★ Search \mathbf{v}_2 such as $\max \text{var}(z_2)$ and $\langle \mathbf{v}_2, \mathbf{v}_2 \rangle = 1$ and $\langle \mathbf{v}_1, \mathbf{v}_2 \rangle = 0$
- ★ Lagrangian:

$$\mathcal{L}(\mathbf{v}_2, \lambda_2, \beta_1) = \mathbf{v}_2^\top \Sigma \mathbf{v}_2 + \lambda_2(1 - \mathbf{v}_2^\top \mathbf{v}_2) + \beta_1(0 - \mathbf{v}_2^\top \mathbf{v}_1)$$

- ★ Compute the derivative w.r.t \mathbf{v}_2 :

$$\begin{aligned}\frac{\partial \mathcal{L}}{\partial \mathbf{v}_2} &= 2\Sigma \mathbf{v}_2 - 2\lambda_2 \mathbf{v}_2 - \beta_1 \mathbf{v}_1 \\ \Sigma \mathbf{v}_2 &= \lambda_2 \mathbf{v}_2 + 2\beta_1 \mathbf{v}_1\end{aligned}$$

- ★ At optimality, $\langle \mathbf{v}_1, \mathbf{v}_2 \rangle = 0$. Left-multiplying by \mathbf{v}_1^\top the above equation:

$$\begin{aligned}\mathbf{v}_1^\top \Sigma \mathbf{v}_2 &= 2\beta_1 \\ \lambda_1 \mathbf{v}_1^\top \mathbf{v}_2 &= 2\beta_1 \\ 0 &= 2\beta_1\end{aligned}$$

- ★ Hence, we have

$$\Sigma \mathbf{v}_2 = \lambda_2 \mathbf{v}_2$$

- ★ \mathbf{v}_2 is the eigenvector corresponding the *second largest* eigenvalues

>>> Maximization of the variance 2/2

- ★ Search \mathbf{v}_2 such as $\max \text{var}(z_2)$ and $\langle \mathbf{v}_2, \mathbf{v}_2 \rangle = 1$ and $\langle \mathbf{v}_1, \mathbf{v}_2 \rangle = 0$
- ★ Lagrangian:

$$\mathcal{L}(\mathbf{v}_2, \lambda_2, \beta_1) = \mathbf{v}_2^\top \Sigma \mathbf{v}_2 + \lambda_2(1 - \mathbf{v}_2^\top \mathbf{v}_2) + \beta_1(0 - \mathbf{v}_2^\top \mathbf{v}_1)$$

- ★ Compute the derivative w.r.t \mathbf{v}_2 :

$$\begin{aligned}\frac{\partial \mathcal{L}}{\partial \mathbf{v}_2} &= 2\Sigma \mathbf{v}_2 - 2\lambda_2 \mathbf{v}_2 - \beta_1 \mathbf{v}_1 \\ \Sigma \mathbf{v}_2 &= \lambda_2 \mathbf{v}_2 + 2\beta_1 \mathbf{v}_1\end{aligned}$$

- ★ At optimality, $\langle \mathbf{v}_1, \mathbf{v}_2 \rangle = 0$. Left-multiplying by \mathbf{v}_1^\top the above equation:

$$\begin{aligned}\mathbf{v}_1^\top \Sigma \mathbf{v}_2 &= 2\beta_1 \\ \lambda_1 \mathbf{v}_1^\top \mathbf{v}_2 &= 2\beta_1 \\ 0 &= 2\beta_1\end{aligned}$$

- ★ Hence, we have

$$\Sigma \mathbf{v}_2 = \lambda_2 \mathbf{v}_2$$

- ★ \mathbf{v}_2 is the eigenvector corresponding the *second largest* eigenvalues
- ★ \mathbf{v}_k is the eigenvector corresponding the k^{th} *largest* eigenvalues

1. Empirical estimation the mean value:

$$\boldsymbol{\mu} = \frac{1}{n} \sum_{i=1}^n \mathbf{x}_i$$

2. Empirical estimation the covariance matrix:

$$\boldsymbol{\Sigma} = \frac{1}{n-1} \sum_{i=1}^n (\mathbf{x}_i - \boldsymbol{\mu})(\mathbf{x}_i - \boldsymbol{\mu})^\top$$

3. Compute p first eigenvalues/eigenvectors... How to choose p ? Explained variance:

$$\frac{\sum_{i=1}^p \lambda_i}{\sum_{i=1}^d \lambda_i}$$

4. Tips for high dimensional data set: if $n < d$ see [MLC16] page 420

>>> PCA case study 1/3


```
import rasterTools as rt
import scipy as sp
from sklearn.decomposition import PCA
import matplotlib.pyplot as plt

# Load data set
im,GeoT,Proj = rt.open_data('../Data/university.tif')
[h,w,b]=im.shape
im.shape=(h*w,b)
wave = sp.loadtxt('../Data/waves.csv',delimiter=',,')


# Do PCA
pca = PCA()
pca.fit(im)

# Save Eigenvectors
D = sp.concatenate((wave[:,sp.newaxis],pca.components_[:,3:,:].T),axis=1)
sp.savetxt('../FeatureExtraction/figures/pca_pcs.csv',D,delimiter=',,')
```

* Explained variance



* Principal components



>>> PCA case study 3/3

Projection of the first PCs

```
imp = sp.dot(im,pca.components_[:3,:].T)  
imp.shape = (h,w,3)
```

Save image

```
rt.write_data('..../Data/pca_university.tif',imp,GeoT,Proj)
```



>>> Kernel PCA

- ★ PCA is limited to second order information
- ★ To capture higher-order statistics, it is possible to map the data onto another space \mathcal{H}

$$\begin{aligned}\phi : \mathbb{R}^d &\rightarrow \mathcal{H} \\ \mathbf{x} &\mapsto \phi(\mathbf{x}).\end{aligned}$$

- ★ In \mathcal{H} , conventional PCA can be applied.
- ★ Using the *kernel trick* it is possible to directly work on the *kernel matrix* in \mathbb{R}^d

$$\mathbf{K} = \begin{pmatrix} k(\mathbf{x}_1, \mathbf{x}_1) & k(\mathbf{x}_1, \mathbf{x}_2) & \dots & k(\mathbf{x}_1, \mathbf{x}_n) \\ k(\mathbf{x}_2, \mathbf{x}_1) & k(\mathbf{x}_2, \mathbf{x}_2) & \dots & k(\mathbf{x}_2, \mathbf{x}_n) \\ \vdots & \vdots & \ddots & \vdots \\ k(\mathbf{x}_n, \mathbf{x}_1) & k(\mathbf{x}_n, \mathbf{x}_2) & \dots & k(\mathbf{x}_n, \mathbf{x}_n) \end{pmatrix}.$$

>>> Kernel PCA




- * PCA is limited to second order information
- * To capture higher-order statistics, it is possible to map the data onto another space \mathcal{H}

$$\begin{aligned}\phi : \mathbb{R}^d &\rightarrow \mathcal{H} \\ \mathbf{x} &\mapsto \phi(\mathbf{x}).\end{aligned}$$

- * In \mathcal{H} , conventional PCA can be applied.
- * Using the *kernel trick* it is possible to directly work on the *kernel matrix* in \mathbb{R}^d

$$\mathbf{K} = \begin{pmatrix} k(\mathbf{x}_1, \mathbf{x}_1) & k(\mathbf{x}_1, \mathbf{x}_2) & \dots & k(\mathbf{x}_1, \mathbf{x}_n) \\ k(\mathbf{x}_2, \mathbf{x}_1) & k(\mathbf{x}_2, \mathbf{x}_2) & \dots & k(\mathbf{x}_2, \mathbf{x}_n) \\ \vdots & \vdots & \ddots & \vdots \\ k(\mathbf{x}_n, \mathbf{x}_1) & k(\mathbf{x}_n, \mathbf{x}_2) & \dots & k(\mathbf{x}_n, \mathbf{x}_n) \end{pmatrix}.$$

- * KPCA versus PCA:



- ★ Choose the kernel and its parameters
- ★ Compute the kernel matrix \mathbf{K} for all the pixels (or a subset)
- ★ Center the matrix

$$\mathbf{K}_c = \mathbf{K} - \mathbf{1}_n \mathbf{K} - \mathbf{K} \mathbf{1}_n + \mathbf{1}_n \mathbf{K} \mathbf{1}_n$$

- ★ Solve the eigenproblems

$$\lambda \boldsymbol{\alpha} = \mathbf{K} \boldsymbol{\alpha} \text{ subject to } \|\boldsymbol{\alpha}\|_2 = \frac{1}{\lambda}$$

- ★ Project on the p first *kernel principal components*: $\phi^{kpc}(\mathbf{x}) = [\phi_1^{kpc}(\mathbf{x}) \quad \dots \quad \phi_p^{kpc}(\mathbf{x})]^t$

$$\phi_j^{kpc}(\mathbf{x}) = \sum_{i=1}^n \alpha_{ki} k(\mathbf{x}_i, \mathbf{x})$$

From [FCB09].

```
import rasterTools as rt
import scipy as sp
from sklearn.decomposition import KernelPCA
import matplotlib.pyplot as plt
from sklearn.preprocessing import StandardScaler


# Load data set
im,GeoT,Proj = rt.open_data('../Data/university.tif')
[h,w,b]=im.shape
im.shape=(h*w,b)
wave = sp.loadtxt('../Data/waves.csv',delimiter=',',)

# Scale data
sc = StandardScaler()
im = sc.fit_transform(im)


# Do KPCA
kpca = KernelPCA(kernel='rbf',gamma=1.0/b,n_jobs=-1)
kpca.fit(im[:,::50]) # Use a subset of the total number of pixels
```

>>> KPCA case study 2/3

* Explained variance



* Principal kernel components



>>> KPCA case study 3/3

```
imp = kpca.transform(im)[:, :, 3]
imp.shape = (h, w, 3)

# Save image
rt.write_data('../Data/kpca_university.tif', imp, GeoT, Proj)
```



1. Motivations

2. Physical Indices

Introduction

Vegetation Indices

Case study

Question

3. Statistical Feature Extraction

Unsupervised

Supervised

Questions

4. Spatial feature extraction

Spatial filters


Mathematical morphology

Extension to multivalued images

Questions

5. References

- ★ We observe some $\{\mathbf{x}_i, y_i\}_{i=1}^n$
- ★ Use the label information to find the linear features that highlight differences among classes



- ★ FDA: find \mathbf{a} such as the ratio between the *between projected variance* and the *sample projected variance* is maximal [MLC16] Chap. 8.8

- ★ Between-class covariance matrix:

$$\mathbf{B} = \frac{1}{n} \sum_{c=1}^C n_c (\boldsymbol{\mu}_c - \boldsymbol{\mu})(\boldsymbol{\mu}_c - \boldsymbol{\mu})^\top$$

- ★ Class covariance matrix

$$\boldsymbol{\Sigma}_c = \frac{1}{n_c - 1} \sum_{i=1, i \in c}^{n_c} (\mathbf{x}_i - \boldsymbol{\mu}_c)(\mathbf{x}_i - \boldsymbol{\mu}_c)^\top$$

- ★ Within-class covariance matrix

$$\mathbf{W} = \sum_{c=1}^C \boldsymbol{\Sigma}_c$$

- ★ The Fisher discriminant subspace is given by the eigenvectors of $\mathbf{W}^{(-1)}\mathbf{B}$
- ★ Remark: there are at most $C - 1$ eigenvectors because $\text{Rank}(\mathbf{B}) \leq C - 1$.

```
>>> FDA case study 1/3
```

```
import rasterTools as rt
import scipy as sp
from sklearn.discriminant_analysis import LinearDiscriminantAnalysis



# Load data set
X,y=rt.get_samples_from_roi('../Data/university.tif','../Data/university_gt.tif')
wave = sp.loadtxt('../Data/waves.csv',delimiter=',',)

# Select the same number of samples
nt = 900
xt,yt=[], []
for i in sp.unique(y):
    t = sp.where(y==i)[0]
    nc = t.size
    rp = sp.random.permutation(nc)
    xt.extend(X[t[rp[0:nt]],:])
    yt.extend(y[t[rp[0:nt]]])


xt = sp.asarray(xt)
yt = sp.asarray(yt)

# Do LDA
lda = LinearDiscriminantAnalysis(solver='eigen', shrinkage='auto')
lda.fit(xt,yt.ravel())
```

* Projection on Fisher components



* Fisher components



>>> FDA case study 3/3

```
im,GeoT,Proj = rt.open_data('..../Data/university.tif')
[h,w,b]=im.shape
im.shape=(h*w,b)
imp = lda.transform(im)[:,3]
imp.shape = (h,w,3)
# Save image
rt.write_data('..../Data/lda_university.tif',imp,GeoT,Proj)
```



- ★ Feature selection: pick few features *from* the original ones (no combination)
- ★ In general, for feature selection, we need:
 - ★ *Criterion* to evaluate how perform the model with a given subset
 - ★ *Optimization procedure* to find the subset that minimizes/maximizes the criterion
- ★ For instance:

Criterion	Optimization	Ref.
Entropy	Genetic algorithm	[Cha07]
Jeffries Matusita	Exhaustive Search	[SM07]
Classification error	Forward search/GA	[CBN14; LFG17]
ℓ_1 norm	Linear-SVM	[Tui+14]

- ★ Fast forward strategy based on a nonlinear model driven by an estimate of the classification error or a measure of separability:



Criterion	Type	Complexity
Overall accuracy	Accuracy	High
Cohen's kappa	Accuracy	High
F1 mean	Accuracy	High
Kullback-Leibler divergences	Divergence	Low
Jeffries-Matusita distance	Divergence	Low

- ★ Use *Gaussian Mixture Models* (natural extension for multiclass problem)
- ★ Fast update and fast forward search [LFG17]: based on linear algebra of semi-definite positive matrices

The forward feature selection works as follow:

1. Starts with an empty pool F of selected features,
2. Select the feature f_1 that provides the best value for the selected criterion and add it to F .
3. Select the feature f_2 such that the couple of features (f_1, f_2) provides the best value for the selected criterion and add it to F .
4. Select the feature f_3 such that the triplet of features (f_1, f_2, f_3) ...
5. ...
6. The algorithm stops either if the increase of the criterion is too low or if the maximum number of features is reached.

>>> Algorithm 2/2



>>> FFFS case study 1/3

```
import rasterTools as rt
import scipy as sp
import npfs as npfs


# Load data set
X,y=rt.get_samples_from_roi('..../Data/university.tif','..../Data/university_gt.tif')
wave = sp.loadtxt('..../Data/waves.csv',delimiter=',',)

# Select the same number of samples
nt = 900
xt,yt=[], []
for i in sp.unique(y):
    t = sp.where(y==i)[0]
    nc = t.size
    rp = sp.random.permutation(nc)
    xt.extend(X[t[rp[0:nt]],:])
    yt.extend(y[t[rp[0:nt]]])


xt = sp.asarray(xt)
yt = sp.asarray(yt)

# Do FFFS
maxVar = 12
model = npfs.GMMFeaturesSelection()
model.learn_gmm(xt,yt)
idx, crit, [] = model.selection('forward',xt, yt,criterion='kappa', varNb=maxVar, nfold=5)
```

* Criterion



* Mean projection on best bands



1. Motivations

2. Physical Indices

Introduction

Vegetation Indices

Case study

Question

3. Statistical Feature Extraction

Unsupervised

Supervised

Questions

4. Spatial feature extraction

Spatial filters

Mathematical morphology

Extension to multivalued images

Questions

5. References

>>> Number of features

Given a set of observed pixels $\mathcal{S} = \{(\mathbf{x}_i, y_i)\}_{i=1}^n$ and $\mathbf{x} \in \mathbb{R}^d$. The number of classes C is 3. What is the *maximum* number of features that can be extracted with

- * PCA, when $d = 200$ and $n = 100$: a) 100, b) 200, c) 400 and d) 2.

Given a set of observed pixels $\mathcal{S} = \{(\mathbf{x}_i, y_i)\}_{i=1}^n$ and $\mathbf{x} \in \mathbb{R}^d$. The number of classes C is 3. What is the *maximum* number of features that can be extracted with

- * PCA, when $d = 200$ and $n = 100$: a) 100, b) 200, c) 400 and d) 2.
- * PCA, when $d = 200$ and $n = 400$: a) 100, b) 200, c) 400 and d) 2.

Given a set of observed pixels $\mathcal{S} = \{(\mathbf{x}_i, y_i)\}_{i=1}^n$ and $\mathbf{x} \in \mathbb{R}^d$. The number of classes C is 3. What is the *maximum* number of features that can be extracted with

- * PCA, when $d = 200$ and $n = 100$: a) 100, b) 200, c) 400 and d) 2.
- * PCA, when $d = 200$ and $n = 400$: a) 100, b) 200, c) 400 and d) 2.
- * FDA, when $d = 200$ and $n = 400$: a) 100, b) 200, c) 400 and d) 2.

Given a set of observed pixels $\mathcal{S} = \{(\mathbf{x}_i, y_i)\}_{i=1}^n$ and $\mathbf{x} \in \mathbb{R}^d$. The number of classes C is 3. What is the *maximum* number of features that can be extracted with

- * PCA, when $d = 200$ and $n = 100$: a) 100, b) 200, c) 400 and d) 2.
- * PCA, when $d = 200$ and $n = 400$: a) 100, b) 200, c) 400 and d) 2.
- * FDA, when $d = 200$ and $n = 400$: a) 100, b) 200, c) 400 and d) 2.
- * KPCA, when $d = 200$ and $n = 400$: a) 100, b) 200, c) 400 and d) 2.

Given a set of observed pixels $\mathcal{S} = \{(\mathbf{x}_i, y_i)\}_{i=1}^n$ and $\mathbf{x} \in \mathbb{R}^d$. The number of classes C is 3. What is the *maximum* number of features that can be extracted with

- * PCA, when $d = 200$ and $n = 100$: a) 100, b) 200, c) 400 and d) 2.
- * PCA, when $d = 200$ and $n = 400$: a) 100, b) 200, c) 400 and d) 2.
- * FDA, when $d = 200$ and $n = 400$: a) 100, b) 200, c) 400 and d) 2.
- * KPCA, when $d = 200$ and $n = 400$: a) 100, b) 200, c) 400 and d) 2.
- * KPCA, when $d = 200$ and $n = 100$: a) 100, b) 200, c) 400 and d) 2.


Given a set of observed pixels $\mathcal{S} = \{(\mathbf{x}_i, y_i)\}_{i=1}^n$ and $\mathbf{x} \in \mathbb{R}^d$. The number of classes C is 3. What is the *maximum* number of features that can be extracted with

- * PCA, when $d = 200$ and $n = 100$: a) 100, b) 200, c) 400 and d) 2.
- * PCA, when $d = 200$ and $n = 400$: a) 100, b) 200, c) 400 and d) 2.
- * FDA, when $d = 200$ and $n = 400$: a) 100, b) 200, c) 400 and d) 2.
- * KPCA, when $d = 200$ and $n = 400$: a) 100, b) 200, c) 400 and d) 2.
- * KPCA, when $d = 200$ and $n = 100$: a) 100, b) 200, c) 400 and d) 2.
- * FFFS, when $d = 200$ and $n = 100$: a) 2, b) 7, c) 15 and d) 200.



Given a set of observed pixels $\mathcal{S} = \{(\mathbf{x}_i, y_i)\}_{i=1}^n$ and $\mathbf{x} \in \mathbb{R}^d$. The number of classes C is 3. What is the *maximum* number of features that can be extracted with

- * PCA, when $d = 200$ and $n = 100$: a) 100, b) 200, c) 400 and d) 2.
- * PCA, when $d = 200$ and $n = 400$: a) 100, b) 200, c) 400 and d) 2.
- * FDA, when $d = 200$ and $n = 400$: a) 100, b) 200, c) 400 and d) 2.
- * KPCA, when $d = 200$ and $n = 400$: a) 100, b) 200, c) 400 and d) 2.
- * KPCA, when $d = 200$ and $n = 100$: a) 100, b) 200, c) 400 and d) 2.
- * FFFS, when $d = 200$ and $n = 100$: a) 2, b) 7, c) 15 and d) 200.
- * FFFS, when $d = 200$ and $n = 400$: a) 2, b) 7, c) 15 and d) 200.

- ★ Given the following data set, using the Gaussian kernel, how do you expect KPCA will behave:
 - as usual,
 - poorly





- Given the following data set, using the Gaussian kernel, how do you expect KPCA will behave:
 - as usual,
 - poorly



- ★ Given the following data set, using the Gaussian kernel, how do you expect KPCA will behave:
 - as usual,
 - poorly
- ★ Gaussian kernel:



$$k(\mathbf{x}_i, \mathbf{x}_j) = \exp\left[-\frac{\|\mathbf{x}_i - \mathbf{x}_j\|^2}{2\sigma^2}\right] = \exp\left[-\frac{\sum_{l=1}^d (\mathbf{x}_{il} - \mathbf{x}_{jl})^2}{2\sigma^2}\right]$$



- Given the following data set, using the Gaussian kernel, how do you expect KPCA will behave:
 - as usual,
 - poorly
- Gaussian kernel:

$$k(\mathbf{x}_i, \mathbf{x}_j) = \exp\left[-\frac{\|\mathbf{x}_i - \mathbf{x}_j\|^2}{2\sigma^2}\right] = \exp\left[-\frac{\sum_{l=1}^d (\mathbf{x}_{il} - \mathbf{x}_{jl})^2}{2\sigma^2}\right]$$




- Solution: scale the features (e.g., zero mean and unit variance)



- Given the following data set, using the Gaussian kernel, how do you expect KPCA will behave:
 - as usual,
 - poorly
- Gaussian kernel:

$$k(\mathbf{x}_i, \mathbf{x}_j) = \exp\left[-\frac{\|\mathbf{x}_i - \mathbf{x}_j\|^2}{2\sigma^2}\right] = \exp\left[-\frac{\sum_{l=1}^d (\mathbf{x}_{il} - \mathbf{x}_{jl})^2}{2\sigma^2}\right]$$





- Solution: scale the features (e.g., zero mean and unit variance)



- Given the following data set, using the Gaussian kernel, how do you expect KPCA will behave:
 - as usual,
 - poorly
- Gaussian kernel:

$$k(\mathbf{x}_i, \mathbf{x}_j) = \exp\left[-\frac{\|\mathbf{x}_i - \mathbf{x}_j\|^2}{2\sigma^2}\right] = \exp\left[-\frac{\sum_{l=1}^d (\mathbf{x}_{il} - \mathbf{x}_{jl})^2}{2\sigma^2}\right]$$

- Solution: scale the features (e.g., zero mean and unit variance)



>>> Outline

1. Motivations

2. Physical Indices

Introduction

Vegetation Indices

Case study

Question

3. Statistical Feature Extraction

Unsupervised

Supervised

Questions

4. Spatial feature extraction

Spatial filters






Mathematical morphology

Extension to multivalued images

Questions

5. References

>>> Why spatial feature extraction?



>>> More on this topics

Image analysis of hyperspectral data using mathematical morphology

Tutorial WHISPERS 2014: Lesson, Labwork and full matlab implementation !

Dalla Mura, Mauro, & Fauvel, Mathieu. (2014, June).

Image analysis of hyperspectral data using mathematical morphology.

Zenodo. <http://doi.org/10.5281/zenodo.437195>

1. Motivations

2. Physical Indices

Introduction

Vegetation Indices

Case study

Question

3. Statistical Feature Extraction

Unsupervised

Supervised

Questions

4. Spatial feature extraction

Spatial filters

Mathematical morphology

Extension to multivalued images

Questions

5. References

- ★ The neighborhood of a given pixel is the set of pixels that are connected to it.
- ★ For a flat (grayscale) image :

$\mathbf{x}_{-1,-1}$	$\mathbf{x}_{0,-1}$	$\mathbf{x}_{1,-1}$
$\mathbf{x}_{-1,0}$	$\mathbf{x}_{0,0}$	$\mathbf{x}_{1,0}$
$\mathbf{x}_{-1,1}$	$\mathbf{x}_{0,1}$	$\mathbf{x}_{1,1}$

4-connected

$\mathbf{x}_{-1,-1}$	$\mathbf{x}_{0,-1}$	$\mathbf{x}_{1,-1}$
$\mathbf{x}_{-1,0}$	$\mathbf{x}_{0,0}$	$\mathbf{x}_{1,0}$
$\mathbf{x}_{-1,1}$	$\mathbf{x}_{0,1}$	$\mathbf{x}_{1,1}$

8-connected

- ★ Wide range of processing are based on pixel neighborhood


- ★ De noising,
- ★ Texture analysis,
- ★ Edges detection,
- ★ Pattern recognition,
- ★ ...

Steps:

1. Define the template G : 4/8-connected and size
2. Define the processing f on the neighborhood. If f is linear \leftrightarrow convolution.
3. Scan all the pixels:

$$\mathbf{x}_{ij}^f = f(\mathbf{x}_1, \dots, \mathbf{x}_N), \quad \mathbf{x}_n \in G(i, j)$$

Max Filter



- * $G = \begin{bmatrix} 1 & 1 & 1 \\ 1 & 1 & 1 \\ 1 & 1 & 1 \end{bmatrix}$, for a 3×3 neighborhood.

- * Mean filter

$$\mathbf{x}^m(x, y) = \frac{1}{9} \sum_{i,j=-1}^1 \mathbf{x}(x+i, y+j)$$

- * Variance filter:

$$\mathbf{x}^v(x, y) = \frac{1}{9} \sum_{i,j=-1}^1 (\mathbf{x}(x+i, y+j) - \mathbf{x}^m(x, y))^2$$

- * Range filter:

$$\mathbf{x}^r(x, y) = \max_{i,j \in G} [\mathbf{x}(x+i, y+j)] - \min_{i,j \in G} [\mathbf{x}(x+i, y+j)]$$

- * Median filter:

$$\mathbf{x}^m(x, y) = \text{median}_{i,j \in G} [\mathbf{x}(x+i, y+j)]$$

>>> Template filters in action 1/3

For multidimensional images: Use spectral feature extraction to get flat images! See 3

```
# Compute the different filters with a template of size 3x3 and 11x11
for i in 3 11
do
    # Mean filter
    otbcli_BandMathX -il ../Data/pca_university.tif -out ../Data/pca_mean_${i}_${i}_university.tif \
        -exp "mean(im1b1N${i}x${i}); mean(im1b2N${i}x${i}); mean(im1b3N${i}x${i})"

    # Var filter
    otbcli_BandMathX -il ../Data/pca_university.tif -out ../Data/pca_std_${i}_${i}_university.tif \
        -exp "var(im1b1N${i}x${i}); var(im1b2N${i}x${i}); var(im1b3N${i}x${i})"



    # Range filter
    otbcli_BandMathX -il ../Data/pca_university.tif -out ../Data/pca_range_${i}_${i}_university.tif \
        -exp "vmax(im1b1N${i}x${i})-vmin(im1b1N${i}x${i}); vmax(im1b2N${i}x${i})-vmin(im1b2N${i}x${i}); \
            vmax(im1b3N${i}x${i})-vmin(im1b3N${i}x${i})"

    # Median filter
    otbcli_BandMathX -il ../Data/pca_university.tif -out ../Data/pca_median_${i}_${i}_university.tif \
        -exp "median(im1b1N${i}x${i}); median(im1b2N${i}x${i}); median(im1b3N${i}x${i})"
done
```

>>> Template filters in action 2/3



>>> Template filters in action 3/3



1. Motivations

2. Physical Indices

Introduction

Vegetation Indices

Case study

Question

3. Statistical Feature Extraction

Unsupervised

Supervised

Questions

4. Spatial feature extraction

Spatial filters



Mathematical morphology

Extension to multivalued images



Questions

5. References

- ★ Mathematical morphology: non-linear image processing.
- ★ A lot of applications in geoscience and remote sensing, see [SP02]
- ★ Erosion: template filter with a min operation in G (called *structuring element*)
- ★ Dilation: template filter with a max operation in G



>>> Effects of structuring elements



0	0	1	0	0
0	1	1	1	0
1	1	1	1	1
0	1	1	1	0
0	0	1	0	0

0	0	0	0	0
0	1	1	1	0
0	1	1	1	0
0	1	1	1	0
0	0	0	0	0

0	0	0	0	1
0	0	0	1	0
0	0	1	0	0
0	1	0	0	0
1	0	0	0	0



>>> Opening and closing

* Opening:

- * *Erosion* followed by a *dilation*
- * Remove bright objects that are smaller than the SE

* Closing:

- * *Dilation* followed by an *erosion*
- * Remove dark objects that are smaller than the SE



>>> Opening and closing

* Opening:

- * *Erosion* followed by a *dilation*
- * Remove bright objects that are smaller than the SE

* Opening by reconstruction:




- * *Erosion* followed by a *reconstruction*
- * Completely removes bright objects that are smaller than the SE, otherwise preserve it

* Closing:

- * *Dilation* followed by an *erosion*
- * Remove dark objects that are smaller than the SE


* Closing by reconstruction:

- * *Dilation* followed by an *erosion*
- * Completely removes dark objects that are smaller than the SE, otherwise preserve it



>>> Opening and closing profile

- ★ For a given B , γ_B^r (resp. ϕ_B^r) indicates which clear (dark) objects fit B .



- ★ Applying γ_{B_i} with a set of $\{B_i | B_i \subset B_{i+1}, i \in [1, \dots, n]\}$: **Opening Profile**
- ★ Applying ϕ_{B_i} with a set of $\{B_i | B_i \subset B_{i+1}, i \in [1, \dots, n]\}$: **Closing Profile**

1. Motivations

2. Physical Indices

Introduction

Vegetation Indices

Case study

Question

3. Statistical Feature Extraction

Unsupervised

Supervised

Questions

4. Spatial feature extraction

Spatial filters

Mathematical morphology

Extension to multivalued images

Questions

5. References

- ★ MM is based on inf and sup operators
- ★ No unambiguous inf / sup for pixel/vector:

$$\begin{bmatrix} 1 \\ 5 \\ 2 \end{bmatrix} \stackrel{?}{\leqslant} \begin{bmatrix} 0 \\ 6 \\ 1 \end{bmatrix}$$

- ★ Marginal ordering \Rightarrow by band filtering
- ★ Reduced ordering $\Rightarrow h : \mathbb{R}^d \rightarrow \mathbb{R}$
$$\mathbf{x} \mapsto h(x)$$
- ★ Use spectral feature extraction *then* spatial feature extraction.

1. Motivations

2. Physical Indices

Introduction

Vegetation Indices

Case study

Question

3. Statistical Feature Extraction

Unsupervised

Supervised

Questions

4. Spatial feature extraction

Spatial filters

Mathematical morphology

Extension to multivalued images

Questions

5. References


- ★ The image has been corrupted by a *salt and pepper* noise, which filter should we use to filter it ?
 - a) mean filter, b) opening, c) median filter and d) closing.
- ★ To remove the small cars on the road, which filter should we use to filter it ?
 - a) mean filter, b) opening, c) median filter and d) closing.



- ★ The image has been corrupted by a *salt and pepper* noise, which filter should we use to filter it ?
 - a) mean filter, b) opening, c) median filter and d) closing.
- ★ To remove the small cars on the road, which filter should we use to filter it ?
 - a) mean filter, b) opening, c) median filter and d) closing.



- ★ The image has been corrupted by a *salt and pepper* noise, which filter should we use to filter it ?
a) mean filter, b) opening, c) median filter and d) closing.
- ★ To remove the small cars on the road, which filter should we use to filter it ?
a) mean filter, b) opening, c) median filter and d) closing.



>>> Outline

1. Motivations

2. Physical Indices

Introduction

Vegetation Indices

Case study

Question

3. Statistical Feature Extraction

Unsupervised

Supervised

Questions

4. Spatial feature extraction

Spatial filters

Mathematical morphology

Extension to multivalued images

Questions

5. References

- Chang, C.-I. *Hyperspectral Data Exploitation: Theory and Applications*. Wiley, 2007.
- Chehata, N., A. Le Bris, and S. Najjar. "Contribution of band selection and fusion for hyperspectral classification". In: *Proc. of the IEEE WHISPERS'14*. 2014.
- Fauvel, Mathieu, Jocelyn Chanussot, and Jon Atli Benediktsson. "Kernel principal component analysis for the classification of hyperspectral remote sensing data over urban areas". In: *EURASIP Journal on Advances in Signal Processing* 2009 (2009), p. 11.
- Jolliffe, I.T. *Principal Component Analysis*. Springer Series in Statistics. Springer, 2002. ISBN: 9780387954424. URL: https://books.google.fr/books?id=%5C_o1ByCrhjwIC.
- Lagrange, A., M. Fauvel, and M. Grizonnet. "Large-scale feature selection with Gaussian mixture models for the classification of high dimensional remote sensing images". In: *IEEE Transactions on Computational Imaging* PP.99 (2017), pp. 1–1. ISSN: 2333-9403. DOI: [10.1109/TCI.2017.2666551](https://doi.org/10.1109/TCI.2017.2666551).
- Manolakis, D., R. Lockwood, and T. Cooley. *Hyperspectral Imaging Remote Sensing: Physics, Sensors, and Algorithms*. Cambridge University Press, 2016. ISBN: 9781316033401. URL: <https://books.google.fr/books?id=Zeg8DQAAQBAJ>.
- Serpico, S.B. and G. Moser. "Extraction of Spectral Channels From Hyperspectral Images for Classification Purposes". In: *Geoscience and Remote Sensing, IEEE Transactions on* 45.2 (Feb. 2007), pp. 484–495.

- Soille, P. and M. Pesaresi. "Advances in Mathematical Morphology Applied to Geoscience and remote Sensing". In: *IEEE Trans. Geosci. Remote Sens* 40.9 (Sept. 2002), pp. 2042–2055.
- Thenkabail, P. S., J. G. Lyon, and A. Huete. *Hyperspectral Remote Sensing of Vegetation*. CRC Press, 211.
- Tuia, D. et al. "Automatic Feature Learning for Spatio-Spectral Image Classification With Sparse SVM". In: *Geoscience and Remote Sensing, IEEE Transactions on* PP.99 (2014), pp. 1–13.

Creative Commons Attribution-ShareAlike 4.0 Unported License

