


# Practice Problems 2/8/2016

## Part 1: Node Diagrams


All of these problems below were taken from <http://jhave.org/jhavepop/java/exercises.html>

1. Use a single assignment statement to make the variable p refer to the Node with info '2'.




Answer: `p = p.next;`


2. Redo exercise 1, but this time your assignment statement must refer to both variables p and q.




3. Use a single assignment statement to make the variable q refer to the Node with info '1'.




4. Use a single assignment statement to make the variable r refer to the Node with info '2'.




5. Use a single assignment statement to set the info of the Node referred to by p equal to the info of the Node referred to by r (you must access this info through r; do not refer to the character '3' directly).




6. Redo exercise 5 by referring only to variable p (not r). You may not refer to the character '3' directly.




7. Write a single assignment statement to transform the linked list headed by p into a circular linked list. Your assignment statement must refer to both variables p and r.




8. Redo exercise 7 but, this time, your assignment statement must refer to both variables p and q.



9. Redo exercise 7 but, this time, your assignment statement must refer only to variable p.



10. Write a single assignment statement to remove the Node with info 'B' from the linked list headed by p. Your assignment statement must refer to both variables p and q.



## Part 2: Node Code

1. Given the `Node<T>` class from the texbook with the `setNext(Node<T> nextNode)` method; execution of the following code would result in what order of Nodes:

```
Node<String> firstNode = new Node<String>("A");
Node<String> b = new Node<String>("B");
Node<String> c = new Node<String>("C");
firstNode.setNextNode(c);
b.setNextNode(c);
firstNode.setNextNode(b);
```

2. Given that a linked chain exists in memory as represented by the following:

`firstNode` → "A" → "B" → "C" → "D" → "E"

Consider execution of the following code, upon the linked chain above. What is the resulting order of Nodes?

```
Node<String> p = firstNode;
Node<String> q = firstNode;
Node<String> r = firstNode;
while( r.next != null )
{
    p = q;
    q = r;
    r = r.next;
}
p.next = r;
q.next = null;
r.next = q;
```

3. Given that a linked chain exists in memory as represented by the following:

`firstNode` → "A" → "B" → "C" → "D"

Consider execution of the following code, upon the linked chain above. What is the resulting order of Nodes?

```
Node<String> x = firstNode.next;
```

```
firstNode.next = x.next;  
x.next = firstNode;  
firstNode = x;
```

4. Given the Node<T> class from the textbook with the constructor Node(T dataPortion, Node<T> nextNode); execution of the following code, would result in what order of Nodes?

```
Node<String> a = new Node<String>("A");  
Node<String> b = new Node<String>("B", a);  
Node<String> d = new Node<String>("D", b);  
Node<String> c = new Node<String>("C", d);  
Node<String> firstNode = c;
```

### Part 3: Eclipse Shortcuts

Try these out!

1. Move a row of code up/down- alt + up/down arrow
2. Fixes import statement by adding missing ones and deleting unused ones- ctrl/command + shift + o
3. Format code- ctrl/command + shift + f
4. Fixes indentation- ctrl/command + i