SAT Resetmaxxing for Fun and Profit
(Final Title TBD)

Martin S. Fixman[1], Fredrik Rømming[2], and Sean B. Holden[3]

University of Cambridge,
United Kingdom
[1]msf43@cl.cam.ac.uk [2]fr409@cl.cam.ac.uk [3]sbh11@cl.cam.ac.uk

Abstract

We improve SATCoP performance by resetting the connection tableau often. This causes more and more varied SAT statements to be added to the SAT prover, which causes it to saturate faster. The resulting prover solves problems faster and in fewer steps than SATCoP and the current state-of-the-art tableau provers.

Contents

1 Introduction **1**

2 Preliminaries **1**
2.1 Tableau Solving Methods . . . 1
2.2 SATCoP and Similar Methods . . . 2

3 Research Vehicle **2**
3.1 ResetSATCoP Specification . . . 2
3.2 Python Implementation . . . 3
3.3 TPTP Benchmarking . . . 3

4 Experimental Evaluation **3**
4.1 Correctness Verification: Problem Satisfiability . . . 3

5 Future Work **3**

1 Introduction

[Write an introduction that enhances the abstract.]

2 Preliminaries

2.1 Tableau Solving Methods

Minimalist tableau-style provers based on Prolog have been used with great success since the release of leanTAP in 1995[1], and have consistently achieved high rankings in solving FOF and CNF problems in the Thousands of Problems for Theorem Provers (TPTP) library[12].

Rather than working like saturation provers such as Vampire[10], which repeatedly derive new clauses from the current clause set until they derive a contradiction or reach saturation, tableau-based provers attempt to create a Connection Tableau with ground terms. The prover builds a tree, where each node corresponds to a particular clause of the problem in conjunctive normal form, using one of the following four steps.

leanCoP improves on earlier connection-tableau provers by combining a very small Prolog implementation with aggressive restricted backtracking[7, 6]. Successful Reduction and Extension

[Add a diagram and/or a description.]

Figure 1: Description of the operations of Tableau calculus[3].

steps commit with a Prolog `cut (!)`, pruning alternative continuations and often reducing search substantially. To maximise the variety of substitutions in the tableau the maximum height of the tree is constrained, and each subsequent Start increases this height. A similar technique is later used in SATResetCoP, which is presented in this paper.

meanCoP revisits this design by separating the effects of Reduction cuts and Extension cuts, and by replacing leanCoP's particularly strong pruning with more selective exclusive cuts[3]. In particular, meanCoP commits only when a successful proof step rules out sibling alternatives at the current choice point, and otherwise allows ordinary backtracking to continue[3]. This keeps much of the practical benefit of cut-based control while avoiding some of the unnecessary incompleteness and over-commitment of the original leanCoP strategy[3].

The leanCoP line has also been extended in several other directions. Functional and machine-learning-guided connection provers refine proof-step ordering and clause selection[4], rlCoP and plCoP add Monte Carlo Tree Search and reinforcement-learning-based control to leanCoP-style proof search[5, 13], and recent work on proof syntax and certification makes connection proofs easier to exchange and verify[8].

2.2 SATCoP and Similar Methods

Rawson and Reger integrate a SAT prover into a clausal tableau system based on leanCoP[9]. Grounded clauses generated in Tableau extensions are added to a SAT solver. The SAT solver resulting in an unsatisfiable set of ground clauses is sufficient to prove that the entire problem is unsatisfiable.

This technique of combining a saturation-style prover with tableau guidance is surprisingly effective at finding solutions before the tableau is closed. As noted by Rawson and Reger, there is a wide range of undiscovered improvements to this technique.

[Check that: 1. SATCoP's tableau guidance is based on leanCoP. 2. The SAT prover part counts as a "saturation prover".]

3 Research Vehicle

3.1 ResetSATCoP Specification

We propose implementing a new tableau prover, based on SATCoP, but whose tableau prover attempts to saturate the SAT prover rather than to close the tableau.

Successive experimentation resulted in a simple hypothesis: aggressively resetting the tree when the SAT solver stops growing results in a larger quantity and variety of SAT statements added to the solver, which results in reaching a SAT unsatisfiability proof faster.

ResetSATCoP[1] uses the same substitution and SAT prover unsatisfiability technique as SATCoP. However, instead of following leanCoP's tableau guidance strategy, it prioritises resetting the tableau often.

1. Choose the next action as in SATSolveLiteral. [Elaborate].
2. Cut (!) reductions and extensions, as in LeanCoP.
3. If the next action is a Backtrack, then Reset the entire tree from scratch.
   (a) If new SAT clauses were added in this tree, keep its same maximum height.
   (b) Otherwise, attempt to make a deeper tree and increase its maximum height by 1.

3.2 Python Implementation

As a testbed for out experiments we use a Python implementation of leanCoP, PyCoP. [PyCoP is as of yet unreleased. Is there anything I can cite here?] This program implements classical tableau calculus and supports leanCoP-style CUTs, different maximum heights, and adding a SAT solver to implement a SATCoP-style prover.

Most importantly, the program allows us to implement different strategies to guide the tableau proof. This makes implementing the guidance of ResetSATCoP simple and its code easy to read and evaluate.

The source code for this implementation is present in https://github.com/mfixman/resetsatcop, and is released under the GNU Lesser General Public Licence[2].

3.3 TPTP Benchmarking

Along with out implementation of ResetSATCoP, PyCoP allows us to reimplement leanCoP and SATCoP in its own backend. This provides a fairer baseline for comparison.

We run ResetSATCoP along with our versions of these two connection tableau strategies, along with a strategy that chooses the first possible action as control, on the 8344 CNF problems and 9091 FOF problems of the Thousands of Problems for Theorem Provers (TPTP) library[11]. This library provides us with a

4 Experimental Evaluation

4.1 Correctness Verification: Problem Satisfiability

5 Future Work

References

[1] Bernhard Beckert and Joachim Posegga. leanTAP: Lean tableau-based deduction. 15(3):339–358, 1995.
[2] Free Software Foundation. GNU lesser general public license, version 3, 2007.
[3] Michael Färber. A Curiously Effective Backtracking Strategy for Connection Tableaux, 2024.

[1] [This is SATResetAtStaleBacktrack in the code. I plan to rename this strategy to ResetSATCoP.]

[4] Michael Färber, Cezary Kaliszyk, and Josef Urban. Machine Learning Guidance for Connection Tableaux. 65(2):287–320, 2021.

[5] Cezary Kaliszyk, Josef Urban, Henryk Michalewski, and Miroslav Olšák. Reinforcement learning of theorem proving. In S. Bengio, H. Wallach, H. Larochelle, K. Grauman, N. Cesa-Bianchi, and R. Garnett, editors, *Advances in Neural Information Processing Systems*, volume 31, pages 8836–8847. Curran Associates, Inc., 2018.

[6] Jens Otten. Restricting backtracking in connection calculi. 23(2–3):159–182, 2010.

[7] Jens Otten and Wolfgang Bibel. leanCoP: Lean connection-based theorem proving. 36(1–2):139–161, 2003.

[8] Jens Otten and Sean Holden. A Syntax for Connection Proofs, 2023.

[9] Michael Rawson and Giles Reger. Eliminating Models During Model Elimination. In Anupam Das and Sara Negri, editors, *Automated Reasoning with Analytic Tableaux and Related Methods*, volume 12842, pages 250–265. Springer International Publishing.

[10] Alexandre Riazanov and Andrei Voronkov. The design and implementation of VAMPIRE. 15(2–3):91–110, 2002.

[11] G. Sutcliffe. Stepping Stones in the TPTP World. In C. Benzmüller, M. Heule, and R. Schmidt, editors, *Proceedings of the 12th International Joint Conference on Automated Reasoning*, number 14739 in Lecture Notes in Artificial Intelligence, pages 30–50, 2024.

[12] Geoff Sutcliffe. The 12th IJCAR automated theorem proving system competition—CASC-J12. 38(1):3–20, 2025.

[13] Zsolt Zombori, Josef Urban, and Chad E. Brown. Prolog Technology Reinforcement Learning Prover: (System Description). In Nicolas Peltier and Viorica Sofronie-Stokkermans, editors, *Automated Reasoning*, volume 12167, pages 489–507. Springer International Publishing, 2020.