

Open Hardware DSP Platform – [www.ohdsp.org](http://www.ohdsp.org)  
CoreOne – xCORE200 Platform  
Revision 2.0



#### Notes:

4 layer stackup:  
1oz copper  
0.2mm FR4  
0.5oz copper  
1mm to 1.2mm FR4  
0.5oz copper  
0.2mm FR4  
1oz copper

eg Dirty PCB or JLCPCB JLC7628 Stackups

Use 26AWG ribbon cables to match PCB impedances (approx 89ohm)

Copyright Paul Janicki 2019  
Licensed under the TAPR Open Hardware License ([www.tapr.org/OHL](http://www.tapr.org/OHL)). This documentation is distributed WITHOUT ANY EXPRESS OR IMPLIED WARRANTY, INCLUDING OF MERCHANTABILITY, SATISFACTORY QUALITY AND FITNESS FOR A PARTICULAR PURPOSE.  
**Open Hardware DSP Platform – [www.ohdsp.org](http://www.ohdsp.org)**

Sheet:  
File: CoreOne-xCORE200-2.0.kicad\_pcb

**Title: CoreOne – xCORE200 Platform**

Size: A4	Date: 2019-04-02	Rev: 2.0
KiCad E.D.A. kicad (5.1.0)-1		Id: 1/1