

GOLDS-UFSC Documentation

GOLDS-UFSC Documentation SpaceLab, Universidade Federal de Santa Catarina, Florianópolis - Brazil

GOLDS-UFSC Documentation

June, 2020

Project Chief:

Eduardo Augusto Bezerra

Authors:

Gabriel Mariano Marcelino André Martins Pio de Mattos Eduardo Augusto Bezerra

Contributing Authors:

Revision Control:

Version	Author	Changes	Date
0.1	Gabriel M. Marcelino	Document creation	2020/06/05



© 2020 by SpaceLab. GOLDS-UFSC Documentation. This work is licensed under the Creative Commons Attribution–ShareAlike 4.0 International License. To view a copy of this license, visit http://creativecommons.org/licenses/by-sa/4.0/.

· · · · · · · · · · · · · · · · · · ·	List of Figures
---------------------------------------	-----------------

4.1	Reference diagram of the PC-104 bus.		8
-----	--------------------------------------	--	---

List of Tables

4.1	PC-104 bus pinout	9
	PC-104 bus signal description	

Contents

Lis	st of Figures	V
Lis	sta of Tables	vii
No	omenclature	vii
1	Introduction1.1 Mission Description1.2 Mission Objectives	1 1
2	Mission Requirements	3
3	Mission Schedule	5
4	Overall Description 4.1 General Diagrams 4.2 General Behaviour 4.3 Power Budget 4.4 Link Budget 4.5 PC-104 Bus	7 7 7 7 7
5	Subsystems 5.1 On-Board Data Handling	11 11 11 11 11 11
6	Ground Segment	13
7	Operation Planning	15
Re	eferences	15

Introduction

.

1.1 Mission Description

.

1.2 Mission Objectives

Mission Requirements

Mission Schedule

Overall Description

.

4.1 General Diagrams

.

4.2 General Behaviour

.

4.3 Power Budget

.

4.4 Link Budget

.

4.5 PC-104 Bus




Figure 4.1: Reference diagram of the PC-104 bus.

Din Daw	H1 Odd	H1 Even	H2 Odd	H2 Even
Pin Row	HT Odd	HI Even	H2 Odd	H2 Even
1-2	_	_	_	_
3-4	_	_	_	_
5-6	_	_	-	_
7-8	_	_	-	_
9–10	_	_	_	_
11-12	_	_	BE_SPI_MOSI	BE_SPI_CLK
13-14	_	_	BE_SPI_CS	BE_SPI_MISO
15-16	_	_	-	_
17-18	-	-	-	-
19-20	_	_	_	_
21-22	-	-	-	-
23-24	-	-	-	-
25-26	-	-	-	-
27-28	-	-	-	-
29-30	GND	GND	GND	GND
31-32	GND	GND	GND	GND
33-34	-	-	-	-
35-36	RD_SPI_CLK	-	ANT_VCC	ANT_VCC
37-38	RD_SPI_MISO	-	-	-
39-40	RD_SPI_MOSI	RD_SPI_CS	_	-
41-42	PL_I2C_SDA	-	-	-
43-44	PL_I2C_SCL	-	_	-
45-46	OBDH_VCC	OBDH_VCC	BAT_VCC	BAT_VCC
47-48	-	_	-	-
49-50	-	-	-	-
51-52	-	-	_	_

Table 4.1: PC-104 bus pinout.

Signal	Pin(s)	Used By	Description
GND	H1-29, H1-30, H1-31, H1-32,	All	Ground reference
	H2-29, H2-30, H2-31, H2-32		
BAT_VCC	H2-45, H2-46	EPS	Battery terminals (+)
ANT_VCC	H2-35, H2-36	EPS, ANT	Antenna power source (3.3 V)
OBDH_VCC	H1-45, H1-46	EPS, OBDH	OBDH power source (3.3 V)
RD_SPI_CLK	H1-35	OBDH, TTC	CLK signal of the main radio SPI bus
RD_SPI_MISO	H1-37	OBDH, TTC	MISO signal of the main radio SPI bus
RD_SPI_MOSI	H1-39	OBDH, TTC	MOS signal of the main radio SPI bus
RD_SPI_CS	H1-40	OBDH, TTC	CS signal of the main radio SPI bus
PL_I2C_SDA	H1-41	OBDH,	SDA signal of the Payload I2C
		Payload*	bus
PL_I2C_SCL	H1-43	OBDH,	SCL signal of the Payload I2C
		Payload*	bus

Table 4.2: PC-104 bus signal description.

Subsystems

.

5.1 On-Board Data Handling

OBDH

5.2 Telemetry, Tracking and Command Module

TTC

5.3 Electrical Power System

EPS

5.4 Attitude Determination and Control System

ADCS

5.5 Mechanical Structure

.

5.6 Payloads

5.6.1 Environmental Data Collection

EDC

Ground Segment

Operation Planning