Relational algebra

Given two relations R and S, where R contains m tuples and S contains n tuples, $m \geq n > 0$, give the minimum and maximum possible sizes (in tuples) for the result of each of the following expressions. In each case, state any assumptions about the schemas needed to make the expression meaningful

- 1. $R \cup S$
- 2. $R \cap S$
- 3. R S
- 4. $R \times S$
- 5. $\sigma_{A=5}R$
- 6. $\pi_A R$
- 7. R/S

Solutions

1. $R \cup S$: m + n, m

2. $R \cap S$: n, 0

3. R - S: m, 0

4. $R \times S$: mn

5. $\sigma_{A=5}R$: m, 0

6. $\pi_A R$: m, 1 (m, m, when R has schema R(A))

7. R/S: m, 0

Consider the following schema

```
Suppliers(sid: integer, sname: string, address: string)
```

Parts(pid: integer, pname: string, colour: string)

Catalog(sid:integer, pid: integer, cost: real)

You can abbreviate the relation names as S, P, and C

Find the names of suppliers who supply some red part

$$\pi_{\mathtt{sname}}(\sigma_{\mathtt{colour}=`red"}S\bowtie P\bowtie C)$$

Suppliers(sid: integer, sname: string, address: string)

Parts(pid: integer, pname: string, colour: string)

Catalog(sid:integer, pid: integer, cost: real)

Find the sids of suppliers who supply some red or green part

Suppliers(sid: integer, sname: string, address: string)

Parts(pid: integer, pname: string, colour: string)

Catalog(sid:integer, pid: integer, cost: real)

Find the sids of suppliers who supply some red or green part

$$\pi_{\text{sid}}(\sigma_{\text{colour}='red', \vee \text{colour}='green'}P \bowtie C)$$

Suppliers(sid: integer, sname: string, address: string)

Parts(pid: integer, pname: string, colour: string)

Catalog(sid:integer, pid: integer, cost: real)

Find the sids of suppliers who supply some red part or are at 221 Packer Ave

 $\pi_{\texttt{sid}}\sigma_{\texttt{colour}=`red`\lor \texttt{address}=`221PackerAve`}(P\bowtie C\bowtie S)$

Suppliers(sid: integer, sname: string, address: string)

Parts(pid: integer, pname: string, colour: string)

Catalog(sid:integer, pid: integer, cost: real)

Find the sids of suppliers who supply some red part and some green part.

1. $R_1 = \pi_{\text{sid}} \sigma_{\text{colour}='red'}(P \bowtie C)$

2. $R_2 = \pi_{\text{sid}} \sigma_{\text{colour='}green'}(P \bowtie C)$

3. Solution: $R_1 \cap R_2$

Suppliers(sid: integer, sname: string, address: string)

Parts(pid: integer, pname: string, colour: string)

Catalog(sid:integer, pid: integer, cost: real)

Find the sids of suppliers who supply every part

1. All part ids: $R=\pi_{\mathrm{pid}}(C)$

2. All pairs of sid and pid: $S=\pi_{\mathrm{pid},\mathrm{sid}}(C)$

3. Solution: S/R

Suppliers(sid: integer, sname: string, address: string)

Parts(pid: integer, pname: string, colour: string)

Catalog(sid:integer, pid: integer, cost: real)

Find the sids of suppliers who supply every red part

1. All red parts: $R = \pi_{\mathrm{pid}}\sigma_{\mathrm{colour}=`red`}(C)$

2. All pairs of sid and pid: $S=\pi_{\mathrm{pid},\mathrm{sid}}(C)$

3. Solution: S/R

Suppliers(sid: integer, sname: string, address: string)

Parts(pid: integer, pname: string, colour: string)

Catalog(sid:integer, pid: integer, cost: real)

Find the sids of suppliers who supply every red or green part

1. All red parts: $R_1 = \pi_{ t pid}\sigma_{ t colour=`red`}(C)$

2. All green parts: $R_2 = \pi_{ t pid} \sigma_{ t colour=`green'}(C)$

3. All pairs of sid and pid: $S=\pi_{\mathrm{pid},\mathrm{sid}}(C)$

4. Solution: $S/(R_1 \cup R_2)$

Suppliers(sid: integer, sname: string, address: string)

Parts(pid: integer, pname: string, colour: string)

Catalog(sid:integer, pid: integer, cost: real)

Find the sids of suppliers who supply every red part or supply every green part

Solution

1. All red parts: $R_1 = \pi_{pid}\sigma_{colour='red'}(C \bowtie P)$

2.
$$S_1 = \pi_{\texttt{pid},\texttt{sid}}(C)$$

3. Supply all red parts: $T_1 = S_1/R_1$

4. All green parts: $R_2 = \pi_{ t pid} \sigma_{ t colour='green'}(C \bowtie P)$

5. $S_2 = \pi_{pid,sid}(C)$

6. Supply all red parts: $T_1 = S_2/R_2$

7. Solution $T_1 \cup T_2$

Suppliers(sid: integer, sname: string, address: string)

Parts(pid: integer, pname: string, colour: string)

Catalog(sid:integer, pid: integer, cost: real)

Find pairs of sids such that the supplier with the first sid charges more for some part than the supplier with the second sid

$$1.\ R = \pi_{\texttt{pid},\texttt{sid},\texttt{cost}}(P\bowtie C)$$

2.
$$R' = \rho(\mathtt{sid} \to \mathtt{sid1}, \mathtt{cost} \to \mathtt{cost1}), R)$$

3.
$$T = R \bowtie R'$$

4. Solution: $\pi_{\text{sid}, \text{sid}1} \sigma_{\text{cost}>\text{cost}1}(T)$

Suppliers(sid: integer, sname: string, address: string)

Parts(pid: integer, pname: string, colour: string)

Catalog(sid:integer, pid: integer, cost: real)

Find the pids of parts supplied by at least two different suppliers

1.
$$R1 = C$$

2.
$$R2 = C$$

3. $\pi_{\text{R1.pid}}\sigma_{\text{R1.pid}=\text{R2.pid}\land\text{R1.sid}\neq\text{R2.sid}}(R1\times R2)$

Suppliers(sid: integer, sname: string, address: string)

Parts(pid: integer, pname: string, colour: string)

Catalog(sid:integer, pid: integer, cost: real)

Find the pids of the most expensive parts supplied by suppliers named Yosemite Sham

1.
$$R_1 = \pi_{ exttt{sid}} \sigma_{ exttt{sname}=\text{`YosemiteSham'}} S$$

2.
$$R_2 = R_1 \bowtie C$$

3.
$$R_3 = R_2$$

4.
$$R_4 = \sigma_{R_3.\mathtt{cost} < R_2.\mathtt{cost}}(R_3 \times R_2)$$

5. Solution:
$$\pi_{\text{pid}}(R_2) - \pi_{R_3.\text{pid}}(R_4)$$

Suppliers(sid: integer, sname: string, address: string)

Parts(pid: integer, pname: string, colour: string)

Catalog(sid:integer, pid: integer, cost: real)

Find the pids of parts supplied by every supplier at less than \$200. (If any supplier either does not supply the part or charges more than \$200 for it, the part is not selected.)

1.
$$R = \pi_{\texttt{pid}, \texttt{sid}} \sigma_{\texttt{cost} < 200}(S \bowtie P \bowtie C)$$

2. Solution: $\pi_{\mathrm{pid}}(R/\pi_{\mathrm{sid}}P)$