

# Sealed Lead-Acid Batteries<sup>1</sup>

## Overview<sup>2</sup>

Rechargeable sealed lead-acid batteries are ideal for use as a secondary (standby) power source as defined by NFPA 72. Their low maintenance and high energy density make them ideal for fire alarm signaling applications.

## Standard Features<sup>4</sup>

- Rechargeable<sup>5</sup>
- Non-spillable
- Non-hazardous
- Low maintenance
- High energy density

## Application<sup>6</sup>

When multiple power supplies are provided, each power supply's battery requirements should be calculated individually. Consult the specific system manual to determine battery capacity requirements.

## Safety Information<sup>8</sup>

Due to a battery's low internal resistance and high power density, high levels of short circuit current can develop across battery terminals. Put on protective eye covering and remove all jewelry before working on batteries. Do not rest tools or cables on the battery, and only use insulated tools. Follow all manufacturers installation instructions and diagrams when installing or maintaining batteries.

## Specifications <sup>1</sup>

Case Material	ABS Thermoplastic	<sup>2</sup>
Regulatory Information	DOT Class 60, Batteries, non-hazardous, non-spillable	
Operating Environment	32° F to 120° F (0° C to 49° C) 0 to 93% RH, Non-condensing	

## Ordering Information <sup>3</sup>

Catalog Number	Description	Shipping Weight, lb (kg)	<sup>4</sup>
12V4A	4.5 Ah Sealed Lead Acid Battery - 12 Vdc	5 (2.27)	
12V6A5	7.2 Ah Sealed Lead Acid Battery - 12 Vdc	6 (2.72)	
6V8A	8 Ah Sealed Lead Acid Battery - 6 Vdc	4 (1.81)	
6V10A	12 Ah Sealed Lead Acid Battery - 6 Vdc	5 (2.27)	
12V10A	11 Ah Sealed Lead Acid Battery - 12 Vdc	10 (4.45)	
12V17A	18 Ah Sealed Lead Acid Battery - 12 Vdc	13 (5.90)	
12V24A	26 Ah Sealed Lead Acid Battery - 12 Vdc	20 (9.07)	
12V40A	40 Ah Sealed Lead Acid Battery - 12 Vdc	32 (14.51)	
12V50A	50 Ah Sealed Lead Acid Battery - 12 Vdc	40 (18.14)	
12V65A	65 Ah Sealed Lead Acid Battery - 12 Vdc	49 (22.23)	